

1 Identification of substance

- **Product details**
- **Trade name** EPOXY FAS 100 DPM RED Comp. A
EPOXY FAS 100 DPM BLUE Comp. A
- **Article number:** 099003, 099103
- **Application of the substance / the preparation** Coating
- **Manufacturer/Supplier:**
Remmers Baustofftechnik GmbH
Postfach 1255
D-49624 Lönningen / Germany
Tel.: 05432/83-0
Fax: 05432/3985
- **Informing department:**
Product Safety department: Tel.: +49 (0)5432/83-138/-538
E-Mail: sales@remmers.co.uk
- **Emergency information:**
during working hours:
U.K.: Tel.: +44 (0) 845 373 0103
Far East: Tel.: +65(0) 67410277
Head Office Germany: Tel.: +49 (0)5432 83 185
after working hours: Tel.: +49 (0)171/6428-297

2 Hazards identification

- **Hazard designation:**



Xi Irritant
N Dangerous for the environment

- **Information pertaining to particular dangers for man and environment**

R 36/38 Irritating to eyes and skin.

R 43 May cause sensitisation by skin contact.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Contains epoxy constituents. See information supplied by the manufacturer.

- **Classification system**

The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

- **GHS label elements**



Danger

H350 - May cause cancer.



Warning

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H317 - May cause an allergic skin reaction.

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 03.11.2010

Revision: 01.11.2010

Trade name **EPOXY FAS 100 DPM RED Comp. A**
EPOXY FAS 100 DPM BLUE Comp. A

(Contd. of page 1)



H411 - Toxic to aquatic life with long lasting effects.

Contains epoxy constituents. May produce an allergic reaction.

• **Prevention:**

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

• **Response:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

• **Storage:**

Store locked up.

• **Disposal:**

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

• **Chemical characterization**

• **Description:** Modified epoxide resin

• **Dangerous components:**

CAS: 25068-38-6 NLP: 500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700) Xi, N; R 36/38-43-51/53 Warning: exclamation mark 3.2/2, 3.3/2, 3.4.S/1 environment 4.1.C/2	60-80%
CAS: 28064-14-4	Bisphenol-F-Epichlorhydrin-Harze MG < 700 Xi, N; R 36/38-43-51/53 Warning: exclamation mark 3.2/2, 3.3/2, 3.4.S/1 environment 4.1.C/2	10-20%
CAS: 100-51-6 EINECS: 202-859-9	Benzyl alcohol Xn; R 20/22 Warning: exclamation mark 3.1.O/4, 3.1.I/4	5-10%

• **Additional information** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

• **General information**

Immediately remove any clothing soiled by the product.

In case of irregular breathing or respiratory arrest, provide artificial respiration.

• **After inhalation**

Use a respiration bag or breathing device.

In case of unconsciousness bring patient into stable side position for transport.

• **After skin contact**

Wash immediately with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

• **After eye contact** Rinse opened eye for several minutes under running water.

• **After swallowing**

Rinse out mouth and then drink plenty of water.

(Contd. on page 3)

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 03.11.2010

Revision: 01.11.2010

Trade name **EPOXY FAS 100 DPM RED Comp. A**
EPOXY FAS 100 DPM BLUE Comp. A

(Contd. of page 2)

Do not induce vomiting; call for medical help immediately.

5 Fire fighting measures

- **Suitable extinguishing agents**
Water spray jet
Carbon dioxide
Foam
- **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
- **Special hazards caused by the material, its products of combustion or flue gases:**
Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:
Hydrogen chloride (HCl)
further harmful conflagration gases and fumes
- **Protective equipment:** Wear self-contained breathing apparatus.
- **Additional information**
Cool endangered containers with water spray jet.
Collect contaminated fire fighting water separately. It must not enter drains.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

- **Person-related safety precautions:**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- **Measures for environmental protection:**
Do not allow product to reach sewage system or water bodies.
Do not allow to enter the ground/soil.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.

7 Handling and storage

- **Handling**
- **Information for safe handling:**
Use only in well ventilated areas.
Open and handle container with care.
- **Information about protection against explosions and fires:** Protect from heat.
- **Storage**
- **Requirements to be met by storerooms and containers:** Prevent any penetration into the ground.
- **Information on storage in a common storage facility:**
Store away from oxidizing agents.
Store away from food.
- **Further information about storage conditions:**
Store cool and dry in tightly closed containers.
Store container in a well ventilated position.
Protect from frost.
Protect from heat and direct sunlight.

GB

(Contd. on page 4)

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 03.11.2010

Revision: 01.11.2010

Trade name **EPOXY FAS 100 DPM RED Comp. A**
EPOXY FAS 100 DPM BLUE Comp. A

(Contd. of page 3)

8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with limit values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during compilation were used as a basis.
- **Personal protective equipment**
- **General protective and hygienic measures**
Immediately remove soiled, saturated clothing.
Store protective clothing separately.
Keep away from food, beverages and animal feed.
Do not eat, drink or smoke while working.
Use skin protection cream for preventive skin protection.
Wash hands before pauses and after work.
Avoid contact with eyes and skin.
Do not inhale gases / vapours / aerosols.
- **Respiratory equipment:**
In case of insufficient ventilation, use respiratory protection:
Filter A/P2.
Only use ambient air independent respiratory equipment in pits, shafts and silos!
- **Protection of hands:** Long cuffed gloves
- **Material of gloves** Nitrile rubber, NBR
- **Penetration time of glove material**
Break through time: max. 240 min (DIN EN 374).
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Tightly sealed safety glasses.
- **Body protection:** Protective work clothing.

9 Physical and chemical properties:

· General Information	
Form:	Fluid
Colour:	clear
Odour:	Weak, characteristic
· Change in condition	
Melting point/Melting range: Not determined	
Boiling point/Boiling range: Not determined	
· Flash point:	> 100°C
· Ignition temperature:	435°C
· Decomposition temperature:	> 200°C
· Danger of explosion:	Product is not explosive.
· Density at 20°C	1.150 g/cm ³
· Solubility in / Miscibility with	
Water:	Insoluble

(Contd. on page 5)

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 03.11.2010

Revision: 01.11.2010

Trade name **EPOXY FAS 100 DPM RED Comp. A**
EPOXY FAS 100 DPM BLUE Comp. A

(Contd. of page 4)

· **Viscosity:**
dynamic at 20°C: 1000 mPas

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:**
 No decomposition if used according to specifications.
 No decomposition if handled and stored according to specifications.
- **Materials to be avoided:** Strong acids, strong bases and strong oxidising agents.
- **Dangerous reactions** Exothermic polymerisation
- **Dangerous decomposition products:**
 None if used properly.
 None if stored properly.
 May be released in fire:
 Carbon monoxide and carbon dioxide
 Hydrogen chloride (HCl)
 Phenol

11 Toxicological information

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

Oral	LD50	> 10000 mg/kg (Ratte)
Dermal	LD50	> 2000 mg/kg (Ratte)

100-51-6 Benzyl alcohol

Oral	LD50	1230 mg/kg (Ratte)
Dermal	LD50	2000 mg/kg (Kaninchen)

- **Primary irritant effect:**
- **on the skin:** Irritates skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitisation:** Sensitisation possible by skin contact.
- **Additional toxicological information:**
 The product shows the following dangers based on the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:
 Irritant
- **Sensitisation** May cause sensitisation by skin contact.

12 Ecological information:

- **General notes:**
 Water hazard class 2 : hazardous to water.
 Do not allow product to reach ground water, bodies of water or sewage system.
 according to appendix 4 VwVwS

GB
 (Contd. on page 6)

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 03.11.2010

Revision: 01.11.2010

Trade name **EPOXY FAS 100 DPM RED Comp. A**
EPOXY FAS 100 DPM BLUE Comp. A

(Contd. of page 5)

13 Notes on disposal:

- **Product:**
- **Recommendation**
Do not dispose of together with household garbage. Do not allow product to reach sewage system. Not hardened material must be disposed of as hazardous waste according to official regulations. Hardened product remains may be disposed of as building rubble or put into household garbage. The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· Land transport ADR/RID and GGVs/GGVE (cross-border/domestic)



- **ADR/RID-GGVs/E Class:** 9 (M6) Miscellaneous hazardous substances and articles.
- **Kemler Number:** 90
- **UN-Number:** 3082
- **Packaging group:** III
- **Danger sign:** 9
- **Special marking:** Symbol (fish and tree)
- **Designation of goods:** 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700), Bisphenol-F-Epichlorhydrin-Harze MG < 700)
- **Remarks:** TREM-Card No.93

· Maritime transport IMDG/GGVSea:



- **IMDG/GGVSea Class:** 9
- **UN Number:** 3082
- **Label** 9
- **Packaging group:** III
- **EMS Number:** F-A,S-F
- **Marine pollutant:** No
- **Correct technical name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700))

· Air transport ICAO-TI and IATA-DGR:



- **ICAO/IATA Class:** 9
- **UN/ID Number:** 3082

(Contd. on page 7)

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 03.11.2010

Revision: 01.11.2010



Trade name **EPOXY FAS 100 DPM RED Comp. A**
EPOXY FAS 100 DPM BLUE Comp. A

(Contd. of page 6)

- **Label** 9
- **Special marking:** Symbol (fish and tree)
- **Packaging group:** III
- **Correct technical name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700))
- **UN "Model Regulation":**
UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III

15 Regulatory information

- **Designation according to EC guidelines:**
The product has been classified and labelled in accordance with EC Guidelines / Ordinance on Hazardous Materials (GefStoffV)
- **Code letter and hazard designation of product:**

Xi Irritant
N Dangerous for the environment
- **Hazard-determining components of labelling:**
reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)
Benzyl alcohol
Bisphenol-F-Epichlorhydrin-Harze MG < 700
- **Risk phrases:**
36/38 Irritating to eyes and skin.
43 May cause sensitisation by skin contact.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- **Safety phrases:**
2 Keep out of the reach of children.
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
28 After contact with skin, wash immediately with plenty of soap and water.
37/39 Wear suitable gloves and eye/face protection.
46 If swallowed, seek medical advice immediately and show this container or label.
61 Avoid release to the environment. Refer to special instructions/safety data sheets.
- **Special labelling of certain preparations:**
Contains epoxy constituents. See information supplied by the manufacturer.
- **Product Code:** RE 1
- **National regulations**
- **Water hazard class:**
German Water hazard class 2: hazardous to water.
according to appendix 4 VwVwS

16 Other information:

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

- **Relevant R-phrases**
20/22 Harmful by inhalation and if swallowed.
36/38 Irritating to eyes and skin.
43 May cause sensitisation by skin contact.

(Contd. on page 8)

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 03.11.2010

Revision: 01.11.2010

Trade name EPOXY FAS 100 DPM RED Comp. A
EPOXY FAS 100 DPM BLUE Comp. A

(Contd. of page 7)

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Department issuing data specification sheet:** Product Safety department

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

GB