

P-Seal 3 Floor

Description:

P-Seal 3 Floor is a high quality strong durable cavity drain membrane with a stud profile of 3mm giving it an overall thickness of only 3.5mm. P-Seal Floor can be used as a floor or wall membrane in new build and refurbishment projects. It is an effective barrier against water.

The 3mm stud height minimises problems caused by raised floor levels. The membrane is highly versatile and can also be used in conjunction with thermal insulation, sound insulation and most types of under floor heating.

Although designed as a floor membrane P-Seal 3 Floor is highly versatile and can also be used on walls, with the same fixing technique as other P-Seal membranes and is ideal for use behind stud work or false walls above ground.

P-Seal 3 Floor is guaranteed for 30 years and has a life expectancy of at least 50 years (DIN 9001:2000). P-Seal 3 Floor is an inert product with high compressive loading stability. It is highly resistant to water, alkalis, saline solutions and organic acids, and is not affected by minerals. It is also resistant to bacteria, fungi and other small organisms.

Technical Information:

Size:	2m x 15m, 2m x 30m
Colour:	Yellow
Coverage:	30m ² /60m ²
Packaging:	Individual
Stud Depth:	3mm
Thickness:	0.5mm



Associated Products:

- P-Seal Quick Plugs - for fixing the membrane to walls
- P-Seal Brick Plugs - for fixing the membrane to walls
- P-Seal Plaster Plugs - for fixing meshed membrane to walls
- P-Seal Cob Plugs - for fixing the membrane to poorer quality substrate such as cob walls
- P-Seal Rope - for sealing plugs
- P-Seal Tape - for sealing membrane joints
- P-Seal Corner Strip – for sealing wall/floor joints or protrusions through the membrane
- P-Seal Drainage Channel, Floor Drain and Aquaduct – for removal of water to evacuation points

All Permagard products are of a high quality and subject to rigid quality control. The company, however, cannot govern the conditions of usage and application of its products and any warranty, written or implied covers material only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss, injury or patent infringement arising from its use. With the publication of this Technical Data Sheet all previous editions are no longer valid.

Permagard Products Limited

Chittening Industrial Estate, Avonmouth, Bristol. BS11 0YB.

Tel: 0117 9381596

Web: www.pemagard.co.uk

Email: sales@permagard.co.uk