

P-Seal Brick Plugs

Description:

P-Seal Brick Plugs are used to secure P-Seal System membranes to building substrates and to fix battens or tracking systems. Before using P-Seal Brick Plugs either wrap a bead of P-Seal Rope around the back of the head of the plug to form a compression seal or put a P-Seal Brick Plug Washer onto the plug to again form a compression seal when the plugs are fixed.

P-Seal Plugs are recommended when fixing P-Seal 8 Clear or P-Seal 8 Mesh to vaulted arches.



Technical Details:

Size: 10mm x 75mm

Colour: Black

Coverage:

Packaging: Bag of 100

Stud Depth:

Thickness:

Associated Products:

- P-Seal Quick Plugs - for fixing the membrane to walls
- P-Seal Plaster Plugs - for fixing meshed membrane to walls
- P-Seal Cob Plugs - for fixing the membrane to poorer quality substrate such as cob walls
- P-Seal Rope - for sealing plugs
- P-Seal Tape - for sealing membrane joints
- P-Seal Corner Strip – for sealing wall/floor joints or protrusions through the membrane
- P-Seal Drainage Channel, Floor Drain and Aquaduct – for removal of water to evacuation points

All Permagard products are of a high quality and subject to rigid quality control. The company, however, cannot govern the conditions of usage and application of its products and any warranty, written or implied covers material only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss, injury or patent infringement arising from its use. With the publication of this Technical Data Sheet all previous editions are no longer valid.

Permagard Products Limited

Chittingen Industrial Estate, Avonmouth, Bristol. BS11 0YB.

Tel: 0117 9381596

Web: www.pemagard.co.uk

Email: sales@permagard.co.uk