

P-Seal 8 Clear

Description:

P-Seal 8 Clear is a high quality cavity drain waterproofing membrane suitable for use internally below ground to retaining walls, vaulted soffits and floors. P-Seal 8 Clear is the most commonly used membrane within the P-Seal Waterproofing range of products. Please see the P-Seal Installation Manual for details of fixing and finishing of the product.

P-Seal 8 Clear is guaranteed for 30 years and has a life expectancy of at least 50 years (DIN 9001:2000). P-Seal 8 Clear is an inert product with high compressive loading stability. It is highly resistant to water, alkalis, saline solutions and organic acids, and is not affected by minerals. It is also resistant to bacteria, fungi, and other small organisms.

Our innovative P-Seal Quick Plug is used when fitting the P-Seal 8 Clear to the wall and if a below ground waterproofing system is being installed then it should be used with our Drainage Channel, Floordrain or Aquaduct perimeter drainage systems.

Technical Information:

Size:	2m, 2.4m x 20m
Colour:	White/Transparent
Coverage:	40m ² /48m ²
Packaging:	Individual
Stud Depth:	8mm
Thickness:	0.65mm



Associated Products:

- P-Seal Quick Plugs - for fixing the membrane to walls
- P-Seal Brick Plugs - for fixing the membrane to walls
- P-Seal Plaster Plugs - for fixing meshed membrane to walls
- P-Seal Cob Plugs - for fixing the membrane to poorer quality substrate such as cob walls
- P-Seal Rope - for sealing plugs
- P-Seal Tape - for sealing membrane joints
- P-Seal Corner Strip – for sealing wall/floor joints or protrusions through the membrane
- P-Seal Drainage Channel, Floor Drain and Aquaduct – for removal of water to evacuation points

All Permagard products are of a high quality and subject to rigid quality control. The company, however, cannot govern the conditions of usage and application of its products and any warranty, written or implied covers material only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss, injury or patent infringement arising from its use. With the publication of this Technical Data Sheet all previous editions are no longer valid.

Permagard Products Limited

Chittening Industrial Estate, Avonmouth, Bristol. BS11 0YB.

Tel: 0117 9381596

Web: www.pemagard.co.uk

Email: sales@permagard.co.uk