

## P-Seal 8 Mesh

### Description:

P-Seal 8 Mesh is a high quality meshed membrane and is part of the Perma-Seal Range. It is one of the toughest and thickest on the market today and is made from 0.65mm high density polyethylene, able to withstand everyday site impact damage.

The P-Seal 8 Mesh should be chosen as a wall membrane if a dot and dab plasterboard finished is required and also provides an excellent substrate for lime mortars, renders and plasters. The square design of the 8mm studs is perfect for corner detailing and managing any protrusions or nibs on the wall surface and it outperforms other diamond stud membranes from other manufacturers.

Our innovative P-Seal Quick Plug is used when fitting the P-Seal 8 Mesh to the wall and if a below ground waterproofing system is being installed then it should be used with our Drainage Channel, Floordrain or Aquaduct perimeter drainage systems.

P-Seal 8 has a 30 year guarantee against deterioration with a life expectancy of at least 50 years (DIN 9001:2000)

### Technical Information:

<b>Size:</b>	2m x 20m
<b>Colour:</b>	White/Transparent
<b>Coverage:</b>	40m <sup>2</sup>
<b>Packaging:</b>	Individual
<b>Stud Depth:</b>	8mm
<b>Thickness:</b>	0.65mm



### Associated Products:

- P-Seal Quick Plugs - for fixing the membrane to walls
- P-Seal Brick Plugs - for fixing the membrane to walls
- P-Seal Plaster Plugs - for fixing meshed membrane to walls
- P-Seal Cob Plugs - for fixing the membrane to poorer quality substrate such as cob walls
- P-Seal Rope - for sealing plugs
- P-Seal Tape - for sealing membrane joints
- P-Seal Corner Strip – for sealing wall/floor joints or protrusions through the membrane
- P-Seal Drainage Channel, Floor Drain and Aquaduct – for removal of water to evacuation points

All Permagard products are of a high quality and subject to rigid quality control. The company, however, cannot govern the conditions of usage and application of its products and any warranty, written or implied covers material only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss, injury or patent infringement arising from its use. With the publication of this Technical Data Sheet all previous editions are no longer valid.

### Permagard Products Limited

Chittening Industrial Estate, Avonmouth, Bristol. BS11 0YB.

Tel: 0117 9381596

Web: [www.pemagard.co.uk](http://www.pemagard.co.uk)

Email: [sales@permagard.co.uk](mailto:sales@permagard.co.uk)