

## P-Seal 3 Mesh

### Description:

P-Seal 3 Mesh is a high quality meshed membrane suitable for use as a damp-proofing membrane above the ground both internally or externally. It can also be used as a waterproofing membrane below the ground as part of the Perma-Seal Waterproofing System. Having a 3mm stud means that P-Seal 3 Mesh only has an overall thickness of 3.5mm and is therefore the preferred meshed membrane where space is of a premium.

P-Seal 3 Mesh has a high quality meshed surface which provides an excellent 'key' for lime mortars, renders, plasters or dabbled plasterboard. Please see the P-Seal Mesh installation instructions for details of fixing and finishing of the product.

P-Seal 3 Mesh is guaranteed against deterioration for 30 years and has a life expectancy of at least 50 years (DIN 9001:2000). It is an inert product with high compressive loading stability. It is highly resistant to water, alkalis, saline solutions and organic acids and is not affected by minerals. It is also resistant to bacteria, fungi and other small organisms.

### Technical Information:

<b>Size:</b>	1m, 2m x 20m
<b>Colour:</b>	White/Transparent
<b>Coverage:</b>	20m <sup>2</sup> /40m <sup>2</sup>
<b>Packaging:</b>	Individual
<b>Stud Depth:</b>	3mm
<b>Thickness:</b>	0.5mm



### Associated Products:

- P-Seal Quick Plugs - for fixing the membrane to walls
- P-Seal Brick Plugs - for fixing the membrane to walls
- P-Seal Plaster Plugs - for fixing meshed membrane to walls
- P-Seal Cob Plugs - for fixing the membrane to poorer quality substrate such as cob walls
- P-Seal Rope - for sealing plugs
- P-Seal Tape - for sealing membrane joints
- P-Seal Corner Strip – for sealing wall/floor joints or protrusions through the membrane
- P-Seal Drainage Channel, Floor Drain and Aquaduct – for removal of water to evacuation points

All Permagard products are of a high quality and subject to rigid quality control. The company, however, cannot govern the conditions of usage and application of its products and any warranty, written or implied covers material only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss, injury or patent infringement arising from its use. With the publication of this Technical Data Sheet all previous editions are no longer valid.

### Permagard Products Limited

Chittening Industrial Estate, Avonmouth, Bristol. BS11 0YB.

Tel: 0117 9381596

Web: [www.pemagard.co.uk](http://www.pemagard.co.uk)

Email: [sales@permagard.co.uk](mailto:sales@permagard.co.uk)