

P-Seal Drainage Channel

Description:

P-Seal Drainage Channel is used to relieve hydrostatic water pressure and is installed below flooring membranes at the floor wall junction.

P-Seal Drainage channel is installed at the floor wall junction. P-Seal Drainage Channel provides for efficient dispersal of water around the perimeter of the structure and when used with jetting eyes P-Seal Drainage Channel constitutes a fully maintainable system which complies with BS 8102.



Technical Details:

Size:	2m lengths
Colour:	White
Coverage:	
Packaging:	Individual
Stud Depth:	
Thickness:	

Associated Products:

- P-Seal Quick Plugs - for fixing the membrane to walls
- P-Seal Brick Plugs - for fixing the membrane to walls
- P-Seal Plaster Plugs - for fixing meshed membrane to walls
- P-Seal Cob Plugs - for fixing the membrane to poorer quality substrate such as cob walls
- P-Seal Rope - for sealing plugs
- P-Seal Tape - for sealing membrane joints
- P-Seal Corner Strip – for sealing wall/floor joints or protrusions through the membrane
- P-Seal Floor Drain and Aquaduct – for removal of water to evacuation points

All Permagard products are of a high quality and subject to rigid quality control. The company, however, cannot govern the conditions of usage and application of its products and any warranty, written or implied covers material only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss, injury or patent infringement arising from its use. With the publication of this Technical Data Sheet all previous editions are no longer valid.

Permagard Products Limited

Chittingen Industrial Estate, Avonmouth, Bristol. BS11 0YB.

Tel: 0117 9381596

Web: www.pemagard.co.uk

Email: sales@permagard.co.uk