

Description:

P-Seal Rope is a black Butyl rope which is used to seal a studded joint between all P-Seal membranes where they overlap.

It is also used to seal fixings in walls and for general use around services or stop ends.

It should be regarded as an excellent general purpose sealing and repair product.



Technical Details:

Size:	4.75m x 10mm
Colour:	Black
Coverage:	
Packaging:	Individual
Stud Depth:	
Thickness:	10mm

Associated Products:

- P-Seal Quick Plugs - for fixing the membrane to walls
- P-Seal Brick Plugs - for fixing the membrane to walls
- P-Seal Plaster Plugs - for fixing meshed membrane to walls
- P-Seal Cob Plugs - for fixing the membrane to poorer quality substrate such as cob walls
- P-Seal Tape - for sealing membrane joints
- P-Seal Drainage Channel, Floor Drain and Aquaduct – for removal of water to evacuation points

All Permagard products are of a high quality and subject to rigid quality control. The company, however, cannot govern the conditions of usage and application of its products and any warranty, written or implied covers material only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss, injury or patent infringement arising from its use. With the publication of this Technical Data Sheet all previous editions are no longer valid.

Permagard Products Limited

Chittingen Industrial Estate, Avonmouth, Bristol. BS11 0YB.

Tel: 0117 9381596

Web: www.pemagard.co.uk

Email: sales@permagard.co.uk