PermaCOAT Liquid Epoxy DPM - Hardener
Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH), as amended

Date of issue: 26/10/2026 Revision date: 26/10/2026 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PermaCOAT Liquid Epoxy DPM HARDENER

Product code: ERDPMT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use: Hardener component of liquid epoxy damp proof membrane.

1.3. Details of the supplier of the safety data sheet

Company name: Permagard Products Limited
Unit B2 - B5 Worthy Road
Chittening Industrial Estate
Avonmouth
Bristol
BS11 0YB

Tel: 0117 982 3282

Fax: 0117 938 1584

Email: Sales@permagard.co.uk

1.4. Emergency telephone number

Emergency tel: 0117 982 3282
9am - 5pm
Monday - Friday

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Sens. 1, Acute Tox. 4, Skin Corr. 1B, Repr. 2, Aquatic Chronic 1

Most important adverse effects: Harmful if swallowed.
Suspected of damaging the unborn child.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard statements: H302 - Harmful if swallowed.
H361d - Suspected of damaging the unborn child.
H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H410 - Very toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS05: Corrosion
GHS07: Exclamation mark
GHS08: Health hazard
GHS09: Environmental



Signal word: Danger

Precautionary statements:

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P405 - Store locked up.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - IF exposed or concerned: Get medical advice/attention.
P310 - Immediately call a POISON CENTER or doctor/physician.
P281 - Use personal protective equipment as required.
P201 - Obtain special instructions before use.
P330 - Rinse mouth.
P264 - Wash hands thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P501 - Dispose of contents/container to an authorised waste collection point

2.3. Other hazards

Other hazards:

Contains: Benzyl alcohol
Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine
Salicylic acid
REACH - Article 57 - 59: The mixture does not contain Substance of Very High Concern (SVHC)

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BENZYL ALCOHOL - REACH registration number: 01-2119492630-38-xxxx

EINECS	CAS	PBT / WEL	CLP Classification	Percent
202-859-9	100-51-6	-	Acute Tox. 4, Eye Irrit. 2; H Statements: H332, H302, H319	25 - 50%

Specific Concentration Limits: No information available; M factor: No information available; Acute toxicity estimate: Not available; Symbols: GHS07

FATTY ACIDS, TALL-OIL, REACTION PRODUCTS WITH BISPHENOL A, EPICHLOROHYDRIN, GLYCIDYL TOLYL ETHER AND TRIETHYLENETETRAMINE - REACH registration number: 01-2119983521-35-0002

EINECS	CAS	PBT / WEL	CLP Classification	Percent
606-078-8	186321-96-0	-	Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H Statements: H315, H317, H318, H400, H410	25 - 50%

Specific Concentration Limits: No information available; M factor: 1; Acute toxicity estimate: Not available; Symbols: GHS09, GHS05, GHS07; M factor, acute: 1

4,4'-ISOPROPYLIDENEDIPHENOL, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE, REACTION PRODUCTS WITH 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE - REACH registration number: 01-2119965165-33-0001

EINECS	CAS	PBT / WEL	CLP Classification	Percent
500-101-4	38294-64-3	-	Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 3; H Statements: H314, H317, H318, H412	10 - 25%

Specific Concentration Limits: No information available; M factor: No information available; Acute toxicity estimate: Not available; Symbols: GHS05. GHS07

SALICYLIC ACID - REACH registration number: 01-2119486984-17-xxxx

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-712-3	69-72-7	-	Acute Tox. 4, Eye Dam. 1, Repr. 2; H Statements: H302, H318, H361d	10 - 25%

Specific Concentration Limits: No information available; M factor: No information available; Acute toxicity estimate: Not available; Symbols: GHS05, GHS07, GHS08

M-PHENYLENEBIS(METHYLAMINE) - REACH registration number: 01-2119480150-50-xxxx

EINECS	CAS	PBT / WEL	CLP Classification	Percent
216-032-5	1477-55-0	-	Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1B, Aquatic Chronic 3; H Statements: H302, H314, H317, H332, H412	5 - 10%

Specific Concentration Limits: No information available; M factor: No information available; Acute toxicity estimate: Not available; Symbols: GHS05, GHS07

3-AMINOPROPYLDIMETHYLAMINE; N, N-DIMETHYL-1,3-DIAMINOPROPANE - REACH registration number: 01-2119486842-27-0000

EINECS	CAS	PBT / WEL	CLP Classification	Percent
203-680-9	109-55-7	-	Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1; H Statements: H226, H302, H314, H317	5 - 10%

Specific Concentration Limits: No information available; M factor: No information available; Acute toxicity estimate: Not available; Symbols: GHS02, GHS05, GHS07

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL - REACH registration number: 01-2119560597-27-xxxx

EINECS	CAS	PBT / WEL	CLP Classification	Percent
202-013-9	90-72-2	-	Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H Statements: H302, H319, H315	5 - 10%

Specific Concentration Limits: No information available; M factor: No information available; Acute toxicity estimate: Not available; Symbols: GHS07

3-AMINOPROPYLTRIETHOXYSILANE - REACH registration number: 01-2119480479-24-xxxx

EINECS	CAS	PBT / WEL	CLP Classification	Percent
213-048-4	919-30-2	-	Acute Tox. 4, Skin Corr. 1B; H Statements: H302, H314	0.1 - 1%

Specific Concentration Limits: No information available; M factor: No information available; Acute toxicity estimate: Not available; Symbols: GHS05, GHS07

SECTION 4: First aid measures

4.1. Description of first aid measures

General information: Take off contaminated clothing.
Symptoms of poisoning from inhalation may not develop for several hours

Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention. In case of unconsciousness place patient stably in side position for transportation. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Skin contact: Seek immediate medical attention After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of soap and water If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. IF exposed or concerned: Get medical advice/attention.

Eye contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention.

Ingestion: Rinse mouth. IF exposed or concerned: Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Eye contact:	No information available
Skin contact:	No information available
Inhalation:	No specific symptoms known.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment:	Immediately call a POISON CENTER or doctor/physician.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Extinguishing media:	Extinguish with foam, carbon dioxide, dry powder or water spray. Use extinguishing media suitable to the surrounding conditions. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards:	No information available

5.3. Advice for fire-fighters

Advice for fire-fighters:	Wear self contained breathing apparatus and full protective clothing

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions:	Wear suitable protective clothing

6.2. Environmental precautions

Environmental precautions:	Do not allow to enter public sewers and watercourses If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

6.3. Methods and material for containment and cleaning up

Clean-up procedures:	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust) Use neutralising agent. Dispose of this material as hazardous waste. Ensure adequate ventilation Collect spillage.

6.4. Reference to other sections

Reference to other sections:	For personal protection see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements:	Ensure adequate ventilation Handle and open container with care Prevent formation of aerosols Wash contaminated clothing before reuse. Dispose of contents/container to an authorised waste collection point

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions:	Store in original, correctly labelled and tightly closed containers Store locked up.

7.3. Specific end use(s)

Specific end use(s):	No information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Table key: DNEL = derived no-effect level; PNEC = predicted no-effect concentration; WEL = workplace exposure limit; ILV = indicative limit value. TWA = time-weighted average; STEL = short-term exposure limit.

BENZYL ALCOHOL				
Type	**Exposure**	**Duration**	**Population**	**Effect**
DNEL	Oral	Acute	-	systemic effects: 20 mg/kg bw/day (general population)
DNEL	Oral	Long term	-	systemic effects: 4 mg/kg bw/day (general population)

BENZYL ALCOHOL				
Type	**Exposure**	**Duration**	**Population**	**Effect**
DNEL	Dermal	Acute	-	systemic effects: 20 mg/kg bw/day (general population) : 40 mg/kg bw/day (worker)
DNEL	Dermal	Long term	-	systemic effects: 4 mg/kg bw/day (general population) : 8 mg/kg bw/day (worker)

BENZYL ALCOHOL				
Type	**Exposure**	**Duration**	**Population**	**Effect**
DNEL	Inhalative	Acute	-	systemic effects: 27 mg/m³ (general population) : 110 mg/m³ (worker)
DNEL	Inhalative	Long term	-	systemic effects: 5.4 mg/m³ (general population) : 22 mg/m³ (worker)

BENZYL ALCOHOL				
Type	**Exposure**	**Duration**	**Population**	**Effect**
PNEC	Aqua	-	-	1 mg/l (fresh water) : 0.1 mg/l (marine water)
PNEC	Sediment	-	-	5.27 mg/kg (fresh water) : 0.527 mg/kg (marine water)
PNEC	STP	-	-	39 mg/l (sewage)
PNEC	Soil	-	-	0.456 mg/kg soil dw (soil)

FATTY ACIDS, TALL-OIL, REACTION PRODUCTS WITH BISPHENOL A, EPICHLOROHYDRIN, GLYCIDYL TOLYL ETHER AND TRIETHYLENETETRAMINE				
Type	**Exposure**	**Duration**	**Population**	**Effect**
DNEL	Dermal	Long term	-	systemic effects: 1 mg/kg bw/day (worker)

FATTY ACIDS, TALL-OIL, REACTION PRODUCTS WITH BISPHENOL A, EPICHLOROHYDRIN, GLYCIDYL TOLYL ETHER AND TRIETHYLENETETRAMINE				
Type	**Exposure**	**Duration**	**Population**	**Effect**
DNEL	Inhalative	Long term	-	systemic effects: 7.05 mg/m³ (worker)

FATTY ACIDS, TALL-OIL, REACTION PRODUCTS WITH BISPHENOL A, EPICHLOROHYDRIN, GLYCIDYL TOLYL ETHER AND TRIETHYLENETETRAMINE				
Type	**Exposure**	**Duration**	**Population**	**Effect**
PNEC	Aqua	-	-	0.000186 mg/l (fresh water) : 0.000019 mg/l (marine water)
PNEC	Sediment	-	-	0.005 mg/kg (fresh water) : 0.0005 mg/kg (marine water)
PNEC	STP	-	-	1.58 mg/l (sewage)
PNEC	Soil	-	-	11.1 mg/kg soil dw (soil)

4,4'-ISOPROPYLIDENEDIPHENOL, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE, REACTION PRODUCTS WITH 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE				
Type	**Exposure**	**Duration**	**Population**	**Effect**
DNEL	Oral	Long term	-	systemic effects: 0.05 mg/kg bw/day (general population)

4,4'-ISOPROPYLIDENEDIPHENOL, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE, REACTION PRODUCTS WITH 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE				
Type	**Exposure**	**Duration**	**Population**	**Effect**
DNEL	Dermal	Long term	-	systemic effects: 0.05 mg/kg bw/day (general population) : 0.14 mg/kg bw/day (worker)

4,4'-ISOPROPYLIDENEDIPHENOL, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE, REACTION PRODUCTS WITH 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE				
Type	**Exposure**	**Duration**	**Population**	**Effect**
DNEL	Inhalative	Long term	-	systemic effects: 0.074 mg/m³ (genneral population) : 0.493 mg/m³ (workers)

4,4'-ISOPROPYLIDENEDIPHENOL, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE, REACTION PRODUCTS WITH 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE				
Type	**Exposure**	**Duration**	**Population**	**Effect**
PNEC	Aqua	-	-	0.111 mg/l (intermittent releases) : 0.011 mg/l (fresh water) : 0.001 mg/l (marine water)
PNEC	Sediment	-	-	4.320 mg/kg (fresh water) : 432 mg/kg (marine water)
PNEC	STP	-	-	10 mg/l (sewage)
PNEC	Soil	-	-	864 mg/kg soil dw (soil)
PNEC	Oral	-	-	1 mg/kg food (secondary poisoning)

M-PHENYLENEBIS(METHYLAMINE)				
Type	**Exposure**	**Duration**	**Population**	**Effect**
DNEL	Dermal	Long term	-	systemic effects: 0.33 mg/kg bw/day (worker)

M-PHENYLENEBIS(METHYLAMINE)				
Type	**Exposure**	**Duration**	**Population**	**Effect**
DNEL	Inhalative	Long term	-	systemic effects: 1.2 mg/m³ (worker)
DNEL	Inhalative	Long term	-	local effects: 0.2 mg/m³ (worker)

M-PHENYLENEBIS(METHYLAMINE)				
Type	**Exposure**	**Duration**	**Population**	**Effect**
PNEC	Aqua	-	-	0.094 mg/l (fresh water) : 0.009 mg/l (marine water)
PNEC	Sediment	-	-	0.43 mg/kg (fresh water) : 0.043 mg/kg (marine water)
PNEC	STP	-	-	10 mg/l (sewage)
PNEC	Soil	-	-	0.045 mg/kg soil dw (soil)

3-AMINOPROPYLDIMETHYLAMINE; N,N-DIMETHYL-1,3-DIAMINOPROPANE				
Type	**Exposure**	**Duration**	**Population**	**Effect**
DNEL	Inhalative	Long term	-	systemic effects: 1.2 mg/m³ (worker)
DNEL	Inhalative	Long term	-	local effects: 1.2 mg/m³ (worker)

3-AMINOPROPYLDIMETHYLAMINE; N,N-DIMETHYL-1,3-DIAMINOPROPANE				
Type	**Exposure**	**Duration**	**Population**	**Effect**
PNEC	Aqua	-	-	0.34 mg/l (intermittent releases) : 0.0728 mg/l (fresh water) : 0.00728 mg/l (marine water)
PNEC	Sediment	-	-	0.735 mg/kg (fresh water)

3-AMINOPROPYLDIMETHYLAMINE; N,N-DIMETHYL-1,3-DIAMINOPROPANE				
Type	**Exposure**	**Duration**	**Population**	**Effect**
PNEC	Exposure limit	-	-	0.0735 mg/kg (marine water)
PNEC	STP	-	-	69.5 mg/l (sewage)
PNEC	Soil	-	-	0.104 mg/kg soil dw (soil)

8.2. Exposure controls

Exposure controls:

Keep away from food, drink and animal feedingstuffs
Wash hands thoroughly after using this substance
Avoid contact with skin and eyes
In case of inadequate ventilation wear respiratory protection.
Wear suitable protective clothing, eye/face protection and gloves
Wear PVC gloves
Wear goggles giving complete eye protection
Remove contaminated clothing

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	Colour:	Colourless to yellow
Odour:	Amine odour	Melting point/Range:	Not available
Boiling Point/Range:	No data available	Flammability:	No information available
Lower explosive limit:	1.3 Vol% (in air)	Upper explosive limit:	13.0 Vol% (in air)
Flashpoint:	>93°C	Autoignition Temperature:	Product is not selfigniting
Decomposition temperature:	NA	pH:	No information available
Kinematic viscosity:	NA mm²/s	Solubility:	NA
Vapour Pressure:	0.1 hPa at 20°C	Density:	1.00 - 1.03 g/cm³
Vapour Density:	Not available	Particle characteristics:	NA
Solubility in water:	Partly miscible with water		

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No information available

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity: No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Chemical stability: Considered stable under normal conditions

10.3. Possibility of hazardous reactions

Hazardous reactions: Reacts with acids

10.4. Conditions to avoid

Conditions to avoid: No information available

10.5. Incompatible materials

Materials to avoid: No information available

10.6. Hazardous decomposition products

Haz. decomp. products: No hazardous decomposition products known

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Table key: ORL = oral; DRM = dermal; SKN = skin; INH = inhalation. RAT = rat; RBT = rabbit; MUS = mouse. LD50 / LC50 = median lethal dose / concentration; ATE = acute toxicity estimate.

BENZYL ALCOHOL

Route	Species	Endpoint	Value	Unit
ORL	RAT	LD50	1,620	mg/kg
DRM	RBT	LD50	2,000	mg/kg

M-PHENYLENEBIS(METHYLAMINE)

Route	Species	Endpoint	Value	Unit
ORL	MUS	LD50	1,180	mg/kg
SKN	RAT	LD50	> 3,100	mg/kg

3-AMINOPROPYLDIMETHYLAMINE; N,N-DIMETHYL-1,3-DIAMINOPROPANE

Route	Species	Endpoint	Value	Unit
ORL	RAT	LD50	410	mg/kg
SKN	RAT	LD50	400 - 2000	mg/kg
DRM	RBT	LD50	2,139	mg/kg
INH	RAT	LC50	21.9	mg/l/4h

Endocrine disrupting properties: No information available

Information on other hazards: No information available

SECTION 12: Ecological information

12.1. Toxicity

Table key: LC50 / EC50 = median lethal / effect concentration; NOEC = no observed effect concentration. Values and units are shown as supplied.

BENZYL ALCOHOL

Species / test	Endpoint	Value	Unit
(Pimephales Promelas) (96h)	LC50	460	mg/l
(Daphnia Magna) (48h)	EC50	230	mg/l
(Algae) (72h)	EC50	770	mg/l

M-PHENYLENEBIS(METHYLAMINE)

Species / test	Endpoint	Value	Unit
(leuciscus idus) (96h)	LC50	87.6	mg/l
(Daphnia Magna) (21d)	LC50	6.77	mg/l
(Daphnia Magna) (24h)	EC50	35.1	mg/l
(Daphnia Magna) (48h)	EC50	15.2	mg/l
(Algae) (72h)	EC50	20.3	mg/l
(Daphnia Magna) (21d)	EC50	8.4	mg/l

4,4'-ISOPROPYLIDENEDIPHENOL, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE, REACTION PRODUCTS WITH 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

Species / test	Endpoint	Value	Unit
(Daphnia Magna) (48h)	LC50	11.1	mg/l
(Daphnia Magna) (96h)	LC50	11.1	mg/l
(Fish) (96h)	LC50	11.1	mg/l
(Algae) (72h)	EC50	79.4	mg/l

3-AMINOPROPYLDIMETHYLAMINE; N,N-DIMETHYL-1,3-DIAMINOPROPANE

Species / test	Endpoint	Value	Unit
(leuciscus idus) (96h)	LC50	122	mg/l
(Pseudomonas Putida) (17h)	EC50	94.5	mg/l
(Daphnia Magna) (48h)	EC50	59.5	mg/l
(Scenedesmus Subspicatus) (72h)	EC50	53.3	mg/l
(Pseudokirchneriella Subcapitata) (72h)	EC50	34	mg/l

12.2. Persistence and degradability

Persistence and degradability: No information available

12.3. Bioaccumulative potential

Bioaccumulative potential: No information available

12.4. Mobility in soil

Mobility: No information available

12.5. Results of PBT and vPvB assessment

PBT identification: No information available
Endocrine disrupting properties
No information available

12.6. Other adverse effects

Other adverse effects: No information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Disposal should be in accordance with local, state or national legislation
Avoid release to the environment. Refer to special instructions/Safety data sheets
Do not empty into drains - dispose of this material and container in a safe way
Dispose of contents/container to an authorised waste collection point

SECTION 14: Transport information

The transport classifications below apply to air (ICAO/IATA), road/rail (ADR/RID) and sea (IMDG).

14.1. UN number

UN number: 1760

14.2. UN proper shipping name

Proper shipping name: CORROSIVE LIQUID, N.O.S.

14.3. Transport hazard class(es)

Transport hazard class: 8

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmental hazards:	No information available Marine Pollutant

14.6. Special precautions for user

Road/rail (ADR/RID)

Limited quantity (LQ):	IL
Excepted quantity (EQ):	Code: E2
Maximum net quantity per inner packaging:	30 ml
Maximum net quantity per outer packaging:	500 ml
ADR transport category:	2
Tunnel Code:	E
Hazard Identification Number:	80 (ADR/RID)
EmS:	F-A, S-B
Contains:	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3- epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine m-phenylenebis(methylamine)

14.7. Maritime transport in bulk

Annex II of MARPOL / IBC Code:	No information available
IMO instruments:	No information available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations:	This Safety Data Sheet is provided in compliance with the EC Regulations 1907/2006, 1272/2008, 2015/830 and 2020/878 Prohibition/Restriction REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: None. REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None. REACH - List of substances subject to authorisation (Annex XIV) : None.

15.2. Chemical Safety Assessment

Chemical safety assessment:	A chemical safety assessment (CSA) for this product has not yet been completed

SECTION 16: Other information

Other information

Other information:

Prepared on 26/10/2026 using the supplier safety data sheet dated 22/01/2025, version 2.1.0. Product identification and supplier details have been updated for PermaCOAT Liquid Epoxy DPM.

Phrases used in s.2 and s.3:

Full text of hazard statements referenced in Sections 2 and 3:
H226: Flammable liquid and vapour.
H302: Harmful if swallowed.
H314: Causes severe skin burns and eye damage.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H318: Causes serious eye damage.
H319: Causes serious eye irritation.
H332: Harmful if inhaled.
H361d: Suspected of damaging the unborn child.
H400: Very toxic to aquatic life.
H410: Very toxic to aquatic life with long lasting effects.
H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer:

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.