

PermaPROTECT Mould Resistant Paint



Description

PermaPROTECT Mould Resistant Paint is a high quality acrylic based emulsion paint which when applied, provides a rich satin finish. The paint is specially formulated and contains an active film fungicide which will prevent any future growth of moulds or algae.

The fungicide is highly active against black spot and mould growth (*Asperillus Niger*) usually associated with condensation and high humidity environments. The coating is effective for both internal and external surface applications and the fungicide will not leach out, even when wiped.

PermaPROTECT Mould Resistant Paint helps maintain a healthy living environment and drastically reduces the need for redecoration in areas where condensation is an issue.

Benefits of use

- Easy application by brush or roller
- Recoat in just 4 hours
- No need for repeat redecoration
- Water based low VOC formula
- Advanced mould resistant layer
- Prevents mould growth for up to 5 years
- Improved atmosphere for asthma sufferers
- Durable and hard wearing
- Easy to clean, wipeable surface
- Premium matt finish

Technical Details

<i>Mould Resistant Paint</i>	Technical Details
<i>Material</i>	Water based acrylic paint
<i>Size of bucket</i>	5 Litre
<i>Colour</i>	Brilliant White / Magnolia
<i>Temp range</i>	5°C to 30°C
<i>Number of coats</i>	2
<i>Drying time</i>	2-4 hours @ 20°C
<i>Coverage</i>	8-10 m ² per litre (2 coats)

Substrate Preparation

Preparation is similar to normal good decorative practice.

- Protect non target surfaces with dust sheets.
- Remove any loose material such as old paint, grease, dirt, mould or defective wallpaper.
- If mould is present, thoroughly clean the area using a Mould Wash and allow to dry thoroughly.
- For glossy surfaces, lightly abrade the surface with abrasive paper avoiding inhalation of dust and wearing suitable personal protective equipment (face mask, gloves, safety glasses etc).
- If necessary, apply an appropriate primer or sealer. Allow to dry thoroughly. New plasterwork should be allowed to dry for 7-14 days before applying any paint finish.

Mixing

Ensure the area is well ventilated. Stir the paint thoroughly before use.

Application

Apply two coats with a brush or roller, leave 4 hours between coats. Do not apply in very damp or humid conditions or extreme temperatures. PermaPROTECT Mould Resistant Paint must be left as the final finish and not overcoated with other finishes.

Packaging

5 litre buckets

Coverage

- Apply at a rate of 8-10m² per litre per coat
- 5 litre bucket 20-25m² (two coats)

Cleaning Equipment

Remove paint from the brush or roller with a cloth then rinse until clean with water. Spillages should be cleaned up immediately whilst still wet. Reseal bucket after use.

Recycle & Disposal

Any leftover paint can be donated to a **Community RePaint** centre. Every small donation can help benefit individuals, families, communities and charities in need. You can find out how by visiting www.communityrepaint.org.uk

Empty containers should be disposed of at a special waste collection point or accordance with local/national regulations.

Storage

PermaPROTECT Mould Resistant Paint should be protected from frost and freezing and stored in ambient conditions between 5°C and 25°C.

Health and Safety

Full health and safety data are given in the Product Safety Data Sheet.