

PermaSEAL 8 Clear

Description:

PermaSEAL 8 Clear is a high quality HPDE cavity drain waterproofing membrane suitable for use internally above and below ground to retaining walls, vaulted soffits and floors. PermaSEAL 8 Clear is the most commonly used membrane within the PermaSEAL Waterproofing range of products. Please see the PermaSEAL Installation Manual for details of fixing and finishing of the product.

PermaSEAL 8 Clear is guaranteed for 30 years and has a life expectancy of at least 50 years (DIN 9001:2000). PermaSEAL 8 Clear is an inert product with high compressive loading stability. It is highly resistant to water, alkalis, saline solutions and organic acids, and is not affected by minerals. It is also resistant to bacteria, fungi, and other small organisms.

Our innovative PermaSEAL Quick Plug is used when fitting the PermaSEAL 8 Clear to the wall and if a below ground waterproofing system is being installed then it should be used with our Drainage Channel or Floor drain perimeter drainage systems.



Associated Products:

- PermaSEAL Quick Plugs - for fixing the membrane to walls
- PermaSEAL Brick Plug Super - for fixing the membrane to walls and vaulted ceilings
- PermaSEAL Cob Plugs - for fixing the membrane to poorer quality substrate such as cob walls
- PermaSEAL Tape - for sealing overlap membrane joints
- PermaSEAL Overtape – for single sided taped butt or overlap joints
- PermaSEAL Corner Strip – for sealing wall/floor joints or protrusions through the membrane
- PermaSEAL Drainage Channel, Floor Drain – for removal of water to evacuation points
- PermaSEAL Sump and Pump Systems – for evacuating water ingress to a controlled area

Technical Details:

Size:	2m x 20m, 2.4m x 20m
Colour:	Clear
Coverage:	40m ² , 48m ²
Compressive Strength:	>200kN/m ²
Stud Depth:	8mm
Thickness:	0.7mm
Volume between Studs:	5.5 Litres/m ²
Drainage Capacity:	4.6 Litres/ sec/m ²
Vicat Softening Temp:	126°C



All Permagard products are of a high quality and subject to rigid quality control. The company, however, cannot govern the conditions of usage and application of its products and any warranty, written or implied covers material only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss, injury or patent infringement arising from its use.

Permagard Products Limited Chittening Industrial Estate, Avonmouth, Bristol. BS11 0YB.
T: 0117 982 3282 W: www.permagard.co.uk E: sales@permagard.co.uk

