

Description:

Platon P5 is a tough and economical membrane for both remedial and new build construction. It is suitable for sub-ground tanking and also for use above ground to isolate walls which are damp or contaminated with salts.

Platon P5 can be dry lined on walls and screeded or a floating dry board system fitted on floors.

Features:

- Economical 5mm HDPE cavity drain membrane
- Suitable for both walls and floors, above or below ground
- Impermeable to water, gas and water vapour
- Compatible with other Platon membranes

Specification:

In accordance with NBS Specification J40 (clause 290)
– Flexible Sheet Tanking/Damp Proofing

Associated Products:

- Platon Brick Plugs - for fixing the membrane to walls
- Platon Plaster Plugs - for fixing meshed membrane to walls
- Platon Rope - for sealing plugs
- Platon Tape - for sealing membrane joints
- Platon Corner Strip – for sealing wall/floor joints or protrusions through the membrane
- Platon Aqua Channel – for removal of water to evacuation points



Technical Details:

Size:	2.07m x 20m x 5mm
Colour:	Clear
Coverage:	40m ²
Packaging:	Roll
Stud Depth:	5mm
Thickness:	Nominal 0.50mm

All Permagard products are of a high quality and subject to rigid quality control. The company, however, cannot govern the conditions of usage and application of its products and any warranty, written or implied covers material only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss, injury or patent infringement arising from its use. With the publication of this Technical Data Sheet all previous editions are no longer valid.

Permagard Products Limited

Chittening Industrial Estate, Avonmouth, Bristol. BS11 0YB.

Tel: 0117 9381596

Web: www.pemagard.co.uk

Email: sales@permagard.co.uk