

Easi-Fix Helical Drive Tie Basic SDS Installation Tool



Description

The Easi-Fix Helical Drive Tie Basic SDS Installation Tool is designed as a cost effective alternative to the Professional Tool where limited quantities of wall ties are to be installed. The tool is a two part tool which allows the user to effectively drive the Easi-Fix Helical Drive Tie into the substrate before adding the second section to countersink the tie below the masonry.


Benefits

- Easy to use
- Economically viable for small projects
- Suitable for up to 200 ties
- Fits SDS drills

Installation Method




1. Insert (part 1) of the Easi-Fix Helical Drive Tie SDS Basic Installation into the SDS hammer drill, then set to hammer only. Place the wall tie into the adaptor and offer to the pre-drilled substrate.



2. With the drill set on hammer mode only drive the wall tie fully home until the shoulder of the Easi-Fix Helical Drive Tie SDS Basic Installation Tool hits the substrate.



3. Insert (part 2) the embedment tip into the Easi-Fix Helical Drive Tie SDS Basic Installation Tool.



4. Locate the end of the tie into the embedment tip, then drive the tie fully home until the tie is below the surface of the substrate. Close the installation hole with colour matching mortar or resin.

All Permagard® products are of a high quality and subject to rigid quality control. The company, however, cannot govern the conditions of usage and application of its products and any warranty, written or implied covers material only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss, injury or patent infringement arising from its use.

Permagard Products Ltd
Units B2-B5, Worthy Road
Chittening Industrial Estate
Avonmouth
Bristol, BS11 0YB