

HydroCoat 103 2K Part A

High Performance Liquid Waterproofing Membrane

SECTION 1. Identification of the Substance/Mixture and of the Company/Undertaking

Product Identifier

- Product form Mixture
- Product name HydroCoat 103 2K
- Product codes 103-S

Relevant identified uses of the substance and uses advised against

- Use of substance/mixture Professional Use only
Internal and external waterproofing
- Uses advised against Not for any other use

Details of the Supplier of the Safety Data Sheet

- Company Address Newton Waterproofing Systems, Newton House, 17-19 Sovereign Way, Tonbridge, Kent TN9 1RH
- Web www.newtonwaterproofing.co.uk
- Email address of the competent person info@newtonwaterproofing.co.uk
- Emergency telephone numbers Newton Waterproofing systems - English language
+44 (0)1732 360095/08:00-17:30 (GMT) Mon-Thur & 08:00-17:00 (GMT) Fri

SECTION 2. Hazards Identification

- Refer to SECTION 16 for The explanation of the abbreviations used throughout this SDS
The full list of Hazard Phrases & Precautionary Statements stated throughout this SDS

2.1 Classification of the Substance or Mixture

- Classification under Regulation (EC) No. 1272/2008 (CLP)
Not classified
- Adverse physicochemical, human health and environmental effects
See SECTION 11 for information on health effects and symptoms

2.2 Label Elements

- Hazard statements No labelling applicable
- Signal words (CLP) N/A
- Hazard pictograms (CLP) N/A
- Hazardous ingredients N/A
- Hazard statements (CLP) N/A
- Precautionary statements (CLP) To be handled and used in accordance with good occupational hygiene and safety practice. Wear PPE as SECTION 8.2, handle and store as SECTION 7, manage accidental release as SECTION 6 and follow the instructions in the Data Sheet
- Supplemental label elements Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC No. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC No. 220-239-6] (3.1 and 1, 2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety Data Sheet available on request

HydroCoat 103 2K Part A

High Performance Liquid Waterproofing Membrane

2.3 Other Hazards

- Other Hazards NDA
- Other information Classification and labelling have been made on the basis of safety data sheets of the raw materials that make up the product

SECTION 3. Composition/information on ingredients

3.2 Mixture This product is a mixture

Hazardous Substances

| Chemical name | CAS | REACH Registration Number | % | Classification according to Regulation (EC) No. 1272/2008 (CLP) |
|---|---|---------------------------|---------|--|
| 1,2-benzisothiazol-3(2H)-one | CAS: 2634-33-5 EC: 220-33-5 Index: 613-088-00-6 | | <0.025 | Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10) |
| Reaction mass of:5-chloro-2-mthyl-4-isothiazolin-3-one [EC No. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC No. 220-239-6] (3.1) | CAS: 55965-84-9 Index: 613-167-00-5 | | <0.0015 | Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1B, H314 Skin Sens.. 1, H317 Acute Tox. 3, H400 (M =1) Acute Chronic 1, H410 (M=1) |

NB Refer to SECTION 8 for Occupational Exposure Limits & Controls and Personal Protection

Refer to SECTION 16 for the full text of Hazard Statements

There are no additional ingredients present, which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, or are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this SECTION.

SECTION 4. First Aid Measures

4.1 Description of First Aid Measures

- General
 - Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice. If exposed or concerned get medical advice / attention. If you feel unwell, seek medical advice
 - Those assisting the exposed persons to take no action involving personal risk or without training. Performing mouth-to-mouth can be dangerous, only to be done by trained personnel
 - Eye bathing equipment and First Aid Box should be available
 - Take this SDS with you when seeking medical advice
- Skin contact
 - Remove contaminated clothing. Gently remove all traces of product and wash with plenty of soap and water. Continue to rinse for at least 10 minutes. If skin irritation or rash occurs seek medical advice / attention. Do NOT use solvents or thinners
- Eye contact
 - Do not rub. Immediately rinse eyes cautiously with plenty of water for at least 15 minutes holding the eyelids open. Remove contact lenses if present

HydroCoat 103 2K Part A

High Performance Liquid Waterproofing Membrane

- Ingestion
and easy to do so, then continue to rinse copiously for 15 minutes. Obtain medical attention if pain, irritation, blinking or redness persists
If swallowed, seek medical advice immediately and show the container or label, and this SDS. Keep person warm and at rest. Do NOT induce vomiting. If vomiting occurs, the head should be kept forward and low so vomit does not enter the lungs. Never give anything to an unconscious person. Move the exposed person to fresh air. If unconscious, place in the recovery position and get medical advice immediately. Loosen tight clothing such as collar, tie, belt and waistband. Seek medical advice if you feel unwell
- Inhalation
Immediately ventilate the area and remove person from the contaminated place to rest in fresh air and keep comfortable and breathing. Assure fresh air breathing. Loosen tight clothing such as collar, tie, belt or waistband. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If you feel unwell seek medical advice
- Self-protection for first aiders
No action to be taken involving any personal risk or without suitable training. If it is suspected that the mixture is still present, wear appropriate Personal Protection Equipment, see SECTION 8.2. Wear gloves to remove contaminated clothing, see SECTION 13 for washing or disposal

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Potential acute health effects:

- Skin contact No known significant effects or critical hazards
- Eye contact No known significant effects or critical hazards
- Ingestion No known significant effects or critical hazards
- Inhalation No known significant effects or critical hazards
- Delayed / immediate effects NDA

Over-exposure signs / symptoms:

- Skin contact No specific data
- Eye contact No specific data
- Ingestion No specific data
- Inhalation No specific data

4.3 Indication of Any Immediate Medical Attention and Special Treatment Needed

- Immediate / special treatment No specific treatment. Treat symptomatically. Contact poison centre immediately if large quantities have been ingested or inhaled

SECTION 5. Fire-Fighting Measures

- 5.1 Extinguishing Media** Use an extinguishing agent suitable for the surrounding fire
Unsuitable extinguishing media:
- None known

5.2 Special Hazards Arising from the Material

In a fire or if heated, a pressure increase will occur and the container may burst

5.3 Advice for Firefighters

Isolate the affected area

All persons to be immediately removed from the vicinity of the fire. Fire to be dealt with by trained personnel and without involving personal risk

Exercise caution when fighting any chemical fire

Collect the fire fighting water separately. Prevent from entering the environment, waterways, sewers and drains, alert the Environmental Agency if this occurs

HydroCoat 103 2K Part A

High Performance Liquid Waterproofing Membrane

Do not enter the area without wearing appropriate protective equipment and self-contained breathing apparatus (SCBA) with full face-piece operated in positive pressure mode. Clothing, including helmets, protective boots and gloves, conforming to EN 469 will provide a basic level of protection for chemical incidents

SECTION 6. Accidental Release Measures

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

- **General measures**

Do not attempt to take action without wearing suitable personal protection, refer to SECTION 8.2 of the SDS

Ensure adequate ventilation
- **Non-emergency personnel**

Evacuate unnecessary personnel
- **Emergency personnel**

Do not touch or walk through the spilled material. Ventilate spillage area. Do not breathe dust / fumes/ gas / vapours / mist / spray. Avoid contact with skin and eyes

Evacuate unnecessary personnel and those not wearing the suitable protection. If outside do not approach from downwind. If outside keep bystanders and passing persons upwind and away from the danger point. Mark out the contaminated area with signage and prevent access by unauthorised persons

Do not attempt to take action without suitable protective equipment. Equip clean-up crew with proper protection, see SECTION 8 'Exposure controls / personal protection'

Ensure adequate ventilation, including forced ventilation if in an internal space and necessary, and vent externally to be safely away from other persons and the general public

Turn leaking containers leak-side up to prevent the escape of material, and place in a sealable leak proof container, label this with the contents

Avoid inhalation of vapours, wear respiratory protection as SECTION 8.2

6.2 Environmental Precautions

Prevent the product from contact with soil and from entering drains, sewers, watercourses, basements or confined spaces (refer to SECTION 11). Contain the spillage using bunding

Alert the Environmental Agency in the event of spillage, etc. entering water ways, sewers or drains

6.3 Methods and Materials for Containment and Cleaning Up

Clean-up should ONLY be dealt with by qualified persons familiar with the specific product

Stop the leak / spillage if it is safe to do so

Large spillages should be contained by bunding using absorbent materials and carefully transferred into sealable impervious containers. Remnants from large spillages and small spillages should be absorbed and transferred into these containers

Appropriate bunding / absorbent materials: sand, sawdust, universal absorbent and diatomaceous earth

All washings to be retained within the bunding and fully collected up into sealable impervious waste container(s), label these with the contents

All contaminated bunding, including all suspected of being contaminated, to be collected up and transferred to these waste containers

All containers to be labelled and held for disposal as SECTION 13

6.4 Reference to Other Sections

Refer to SECTIONS 1 (Emergency contact), 8 (Personal Protection / Exposure Controls), 12 (Ecological Information) and 13 (Disposal Consideration)

HydroCoat 103 2K Part A

High Performance Liquid Waterproofing Membrane

SECTION 7. Handling and Storage

The information in the SECTION includes generic advice and guidance. The list of 'Relevant identified uses' in SECTION 1 should be consulted for any available use-specific information provided here and in SECTION 8

7.1 Precautions for Safe Handling

- a. Safe handling
- Wear protective equipment as required by use- see SECTION 8
- Do not get in eyes, on skin or on clothing - see SECTION 8 for the protection of work clothing. Do not ingest. Obtain special instructions before use. Do not handle or use until all safety precautions have been read and understood.
- Only use outdoors or in well ventilated areas, wear appropriate respirator when ventilation is inadequate. Keep in original container, kept tightly closed when not in use
- Do not breathe vapours, aerosols or gases
- b. Hygiene measures
- Do not eat, drink or smoke when handling. Wash hands and other exposed areas with mild soap and water after using the material and remove contaminated clothing and protective equipment before entering areas where food and drink are consumed and when leaving the work site
- Contaminated work clothing should be securely bagged before being allowed out of the work site. See SECTION 13 for the protection of work clothing and the washing or disposal of contaminated work clothing and boots. Wash hands and face before eating, drinking, smoking and using the toilet
- c. Prevention of handling incompatible substances or mixtures
- Do not handle other substances or mixtures at the same time. Keep away from other substances and mixtures
- d. Operations and conditions that could create new risks
- Do not allow opened, part used or the container in use to come into contact with other materials including all surfaces around. Ensure the containers are securely sealed during transport, storage and when at the work site
- e. Reduce risk of release to the environment
- Avoid spillage. Ensure the floor at storage, transport and the work location will not allow access to drains or water courses. Lay heavy gauge plastic sheeting or similarly impervious protective covering when mixing and dispensing. Contain and clean up spillage as SECTION 6.3 of the SDS

7.2 Conditions for Safe Storage, Including Any Incompatibilities

- a. Storage conditions
- Store in a well ventilated locked area, keep cool, away from direct sunlight and in accordance with local regulations. Only store in original containers. Keep container tightly closed. Do not store in unlabelled containers, if transferred to another container include the Batch Number and Manufacturing or Expiry Date on the new label. The floor of the storage area to be impermeable to prevent the escape of spillage
- b. Maximum storage period
- Maximum storage period (shelf life): 12 months from date of manufacture when stored at 20°C (68°F)
- Use of the stock must be by manufacturing date or expiry date rotation. Containers past their expiry date must be removed for disposal according to SECTION 13 of the SDS
- c. Control of the effects of weather, ambient pressure, temperature, sunlight, humidity and vibration
- Protect from freezing, frost, heat and direct sunlight. Keep away from sources of ignition, open flames or excessive heat
- Ensure containers are securely closed against vibration spillage during transport when loading / unloading vehicles, during transport and moving from vehicle to the work location. Unopened containers to be protected

HydroCoat 103 2K Part A

High Performance Liquid Waterproofing Membrane

against damage during these movements

d. Storage with other substances and mixtures

Only store in the original packaging. Store against falling / touching other materials and in an allocated location

e. Storage room design, quantity limits, ventilation and packaging compatibilities

Storage room to be dry, ventilated, and constructed to have impermeable floors and walls to prevent the escape of spillages into the environment

f. Other considerations

No other data available

7.3 Specific End Use(es)

Part A of a 2-Part liquid applied cementitious waterproofing membrane. Refer to the Technical Data Sheet for further information

SECTION 8. Personal Protection/Exposure Control

The information in this SECTION contains generic advice and guidance and is based on typical anticipated uses of the product. Additional measures might be required for bulk handling or uses other than those described in the Technical Data Sheet that could significantly increase worker exposure or environmental releases

8.1 Control Parameters

Workplace Exposure Limits (WEL)

EH40: Taken from the HSE EH40/2005 (3rd edition, published 2018):

- not stated = not on EH40
- if no 15 min STEL, 3x TWA used

Carc: Capable of causing cancer and / or heritable genetic damage

Sen: Capable of causing occupational asthma

Sk: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systematic toxicity

| Substance & CAS | Long-term exposure limit (8hr TWA reference period) | | Short-term exposure limit (15 minute reference period) | | Comments | Source |
|-----------------------------|---|---------------------|--|---------------------|----------|--------|
| | ppm | mg / m ³ | ppm | mg / m ³ | | |
| No exposure limits known | | | | | | HSE |
| NDA - not on the EH40 Table | | | | | | |

DNELs / DMELs

No DNELs / DMELs available

PNECs

No PNECs available

8.2 Exposure Controls

8.2.1 Appropriate Engineering Controls

a. Ventilation

Ensure there is sufficient ventilation in the area, including forced ventilation if necessary or in an internal or enclosed space with safe exhaust away from other persons. The floor must be impermeable to prevent the escape of liquids, laying impermeable protective covering if in doubt

b. Isolation

Isolate the work area with warning signage against unauthorised access. Ensure all other persons are pre-notified of the works and remain clear of the work area

c. Washing

Provide eye wash facilities, individual eye wash ampoules and safety shower

d. Against contamination

Refer to SECTION 15.1 for any 'Other Regulations' and the REACH Annex XVII statements there
Only mix the 2 Parts of the product on impervious protective sheeting and with this laid at the area(s) where the mixed product is to be applied, against splashes onto the person(s) performing this task, any other persons and onto

HydroCoat 103 2K Part A

High Performance Liquid Waterproofing Membrane

the surrounding areas:

- When opening each Part and when progressively mixing them together
- When using the power mixer / paddle off a drill, include erecting barrier around if necessary to stop splashes off the protective sheeting onto other persons, structures, ground, etc
- When applying the mixed product to the area(s) to be treated
- The person(s) performing this to wear disposable overshoes over their safety work boots when working off the protective sheeting against walking contamination onto the surrounding area
- When the mixing is done, dispose of the contaminated protective sheeting, the overshoes, etc as controlled waste

e. Mists

Prevent the formation of vapour or aerosol

f. Hygiene & Occupational care

Do not eat, drink or smoke during stirring or use of the product. Wash hands, face and if uncover forearms with soap and water before eating, drinking, smoking, using the toilet and when leaving the work site for natural breaks, break times and at end of day

8.2.2 Personal Protective Equipment

a. Work clothing

Wash contaminated work clothing before reusing. Alternatively wear impervious disposable 1-piece covering to body, legs and arms with closure at wrists and ankles, and disposable overshoes. EN ISO 13688

b. Eye / face protection

Tight fitting safety chemical goggles / safety glasses with side protection or face visor, to EN166

If at risk of splashing to face when mixing the 2-part product wear a full face visor

c. Skin protection

(i) Hand Protection

To be impermeable chemical resistant gloves, resistant to micro-organisms, to EN 374

Material of gloves

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC, this being repealed by EU 2016/425 on 21/04/2018, and the resultant standard EN 374

Recommended: Butyl rubber gloves. The selection of the suitable gloves does not only depend upon the material, but also further marks of quality and varies from manufacturer to manufacturer

Break through, and other characteristics, depending upon material density and the glove type, and must be determined in each case

Gloves to be tightly fitting at the wrists and extend onto the work clothing, see above. Gloves must be inspected prior to each time used and must be replaced when damaged or worn out

Penetration time of gloves

Breakthrough time of the glove material > 4 hours

(ii) Other

Chemical resistant safety boots with external feed for the laces, not holes for the laces

Safety helmet if required, or other head covering, against splashes

Good hygiene measures should be followed at all time

d. Respiratory protection

Mouth & nose filter face mask to EN149:2001, with Face Fit Certification

In the case of inadequate ventilation wear an appropriate gas filter (i.e. type A according to EN 14387). Ensure the filter is within its working limits

Mist formation; wear protection as for inadequate ventilation

e. Thermal hazards

NDA

f. Environmental exposure measures

Avoid release to the environment

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental legislation.

HydroCoat 103 2K Part A

High Performance Liquid Waterproofing Membrane

- g. Hygiene measures
- Apply process engineering modifications, ventilation filters, etc. if required
- Wash thoroughly after handling. Do NOT eat, drink or smoke while using this product. Remove contaminated clothing, see SECTION 13 for the washing or disposal of contaminated clothing

SECTION 9. Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

| | | |
|---|-------------|---|
| • Appearance | (i) Form | Liquid |
| | (ii) Colour | White |
| • Odour | | Faint odour (slight) |
| • Odour threshold | | NDA |
| • pH | | 8 |
| • Melting point/range °C | | NDA |
| • Freezing point/range °C | | NDA |
| • Initial boiling point/range °C | | Lowest known value: 100°C (212°F) (water) |
| • Flash point/self-ignition °C | | Closed cup: 101°C |
| • Evaporation rate | | NDA |
| • Flammability (solid, gas) | | NDA |
| • Flammability limits, lower % | | NDA |
| • Flammability limits, upper % | | NDA |
| • Auto flammability °C | | NDA |
| • Decomposition temperature | | NDA |
| • Explosive properties | | NDA |
| • Explosive limits | | NDA |
| • Oxidising properties | | NDA |
| • Vapour pressure | | NDA |
| • Relative vapour density at 20°C | | NDA |
| • Relative density | | 1.02 |
| • Specific weight | | NDA |
| • Solubility in water | | Soluble in cold water |
| • Partition coefficient n-octanol/water | | NDA |
| • Also soluble in | | NDA |
| • Viscosity, kinematic | | 1123.38 mm ² /s (room temperature) |
| • Viscosity, dynamic | | NDA |
| • VOC g/l | | NDA |

NOTE: The above values related to physiochemical properties are typical values for this product and should not, therefore, be construed as a specification

9.2 Other Information NDA

HydroCoat 103 2K Part A

High Performance Liquid Waterproofing Membrane

SECTION 10. Stability and Reactivity

| | |
|---|---|
| 10.1 Reactivity | No specific test data related to reactivity is available for this product |
| 10.2 Chemical Stability | Stable at room temperature, under recommended transport or storage conditions and when protected against the materials or conditions listed in SECTIONS 10.1 and 10.3 |
| 10.3 Possibility of Hazardous Reactions | Under normal conditions of storage and use (see the Technical Data Sheet), hazardous reactions will not occur |
| 10.4 Conditions to Avoid | No specific data |
| 10.5 Incompatible Materials to Avoid | No specific data |
| 10.6 Hazardous Decomposition Products | Under normal conditions of storage and use, hazardous decomposition products should not be produced |

SECTION 11. Toxicological Information

11.1 Information on Toxicological Effects

In the absence of experimental toxicological data on the product itself, potential health risks were evaluated based on the properties of the constituent substances, according to the criteria from relevant regulations for Classification

- Acute toxicity - Hazardous ingredients

| Substance | Route | Test | Species | Value | Exposure |
|--|-------|------|---------|-------------|----------|
| 1,2-benzisothiazol-3(2H)-one | Oral | LD50 | Rat | 1,020 mg/kg | - |
| Reaction mass of:5-chloro-2-mthyl-4-isothiazolin-3-one [EC No. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC No. 220-239-6] (3.1 | Oral | LD50 | Rat | 53 mg/kg | - |

- Conclusion: NDA

- Irritation / Corrosion - Hazardous ingredients

| Substance | Result | Species | Score | Exposure | Observation |
|--|------------------------|---------|-------|-------------|-------------|
| 1,2-benzisothiazol-3(2H)-one | Skin - mild irritant | Human | - | 48 hours 5% | - |
| Reaction mass of:5-chloro-2-mthyl-4-isothiazolin-3-one [EC No. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC No. 220-239-6] (3.1 | Skin - severe irritant | Human | - | 0.01% | - |

- Conclusion: NDA

- Relevant hazards for product

| Hazard | Negative Symptoms |
|-----------------------------|----------------------|
| Acute toxicity - oral | Harmful if swallowed |
| Skin corrosion / irritation | Harmful to skin |

Other hazards

| Hazard | Basis |
|---------------------------------|-------|
| Respiratory hazard / inhalation | NDA |
| Serious eye damage / irritation | NDA |
| Skin sensitisation | NDA |
| Carcinogenicity | NDA |
| Germ cell mutagenicity | NDA |
| Reproductive toxicity | NDA |

HydroCoat 103 2K Part A

High Performance Liquid Waterproofing Membrane

| | |
|-----------------------------|-----|
| STOT single exposure | NDA |
| STOT repeated exposure | NDA |
| Acute toxicity - dermal | NDA |
| Acute toxicity - inhalation | NDA |
| Aspiration hazard | NDA |

- Viscosity, kinematic 1,123.38 mm²/s (room temperature)
- Potential acute health effects
 - Eye contact - No known significant effects or critical hazards
 - Inhalation - No known significant effects or critical hazards
 - Skin contact - No known significant effects or critical hazards
 - Ingestion - No known significant effects or critical hazards
- Symptoms related to the physical, chemical and toxicological characteristics
 - Eye contact - No specific data
 - Inhalation - No specific data
 - Skin contact - No specific data
 - Ingestion - No specific data
- Delayed and immediate effects as well as chronic effects from short and long-term exposure
 - Short-term exposure
 - Potential immediate effects - NDA
 - Potential delayed effects - NDA
 - Long-term exposure
 - Potential immediate effects - NDA
 - Potential delayed effects - NDA
 - Potential chronic health effects NDA
 - Conclusion NDA
 - General - No known significant effects of critical hazard
 - Carcinogenicity - No known significant effects of critical hazard
 - Mutagenicity - No known significant effects of critical hazard
 - Teratogenicity - No known significant effects of critical hazard
 - Developmental effects - No known significant effects of critical hazards
 - Fertility effects - No known significant effects of critical hazard
- Other information NDA

The product was not tested. The data reported here are based on the manufacturer's SDS which is based on information contained in the safety data sheets of the raw materials that make up the product

SECTION 12. Ecological Information

12.1 Toxicity

| Substance | Species | Test | Result | Exposure | |
|------------------------------|---|------|-----------------------|----------|----------|
| 1,2-benzisothiazol-3(2H)-one | Daphnia - Daphnia magna | EC50 | 1.5 mg/L | Acute | 48 hours |
| | Daphnia - Daphnia magna | EC50 | 97 ppb Fresh water | Acute | 48 hours |
| | Algae - Pseudokirchneriella subcapitata | IC50 | 0.067 mg/L | Acute | 72 hours |
| | Crustaceans - Ceriodaphnia dubia | LC50 | > 10 mg/L Fresh water | Acute | 48 hours |
| | Fish - Ochorhynchus mykiss | LC50 | 1.3 mg/L | Acute | 96 hours |
| | Fish - Oncorhynchus mykiss | LC50 | 167 ppb Fresh water | Acute | 96 hours |

Conclusion / Summary NDA

12.2 Persistence and Biodegradability NDA

12.3 Bioaccumulative Potential NDA

12.4 Mobility in Soil NDA

12.5 Results of PBT & vPvT Assessment N/A

12.6 Other Adverse Effects No known significant effects or critical hazards

HydroCoat 103 2K Part A

High Performance Liquid Waterproofing Membrane

12.7 Additional information

The product was not tested. The data reported here are based on the manufacturer's SDS which is based on information contained in the safety data sheets of the raw materials that make up the product

No other information available

SECTION 13. Disposal Considerations

13.1 Waste Treatment Methods

- Recovery operations: Treat as SECTION 6: Accidental Release Measures
- Disposal operations: Product - dispose at approved waste collection sites as controlled waste
- Disposal of packaging: Plastic 5L screw cap container for controlled waste disposal
- Waste code number: Product: 08 02 01
Packaging, always has remnants: 15 01 02
- Special precautions for the disposal method: Ensure substances or mixtures are not mixed with other materials and if held in the same outer container with other materials all are in separate sealed containers within the outer container
- NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal

SECTION 14. Transport Information

| ADR | IMDG | IATA | ADN | RID |
|--|---------------|---------------|-----|---------------|
| 14.1 UN Number | | | | |
| Not regulated | Not regulated | Not regulated | N/A | Not regulated |
| 14.2 UN proper shipping name | | | | |
| N/A | N/A | N/A | N/A | N/A |
| 14.3 Transport hazard class(es) | | | | |
| N/A | N/A | N/A | N/A | N/A |
| 14.4 Packing group | | | | |
| N/A | N/A | N/A | N/A | N/A |
| 14.5 Environmental hazards | | | | |
| No | No | No | N/A | No |
| No supplementary information available | | | | |

14.6 Special Precautions for User

Always transport in closed containers that secure against damage, Ensure that persons transporting the product know what to do in the event of an accident or spillage

- Overland transport: N/A
- Transport by sea: N/A
- Air transport: N/A
- Inland waterway transport: N/A
- Rail transport: N/A

14.7 Transport in Bulk According to:

Transport in bulk is not available / offered

- (i) Annex II of Marpol: N/A
- (ii) the IBC Code: N/A

HydroCoat 103 2K Part A

High Performance Liquid Waterproofing Membrane

SECTION 15. Regulatory Information

15.1 Safety, Health and Environmental Regulations/Legislation Specific for the Substance, Mixture or Article

COMMISSION REGULATIONS (EC) No 1272/2008 and (EU) No 2015/830 of 28/05/2015 amending Regulation (EC) No 1907/2006 and repealing (EU) 453/2010 20 May 2010 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

- Other regulations, limitations and prohibitive regulations

Contains no REACH substances with Annex XVII restrictions
Contains no REACH Annex XIV substances

15.2 Chemical Safety Assessment

A chemical safety assessment has not been carried out. Data from the component substances is included in this SDS

SECTION 16. Other Information

16.1 Basis of this SDS

The data reported here are based on the manufacturer's SDS which is based on information contained in the safety data sheets of the raw materials that make up the product

16.2 Changes Compared to the Previous Version

| Date | Replaces | Sections | Item | Change | Comment |
|----------|----------|----------|------|-------------|---|
| 12/12/19 | 1.0 | All | All | See Comment | Full re-write, read the entire document |

16.3 Key literature and sources of data

Regulation (EC) 1907/2006
Regulation (EC) No. 1272/2008
Regulation (EU) No. 2015/830
Supplier SDS
ECHA, including REACH dossier for component substances
EH40/2005 3rd Edition, 2018

16.4 Abbreviations & Acronyms

CLP: EU Regulation 1272/2008: Classification, Labelling & packaging of chemical substances
DMEL: Derived Minimal Effect Level
DNEL: Derived No Effect Level
EC50: Concentration giving response half way between baseline and maximum
EINECS: European Inventory of Existing Commercial Chemical Substances or European List of Notified Chemical Substance number
EUH statement: CLP-specific Hazard statement
HSE: (UK) Health & Safety Executive
IBC Code: International Building Code
IC50: half maximal Inhibitory Concentration
LD50: Lethal dose, 50% affected
MARPOL: International Convention for the Prevention of Pollution from Ships
N/A: Not Applicable
NDA: No Data Available
PBT: Persistent, Bioaccumulative and Toxic substances
vPvB: Very Persistent and very Bioaccumulative substances
PNEC: Predicted No-Effect Concentration

HydroCoat 103 2K Part A

High Performance Liquid Waterproofing Membrane

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals: Regulation (EC) No 1907/2006

SDS: Safety Data Sheet

STEL: Short Term Exposure Limit

STOT RE: Specific target organ toxicity (from) repeated exposure

STOT SE: Specific target organ toxicity (from) single exposure

TWA: Time Weighted Averages

VOC: Volatile organic compounds

16.5 Procedure used to derive the Classification according to Regulation (EC) No. 1272/2008

| Classification | Justification |
|----------------|---------------|
| Not classified | |

16.6 Full text of H and EUH statements

| | |
|------|--|
| H301 | Toxic if swallowed |
| H302 | Harmful if swallowed |
| H311 | Toxic in contact with skin |
| H314 | Causes severe eye burns and eye damage |
| H315 | Causes skin irritation |
| H317 | May cause an allergic reaction |
| H318 | Causes serious eye damage |
| H331 | Toxic if inhaled |
| H400 | Very toxic to aquatic life |
| H410 | Very toxic to aquatic life with long lasting effects |

16.7 Full text of Classifications (CLP / GHS)

| | |
|-------------------------|--|
| Acute Tox. 3, H301 | Acute Toxicity (oral) - Category 3 |
| Acute Tox. 3, H311 | Acute Toxicity (dermal) - Category 3 |
| Acute Tox. 3, H331 | Acute Toxicity (inhalation) - Category 3 |
| Acute Tox. 4, H302 | Acute Toxicity (oral) - Category 4 |
| Aquatic Acute 1, H400 | Acute Aquatic Hazard - Category 1 |
| Aquatic Chronic 1, H410 | Long Term Aquatic Hazard - Category 1 |
| Eye Dam. 1, H318 | Serious Eye Damage / Eye Irritation - Category 1 |
| Skin Corr. 1B, H314 | Skin Corrosion / Irritation - Category 1B |
| Skin Irrit. 2, H315 | Skin Corrosion / Irritation - Category 2 |
| Skin Sens. 1, H317 | Skin Sensitisation - Category 1 |

16.8 Training advice

Obtain special instructions and read the Safety Data Sheet before use. Do not handle until all safety precautions have been read and understood. It is recommended that workers are trained in the safe handling of hazardous chemicals

16.9 DISCLAIMER

Persons using the information contained here must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where these purposes are other than as specifically recommended in this Safety Data Sheet and in the Technical Data Sheet, then the user uses the product at their own risk

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best on the Company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the users responsibility to satisfy themselves as to the suitability of such information for their own particular use

HydroCoat 103 2K Part B

High Performance Liquid Waterproofing Membrane

SECTION 1. Identification of the Substance/Mixture and of the Company/Undertaking

Product Identifier

- Product form: Mixture
- Product name: HydroCoat 103 2K
- Product codes: 103-S

Relevant identified uses of the substance and uses advised against

- Use of substance/mixture: Professional use only
Internal and external waterproofing
- Uses advised against: Not for any other use

Details of the Supplier of the Safety Data Sheet

- Company Address: Newton Waterproofing Systems, Newton House, 17-19 Sovereign Way, Tonbridge, Kent TN9 1RH
- Web: www.newtonwaterproofing.co.uk
- Email address of the competent person: info@newtonwaterproofing.co.uk
- Emergency telephone numbers: Newton Waterproofing systems - English language
+44 (0)1732 360095/08:00-17:30 (GMT) Mon-Thur & 08:00-17:00 (GMT) Fri

SECTION 2. Hazards Identification

- Refer to SECTION 16 for: The explanation of the abbreviations used throughout this SDS
The full list of Hazard Phrases & Precautionary Statements stated throughout this SDS

2.1 Classification of the Substance or Mixture



- Classification under Regulation (EC) No. 1272/2008 (CLP)

| | |
|---------------|------|
| Skin Irrit. 2 | H315 |
| Skin Sens. 1 | H317 |
| Eye Dam. 1, | H318 |
| STOT SE 3 | H335 |

 Full text of hazard classes and H-statements: see SECTION 16
- Adverse physicochemical, human health and environmental effects
This product is classified as hazardous according to Regulation (EC) 1272/2008 as amended

2.2 Label Elements

- Signal words (CLP): Danger
- Hazard pictograms (CLP):

| | |
|---|---|
|  |  |
| GHS05 | GHS07 |
- Hazardous ingredients: Cement, Portland cement, chemicals
- Hazard statements (CLP):

| | |
|------|---------------------------|
| H318 | Causes serious eye damage |
| H315 | Causes skin irritation |

HydroCoat 103 2K Part B

High Performance Liquid Waterproofing Membrane

- Precautionary statements (CLP)

H317 May cause an allergic skin reaction
 H335 May cause respiratory irritation

P260 Do not breathe dust, fume, gas, mist, spray, vapours
 P271 Only use outdoors or in a well-ventilated area
 P280 Wear protective gloves / clothing and eye / face protection
 P302+P352 IF ON SKIN: Wash with plenty of water
 P303+P361 IF ON SKIN (or hair): take off immediately all contaminated
 +P353 clothing. Rinse skin with water
 Wash clothing before reuse
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable
 for breathing
 P305+P351 IF IN EYES: Rinse cautiously with water for several minutes.
 +P338 Remove contact lenses, if present and easy to do. Continue
 rinsing
 P333+P313 If skin irritation or rash occurs: Get medical advice / attention
 P405 Store locked up
 P501 Dispose of contents / container to hazardous or special
 waste collection point, in accordance with local, regional, national
 and/or international regulation
- Other

To be handled and used in accordance with good occupational hygiene and safety practice. Wear PPE as SECTION 8.2, handle and store as SECTION 7, manage accidental release as SECTION 6 and follow the instructions in the Data Sheet

2.3 Other Hazards

- PBT / vPvB No additional information available
- Other Hazards NDA
- Other information Classification and labelling have been made on the basis of safety data sheets of the raw materials that make up the product

SECTION 3. Composition/information on ingredients

3.2 Mixture

This product is a mixture

Hazardous Substances

| Chemical name | CAS | EC No. | EC Index-No | REACH Registration Number | % | Classification according to Regulation (EC) No. 1272/2008 (CLP) |
|-----------------------------|------------|-----------|-------------|---------------------------|-----------|---|
| Crystalline silica | 14808-60-7 | 238-878-4 | | | ≥25 - ≤50 | Not classified |
| Cement, Portland, chemicals | 65997-15-1 | 266-043-4 | | | ≥25 - ≤50 | Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Dam. 1, H318 STOT SE 3, H335 |
| Glass, oxide, chemicals | 65997-17-3 | 266-046-0 | | | ≤3 | Not classified |
| Calcium dihydroxide | 1305-62-0 | 215-137-3 | | | ≤3 | Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 3, H412 |

NB Refer to SECTION 8 for Personal Protection / Exposure Controls
 Refer to SECTION 16 for the full text of Hazard Statements

HydroCoat 103 2K Part B

High Performance Liquid Waterproofing Membrane

SECTION 4. First Aid Measures

4.1 Description of First Aid Measures

- **General**

Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice. If exposed or concerned get medical advice / attention. If you feel unwell, seek medical advice

Those assisting the exposed persons to take no action involving personal risk or without training. Performing mouth-to-mouth can be dangerous, only to be done by trained personnel

Eye bathing equipment and First Aid Box should be available

Take this SDS with you when seeking medial advice
- **Skin contact**

Remove contaminated clothing and shoes. Gently remove all traces of product and wash with plenty of soap and water. Continue to rinse for at least 10 minutes. If skin irritation or rash occurs seek medial advice / attention. Do NOT use solvents or thinners
- **Eye contact**

Do not rub. Immediately rinse eyes cautiously with plenty of water for at least 15 minutes holding the eyelids open. Remove contact lenses if present and easy to do so, then continue to rinse cautiously for 15 minutes. Seek immediate medical attention
- **Ingestion**

If swallowed, seek medical advice immediately and show the container or label and this SDS. Keep the person warm and at rest. Do NOT induce vomiting. If vomiting occurs, the head should be kept forward and low so vomit does not enter the lungs.
- **Inhalation**

Ventilate the area. Remove person from the contaminated place to rest in fresh air and keep comfortable and breathing. Assure fresh air breathing. Loosen tight clothing such as collar, tie, belt or waistband. If you feel unwell seek medical advice. Call a doctor or poison centre if you feel unwell
- **Self-protection for first aiders**

No action to be taken involving any personal risk or without suitable training. If it is suspected that the mixture is still present, wear appropriate Personal Protection Equipment, see SECTION 8.2. If suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wear gloves to remove contaminated clothing, see SECTION 13 for washing or disposal

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

- **Skin contact** Adverse symptoms may include pain or irritation, redness, blistering
- **Eye contact** Adverse symptoms may include pain, watering, redness
- **Ingestion** Adverse symptoms may include stomach pains
- **Inhalation** Adverse symptoms may include respiratory tract irritation, coughing
- **Delayed / immediate effects** NDA

4.3 Indication of Any Immediate Medical Attention and Special Treatment Needed

- **Immediate / special treatment** No specific treatment. Treat symptomatically. Contact poison treatment specialist if large quantities have been ingested or inhaled

SECTION 5. Fire-Fighting Measures

- **5.1 Extinguishing Media** Use an extinguishing media suitable for the surrounding fire
Unsuitable extinguishing media: None known

- **5.2 Special Hazards Arising from the Material** No specific fire or explosion hazard

HydroCoat 103 2K Part B

High Performance Liquid Waterproofing Membrane

Decomposition products may include: carbon dioxide, carbon monoxide, sulphur oxides, metal oxide / oxides

5.3 Advice for Firefighters

Isolate the affected area

All persons to be immediately removed from the vicinity of the fire. Fire to be dealt with by trained personnel and without involving personal risk

Exercise caution when fighting any chemical fire

Collect the fire fighting water separately. Prevent from entering the environment, waterways, sewers and drains, alert the Environmental Agency if this occurs

Do not enter the area without wearing proper protective equipment, including respiratory protection

Do not enter the area without wearing appropriate protective equipment and self-contained breathing apparatus (SCBA) with full face-piece operated in positive pressure mode. Clothing, including helmets, protective boots and gloves, conforming to EN 469 will provide a basic level of protection for chemical incidents

SECTION 6. Accidental Release Measures

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

- **General measures**

Do not attempt to take action without wearing suitable personal protection, refer to SECTION 8.2 of the SDS

Ensure adequate ventilation
 - **Non-emergency personnel**

Evacuate unnecessary personnel

Do not touch or walk through the spilled material. Ventilate spillage area. Do not breathe dust / fumes/ gas / vapours / mist / spray. Avoid contact with skin and eyes
 - **Emergency personnel**

Evacuate unnecessary personnel and those not wearing the suitable protection. If outside do not approach from downwind. If outside keep bystanders and passing persons upwind and away from the danger point. Mark out the contaminated area with signage and prevent access by unauthorised persons

Do not attempt to take action without suitable protective equipment. Equip clean-up crew with proper protection, see SECTION 8 'Exposure controls / personal protection'

Ensure adequate ventilation, including forced ventilation if in an internal space and necessary, and vent externally to be safely away from other persons and the general public

Turn leaking containers leak-side up to prevent the escape of material, and place in a sealable leak proof container, label this with the contents

Avoid inhalation of vapours, wear respiratory protection as SECTION 8.2
- ### 6.2 Environmental Precautions
- Prevent the product from contact with soil and from entering drains, sewers or watercourses (refer to SECTION 11). Contain the spillage using bunding
- Alert the Environmental Agency in the event of spillage, etc entering water ways, sewers or drains

6.3 Methods and Materials for Containment and Cleaning Up

Clean-up should ONLY be dealt with by qualified persons familiar with the specific product. Approach from upwind against dust inhalation

Stop the leak if it is safe to do so. Avoid dust generation

Large spillages should be contained by bunding using absorbent materials and carefully transferred into sealable impervious containers. Remnants

HydroCoat 103 2K Part B

High Performance Liquid Waterproofing Membrane

from large spillages and small spillages should be carefully swept up without dust generation and transferred into these containers. Using a vacuum with a HEPA filter will reduce dust dispersal

All collected spillages to be retained within and fully collected up into sealable impervious waste container(s), label these with the contents

If used, all contaminated bunding, including all suspected of being contaminated, to be collected up and transferred to these waste containers

All containers to be labelled and held for disposal as SECTION 13

6.4 Reference to Other SECTIONS

Sections 1 (emergency contact), 8 (Personal Protection/Exposure Controls), 12 (Ecological Information) and 13 (Disposal Consideration) of the SDS

SECTION 7. Handling and Storage

The information in the SECTION includes generic advice and guidance. The list of 'Relevant identified uses' in SECTION 1 should be consulted for any available use-specific information provided here and in SECTION 8

7.1 Precautions for Safe Handling

a. Safe handling

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product

Wear protective equipment as required by use- see SECTION 8

Do not get in eyes, on skin or on clothing - see SECTION 8 for the protection of work clothing. Do not ingest. Obtain special instructions before use. Do not handle or use until all safety precautions have been read and understood.

Only use outdoors or in well ventilated areas, wear appropriate respirator when ventilation is inadequate. Keep in original container, kept tightly closed when not in use

Do not breathe vapours, aerosols or gases

b. Hygiene measures

Do not eat, drink or smoke when handling. Wash hands and other exposed areas with mild soap and water after using the material and remove contaminated clothing and protective equipment before entering areas where food and drink are consumed and when leaving the work site. Wash hands and face before eating, drinking, smoking and using the toilet

Contaminated work clothing should be securely bagged before being allowed out of the work site. See SECTION 13 for the protection of work clothing and the washing or disposal of contaminated work clothing and boots

c. Prevention of handling incompatible substances or mixtures

Do not handle other substances or mixtures at the same time. Keep away from other substances and mixtures

d. Operations and conditions that could create new risks

Do not allow opened, part used or the container in use to come into contact with other materials including all surfaces around. Ensure the containers are securely sealed during transport, storage and when at the work site

e. Reduce risk of release to the environment

Avoid spillage. Ensure the floor at storage, transport and the work location will not allow access to drains or water courses. Lay heavy gauge plastic sheeting or similarly impervious protective covering when mixing and dispensing. Contain and clean up spillage as SECTION 6.3 of the SDS

7.2 Conditions for Safe Storage, Including Any Incompatibilities

a. Storage conditions

Store in a well ventilated locked area, keep cool and away from direct sunlight. Only store in original containers. If transferred to another container include the Batch Number and Manufacturing or Expiry Date on the new label. Keep container tightly closed. The floor of the storage area to be impermeable to prevent the escape of spillage

HydroCoat 103 2K Part B

High Performance Liquid Waterproofing Membrane

- b. Maximum storage period
Maximum storage / use period: 12 months at 20°C (68°F), refer to the container label for the Date of Manufacture, Expiry Date or Best Before Date
Use of the stock should be by date rotation, using the oldest dates first. Containers past their Best Before date should be removed for disposal according to SECTION 13 of the SDS
- c. Control of the effects of weather, ambient pressure, temperature, sunlight, humidity and vibration
Protect from freezing, frost, heat and direct sunlight. Keep away from sources of ignition, open flames or excessive heat
Ensure containers are securely closed against vibration spillage during transport when loading / unloading vehicles, during transport and moving from vehicle to the work location. Unopened containers to be protected against damage during these movements
- d. Storage with other substances and mixtures
Only store in the original packaging. Store against falling / touching other materials and in an allocated location
- e. Storage room design, quantity limits, ventilation and packaging compatibilities
Storage room to be dry, ventilated, and constructed to have impermeable floors and walls to prevent the escape of spillages into the environment
- f. Other considerations
No other data available
- 7.3 Specific End Use(es)
Part B of a 2-Part liquid applied cementitious waterproofing membrane. Refer to the Technical Data Sheet for further information

SECTION 8. Personal Protection/Exposure Control

8.1 Control Parameters

Workplace Exposure Limits (WEL)

EH40: Taken from the HSE EH40/2005 (3rd edition, published 2018):

- not stated = not on EH40
- if no 15 min STEL, 3x TWA used

Carc: Capable of causing cancer and / or heritable genetic damage

Sen: Capable of causing occupational asthma

Sk: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systematic toxicity

| Substance & CAS | Long-term exposure limit (8hr TWA reference period) | | Short-term exposure limit (15 minute reference period) | | Comments | Source |
|---|---|----------------------|--|---------------------|--------------------------|--------|
| | ppm | mg / m ³ | ppm | mg / m ³ | | |
| Crystalline silica - respirable 14808-60-7 | - | 0.1 | - | - | - | EH40 |
| Cement, Portland, chemicals - respirable & inhalable dust 65997-15-1 | - | Inhal 10 Respir 4 | - | - | - | EH40 |
| Glass, oxide, chemicals 65997-17-3 | - | 5 | - | - | - | EH40 |
| Calcium dihydroxide 1305-62-0 | - | 5 1 | - | - 4 | - Respirable fraction | EH40 |

HydroCoat 103 2K Part B

High Performance Liquid Waterproofing Membrane

Recommended monitoring procedures Reference should be made to monitoring standards, such as:

EN 689 Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy

EN 14042 Workplace atmospheres - Guide for the application and use for the assessment of exposure to chemical and biological agents

EN 482 Workplace atmospheres - General requirement for the performance of procedures for the measurement of chemical agents

Reference to national guidance documents for methods for the determination of hazardous substances will also be required

DNELs / DMELs

No DNELs / DMELs available

PNECs

No PNECs available

8.2 Exposure Controls

8.2.1 Appropriate Engineering Controls

a. Ventilation

Ensure there is sufficient ventilation in the area, including forced ventilation if necessary or in an internal or enclosed space with safe exhaust away from other persons. The floor must be impermeable to prevent the escape of liquids, laying impermeable protective covering if in doubt

b. Isolation

Isolate the work area with warning signage against unauthorised access. Ensure all other persons are pre-notified of the works and remain clear of the work area

c. Washing

Provide eye wash facilities, individual eye wash ampoules and safety shower

d. Against contamination

Refer to SECTION 15.1 for any 'Other Regulations' and the REACH Annex XVII statements there

Only mix the 2 Parts of the product on impervious protective sheeting and with this laid at the area(s) where the mixed product is to be applied, against splashes onto the person(s) performing this task, any other persons and onto the surrounding areas:

- When opening each Part and when progressively mixing them together
- When using the power mixer / paddle off a drill, include erecting barrier around if necessary to stop splashes off the protective sheeting onto other persons, structures, ground, etc
- When applying the mixed product to the area(s) to be treated
- The person(s) performing this to wear disposable overshoes over their safety work boots when working off the protective sheeting against walking contamination onto the surrounding area
- When the mixing is done, dispose of the contaminated protective sheeting, the overshoes, etc as controlled waste

e. Mists

Prevent the formation of vapour or aerosol

f. Hygiene & Occupational care

Do not eat, drink or smoke during stirring or use of the product. Wash hands with soap and water before eating, drinking, smoking, using the toilet and when leaving the work site for natural breaks, break times and at end of day. Remove contaminated clothing, see SECTION 13 for the washing or disposal of contaminated clothing

8.2.2 Personal Protective Equipment

a. Work clothing

Impervious disposable 1-piece covering to body, legs and arms with closure at wrists and ankles, and disposable overshoes. EN ISO 13688

b. Eye / face protection

Tight fitting safety goggles, safety glasses with side protection or face visor EN166

c. Skin protection

(i) Hand Protection

To be impermeable and resistant to the product / substance / mixture. Due to missing tests no recommendation to the glove material can be given

HydroCoat 103 2K Part B

High Performance Liquid Waterproofing Membrane

| | |
|------------------------------------|---|
| | Selection of the glove material to be on consideration of the penetration times, rates of diffusion and the degradation |
| | Barrier cream applied to clean hands before using the product |
| Material of gloves | The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC, this being repealed by EU 2016/425 on 21/04/2018, and the resultant standard EN 374 |
| | The selection of the suitable gloves does not only depend upon the material, but also further marks of quality and varies from manufacturer to manufacturer |
| | Break through, and other characteristics, depending upon material density and the glove type, and must be determined in each case |
| | Gloves to be tightly fitting at the wrists and extend onto the disposable 1-piece covering. Gloves must be inspected prior to each time used and must be replaced when damaged or worn out |
| | Impervious gloves, chemical resistant: Vitron® or Nitrile to EN 374 |
| Penetration time of gloves | Breakthrough time of the glove material - prolonged use > 8 hours - brief contact > 30 minutes |
| (ii) Other | Chemical resistant safety boots with external feed for the laces, not holes for the laces |
| | Safety helmet if required, or other head covering, against splashes |
| | Good hygiene measures should be followed at all time |
| d. Respiratory protection | Mouth & nose filter face mask to EN149:2001. |
| | In the case of inadequate ventilation wear an appropriate gas filter (i.e. type A according to EN 14387) is worn |
| | Mist formation; wear protection as for inadequate ventilation |
| e. Thermal hazards | NDA |
| f. Environmental exposure measures | Avoid release to the environment |
| | Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental legislation. Apply process engineering modifications, ventilation filters, etc. if required |

SECTION 9. Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

| | | |
|----------------------------------|-------------|-------------------|
| • Appearance | (i) Form | Solid, powder |
| | (ii) Colour | Grey |
| • Odour | | Odourless |
| • Odour threshold | | NDA |
| • pH | | NDA |
| • Melting point/range °C | | N/A |
| • Freezing point/range °C | | NDA |
| • Initial boiling point/range °C | | NDA |
| • Flash point/self-ignition °C | | Closed cup: 101°C |
| • Evaporation rate | | NDA |
| • Flammability (solid, gas) | | NDA |
| • Flammability limits, lower % | | NDA |

HydroCoat 103 2K Part B

High Performance Liquid Waterproofing Membrane

| | |
|---|---|
| • Flammability limits, upper % | NDA |
| • Auto flammability °C | NDA |
| • Decomposition temperature | NDA |
| • Explosive properties | NDA |
| • Explosive limits | NDA |
| • Oxidising properties | NDA |
| • Vapour pressure | NDA |
| • Relative vapour density at 20°C | NDA |
| • Relative density | 2.58 |
| • Specific weight | NDA |
| • Solubility in water | In cold water |
| • Partition coefficient n-octanol/water | NDA |
| • Also soluble in | NDA |
| • Viscosity, kinematic | 999.1 mm ² /s (room temperature) |
| • Viscosity, dynamic | NDA |
| • VOC g/l | NDA |

NOTE: The above values related to physiochemical properties are typical values for this product and should not, therefore, be construed as a specification

9.2 Other Information NDA

SECTION 10. Stability and Reactivity

| | |
|--|---|
| 10.1 Reactivity | No specific test data related to reactivity available for this product or its ingredients |
| 10.2 Chemical Stability | The product is stable under recommended transport or storage conditions and when protected against the materials or conditions listed in SECTIONS 10.1 and 10.3 |
| 10.3 Possibility of Hazardous Reactions | Under normal conditions of storage and use, hazardous reactions will not occur |
| 10.4 Conditions to Avoid | No specific data |
| 10.5 Incompatible Materials to Avoid | No specific data |
| 10.6 Hazardous Decomposition Products | Under normal conditions of storage and use, hazardous decomposition products should not be produced |

SECTION 11. Toxicological Information

11.1 Information on Toxicological Effects

| | |
|------------------|---|
| • Acute toxicity | Harmful if inhaled |
| | In the absence of experimental toxicological data on the product itself, the potential risks to health were evaluated based on the properties of the constituent substances, according to the criteria laid down by the relevant regulations for Classification |

Hazardous ingredients

| Substance | Route | Test | Species | Value |
|-----------------------------------|-------|------|---------|------------|
| CAS 1305-62-0 Calcium dihydroxide | Oral | LD50 | Rat | 7340 mg/kg |

- Conclusion: NDA

HydroCoat 103 2K Part B

High Performance Liquid Waterproofing Membrane

- Irritation / Corrosion - Hazardous ingredients

| Substance | Result | Score | Species | Exposure |
|-----------------------------------|------------------------|-------|---------|---------------|
| CAS 1305-62-0 Calcium dihydroxide | Eyes - severe irritant | - | Rabbit | 10 milligrams |

- Conclusion: NDA

- Specific target organ toxicity - single exposure (STOT SE)

| Substance | Category | Route of exposure | Target organs |
|-----------------------------|------------|-------------------|------------------------------|
| Cement, Portland, chemicals | Category 3 | Not applicable | Respiratory tract irritation |
| Calcium dihydroxide | Category 3 | Not applicable | Respiratory tract irritation |

- Other hazards

| Hazard | Negative Symptoms |
|---------------------------------|---|
| Respiratory hazard / inhalation | May cause respiratory irritation if inhaled |
| Serious eye damage / irritation | Causes serious eye damage |
| Skin sensitisation | May cause an allergic skin reaction |
| Skin corrosion / irritation | Causes skin irritation |
| STOT single exposure | May cause respiratory irritation |

| Hazard | Basis |
|-----------------------------|----------------|
| Acute toxicity - oral | NDA |
| Acute toxicity - dermal | NDA |
| Acute toxicity - inhalation | NDA |
| Ingestion | NDA |
| Carcinogenicity | NDA |
| Germ cell mutagenicity | NDA |
| Reproductive toxicity | NDA |
| Teratogenicity | NDA |
| Aspiration hazard | Not classified |
| STOT repeated exposure | NDA |

Viscosity, kinematic 999.1 mm²/s

- Potential acute health effects
 - Eye contact - Causes serious eye damage
 - Inhalation - May cause respiratory irritation
 - Skin contact - Causes skin irritation. May cause an allergic reaction
 - Ingestion - Irritating to mouth, throat and stomach
- Symptoms related to the physical, chemical and toxicological characteristics
 - Eye contact - Adverse symptoms may include pain, watering, redness
 - Inhalation - Adverse symptoms may include respiratory tract irritation, coughing
 - Skin contact - Adverse symptoms may include pain or irritation, redness, blistering may occur
 - Ingestion - Adverse symptoms may include stomach pains
- Delayed and immediate effects as well as chronic effects from short and long-term exposure
 - Short-term exposure
 - Potential immediate effects - NDA
 - Potential delayed effects - NDA
 - Long-term exposure
 - Potential immediate effects - NDA
 - Potential delayed effects - NDA
 - Potential chronic health effects NDA

HydroCoat 103 2K Part B

High Performance Liquid Waterproofing Membrane

| | | |
|-------------------|--|--|
| Conclusion | NDA | |
| | General | - Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels |
| | Carcinogenicity | - No known significant effects of critical hazard |
| | Mutagenicity | - No known significant effects of critical hazard |
| | Teratogenicity | - No known significant effects of critical hazard |
| | Developmental effects | - No known significant effects of critical hazards |
| | Fertility effects | - No known significant effects of critical hazard |
| Other information | NDA | |
| | The product was not tested. The data reported here are based on the manufacturers' SDS which is based on information contained in the safety data sheets of the raw materials that make up the product | |

SECTION 12. Ecological Information

12.1 Toxicity

Environment

| Substance | Species | Test | Result | Exposure |
|---------------------|--|------|--------------------------|-------------------|
| Calcium dihydroxide | Fish - Clarias gariepinus - Fingerling | LC50 | 33884.4 µg/L Fresh water | Acute 96 hours |

Conclusion / summary

NDA

12.2 Persistence and Biodegradability

NDA

12.3 Bioaccumulative Potential

NDA

12.4 Mobility in Soil

NDA

12.5 Results of PBT & vPvT Assessment

N/A

12.6 Other Adverse Effects

No known significant effects or critical hazards

Do not release to the environment

12.7 Additional information

The product was not tested. The data reported here are based on the manufacturers' SDS which is based on information contained in the safety data sheets of the raw materials that make up the product

No other information available

SECTION 13. Disposal Considerations

13.1 Waste Treatment Methods

- Recovery operations Treat as SECTION 6: Accidental Release Measures
- Disposal operations Product - dispose at approved waste collection sites as controlled waste
- Disposal of packaging Paper bag - always has remnants, dispose of a controlled waste
- Waste code number Part B and wet & solidified mixed Part A+Part B: 17 01 06*
Packaging: 15 01 10*
- Special precautions for the disposal method
Ensure substances or mixtures are not mixed with other materials and if held in the same outer container with other materials all are in separate sealed containers within the outer container
- NB The user's attention is drawn to the possible existence of regional or national regulations regarding disposal

HydroCoat 103 2K Part B

High Performance Liquid Waterproofing Membrane

SECTION 14. Transport Information

| ADR | IMDG | IATA | ADN | RID |
|--|---------------|---------------|-----|---------------|
| 14.1 UN Number | | | | |
| Not regulated | Not regulated | Not regulated | NDA | Not regulated |
| 14.2 UN proper shipping name | | | | |
| - | - | - | NDA | - |
| 14.3 Transport hazard class(es) | | | | |
| - | - | - | NDA | - |
| 14.4 Packing group | | | | |
| - | - | - | NDA | - |
| 14.5 Environmental hazards | | | | |
| No | No | No | NDA | No |
| No supplementary information available IMDG Code Segregation Group: N/A | | | | |

14.6 Special Precautions for User Always transport in closed containers that secure against damage, Ensure that persons transporting the product know what to do in the event of an accident or spillage

- Overland transport N/A
- Transport by sea N/A
- Air transport N/A
- Inland waterway transport N/A
- Rail transport N/A

14.7 Transport in Bulk According to: Transport in bulk in not available / offered

- (i) Annex II of Marpol N/A
- (ii) the IBC Code N/A

SECTION 15. Regulatory Information

15.1 Safety, Health and Environmental Regulations/Legislation Specific for the Substance, Mixture or Article

COMMISSION REGULATIONS (EC) No 1272/2008 and (EU) No 2015/830 of 28/05/2015 amending Regulation (EC) No 1907/2006 and repealing (EU) 453/2010 20 May 2010 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

- Other regulations, limitations and prohibitive regulations
 - Contains no substances with REACH Annex XVII restrictions
 - Contains no REACH Annex XIV substances

15.2 Chemical Safety Assessment A chemical safety assessment has not been carried out. Data from the component substances is included in this SDS

HydroCoat 103 2K Part B

High Performance Liquid Waterproofing Membrane

SECTION 16. Other Information

16.1 Basis of this SDS The data reported here are based on the manufacturer's SDS which is based on information contained in the safety data sheets of the raw materials that make up the product

16.2 Changes Compared to the Previous Version

| Date | Replaces | Sections | Item | Change | Comment |
|----------|----------|----------|------|-------------|--|
| 12/12/19 | 1.0 | All | All | See Comment | This is a full rewrite, read the entire document |

16.3 Key literature and sources of data Regulation (EC) 1907/2006
 Regulation (EC) No. 1272/2008
 Regulation (EU) No. 2015/830
 Supplier SDS
 ECHA, including REACH dossier for component substances
 EH40/2005 3rd Edition, 2018

16.4 Abbreviations & Acronyms CLP: EU Regulation 1272/2008: Classification, Labelling & packaging of chemical substances
 HSE: (UK) Health & Safety Executive
 IBC Code: International Building Code
 LD50: Lethal dose, 50% affected
 MARPOL: International Convention for the Prevention of Pollution from Ships
 N/A: Not Applicable
 NDA: No Data Available
 PBT: Persistent, Bioaccumulative and Toxic substances
 vPvB: Very Persistent and very Bioaccumulative substances
 REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals: Regulation (EC) No 1907/2006
 SDS: Safety Data Sheet
 STEL: Short Term Exposure Limit
 STOT RE: Specific target organ toxicity (from) repeated exposure
 STOT SE: Specific target organ toxicity (from) single exposure
 TWA: Time Weighted Averages
 VOC: Volatile organic compounds

16.5 Procedure used to derive the Classification according to Regulation (EC) No. 1272/2008

| Classification | Justification |
|---------------------|--------------------|
| Skin Irrit. 2, H315 | Calculation method |
| Eye Dam. 1, H318 | Calculation method |
| Skin Sens. 1, H317 | Calculation method |
| STOT SE 3, H335 | Calculation method |

16.6 Full text of H and EUH statements

| | |
|------|---|
| H315 | Causes skin irritation |
| H317 | May cause an allergic reaction |
| H318 | Causes serious eye damage |
| H319 | Causes serious eye irritation |
| H335 | May cause respiratory irritation |
| H412 | Harmful to aquatic life with long lasting effects |

HydroCoat 103 2K Part B

High Performance Liquid Waterproofing Membrane

16.7 Full text of Classifications (CLP / GHS)

| | |
|-------------------------|--|
| Aquatic Chronic 3, H412 | Long Term Aquatic Hazard - Category 3 |
| Eye Dam. 1, H318 | Serious Eye Damage / Eye Irritation - Category 1 |
| Eye Irrit. 2, H319 | Serious eye damage / irritation, Category 2 |
| Skin Irrit. 2, H315 | Skin Corrosion / Irritation - Category 2 |
| Skin Sens. 1, H317 | Skin Sensitisation - Category 1 |
| STOT SE 3, H335 | Specific target organ toxicity (single exposure) - respiratory tract, Category 3 |

16.8 Training advice

Obtain special instructions and read the Safety Data Sheet before use. Do not handle until all safety precautions have been read and understood. It is recommended that workers are trained in the safe handling of hazardous chemicals

16.9 DISCLAIMER

Persons using the information contained here must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where these purposes are other than as specifically recommended in this Safety Data Sheet and in the Technical Data Sheet, then the user uses the product at their own risk

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best on the Company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the users responsibility to satisfy themselves as to the suitability of such information for their own particular use