

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

Revision: 2.1 - 9th January 2023
Code: 107F

SECTION 1. Identification of the Substance/Mixture and of the Company/Undertaking

Product Identifier

- Product form Mixture
- Product name HydroCoat 107F
- Product codes 107F

Relevant identified uses of the substance and uses advised against

- Use of substance/mixture Professional Use only
Internal and external waterproofing
- Uses advised against Not for any other use

Details of the Supplier of the Safety Data Sheet

- Company Address Newton Waterproofing Systems, Newton House, 17-19 Sovereign Way, Tonbridge, Kent TN9 1RH
- Web www.newtonwaterproofing.co.uk
- Email address of the competent person info@newtonwaterproofing.co.uk
- Emergency telephone numbers Newton Waterproofing systems - English language
+44 (0)1732 360095/08:00-17:30 (GMT) Mon-Thur & 08:00-17:00 (GMT) Fri

SECTION 2. Hazards Identification

- Refer to SECTION 16 for The explanation of the abbreviations used throughout this SDS
The full list of Hazard Phrases & Precautionary Statements stated throughout this SDS
- Refer to SECTION 11 for More detailed information on health effects and symptoms

2.1 Classification of the Substance or Mixture

- Classification under Regulation (EC) No. 1272/2008 (CLP)
Aquatic Chronic 3, H412
The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended
- Adverse physicochemical, human health and environmental effects
See SECTION 11 for information on health effects and symptoms

2.2 Label Elements

- Hazard statements H412: Harmful to aquatic life with long lasting effects
- Signal words (CLP) No signal word
- Hazard pictograms (CLP) No hazard pictogram
- Hazardous ingredients N/A
- Precautionary statements (CLP)
 - General: N/A
 - Prevention: Avoid release to the environment
 - Response: N/A
 - Storage: N/A
 - Disposal: Dispose of contents and container in accordance with all local, regional, national and international regulations

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

Supplemental label elements	To be handled and used in accordance with good occupational hygiene and safety practice. Wear PPE as SECTION 8.2, handle and store as SECTION 7, manage accidental release as SECTION 6 and follow the instructions in the Data Sheet
	Contains reaction mass of: 5-chloro-2-mthyl-4-isothiazolin-3-one [EC No. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC No. 220-239-6] (3:1) and 1, 2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
	Wear appropriate respirator when ventilation is inadequate
2.3 Other Hazards	
• Other Hazards	NDA
• Other information	Classification and labelling have been made on the basis of safety data sheets of the raw materials that make up the product

SECTION 3. Composition/information on ingredients

3.2 Mixture	This product is a mixture
Hazardous Substances	

Chemical name	Identifiers	%	Classification according to Regulation (EC) No. 1272/2008 (CLP)	Type (see below)
1,2-benzisothiazol-3(2H)-one	CAS: 2634-33-5 EC: 220-120-9 Index: 613-088-00-6	<0.025	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)	1
Reaction mass of: 5-chloro-2-mthyl-4-isothiazolin-3-one [EC No. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC No. 220-239-6] (3:1)	CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1B, H314 Skin Sens. 1, H317 Acute Tox. 3, H400 (M =1) Acute Chronic 1, H410 (M=1)	1

NB	Refer to SECTION 8 for Occupational Exposure Limits & Controls and Personal Protection
	Refer to SECTION 16 for the full text of Hazard Statements
	There are no additional ingredients present, which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, or are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this SECTION.
Type:	1: Substance classified with a health or environmental hazard 2: Substance with a workplace exposure limit 3: Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII 4: Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII 5: Substance of equivalent concern

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

SECTION 4. First Aid Measures

4.1 Description of First Aid Measures

- **General**

Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice. If exposed or concerned get medical advice / attention. If you feel unwell, seek medical advice

Those assisting the exposed persons to take no action involving personal risk or without training. Performing mouth-to-mouth can be dangerous, only to be done by trained personnel

Eye bathing equipment and First Aid Box should be available

Take this SDS with you when seeking medical advice
- **Skin contact**

Remove contaminated clothing. Gently remove all traces of product and wash with plenty of soap and water or recognised skin cleanser. Continue to rinse for at least 10 minutes. If skin irritation or rash occurs seek medical advice / attention. Do NOT use solvents or thinners
- **Eye contact**

Do not rub. Immediately rinse eyes cautiously with plenty of water for at least 15 minutes holding the eyelids open. Remove contact lenses if present and easy to do so, then continue to rinse copiously for 15 minutes. Obtain immediate medical advice
- **Ingestion**

If swallowed, seek medical advice immediately and show the container or label, and this SDS. Keep person warm and at rest. Do NOT induce vomiting. If vomiting occurs, the head should be kept forward and low so vomit does not enter the lungs. Never give anything to an unconscious person. Move the exposed person to fresh air. If unconscious, place in the recovery position and get medical advice immediately. Loosen tight clothing such as collar, tie, belt and waistband
- **Inhalation**

Immediately ventilate the area and remove person from the contaminated place to rest in fresh air and keep comfortable and breathing. Assure fresh air breathing. Loosen tight clothing such as collar, tie, belt or waistband. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Seek medical attention
- **Self-protection for first aiders**

No action to be taken involving any personal risk or without suitable training. If it is suspected that the mixture is still present, wear appropriate Personal Protection Equipment, see SECTION 8.2. Wear gloves to remove contaminated clothing, see SECTION 13 for washing or disposal

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Potential acute health effects:

- **Skin contact** No known significant effects or critical hazards
- **Eye contact** No known significant effects or critical hazards
- **Ingestion** No known significant effects or critical hazards
- **Inhalation** No known significant effects or critical hazards

Over-exposure signs / symptoms:

- **Skin contact** No specific data
- **Eye contact** No specific data
- **Ingestion** No specific data
- **Inhalation** No specific data

4.3 Indication of Any Immediate Medical Attention and Special Treatment Needed

- **Notes to physician** Treat symptomatically. Contact poison centre immediately if large quantities have been ingested or inhaled
- **Specific treatments** No specific treatment

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

SECTION 5. Fire-Fighting Measures

5.1 Extinguishing Media

Use an extinguishing agent suitable for the surrounding fire

Unsuitable extinguishing media:

- None known

5.2 Special Hazards Arising from the Material

Hazards from the substance or mixture In a fire or if heated, a pressure increase will occur and the container may burst. This material is hazardous to aquatic life with long lasting effects

This material is harmful to aquatic life with long lasting effects. Fire fighting water contaminated with this material must be contained and prevented from being discharged to the environment or any waterway, sewer or drain, alert the Environmental Agency if this occurs

Hazardous thermal decomposition products

No specific data

5.3 Advice for Firefighters

Isolate the affected area

All persons to be immediately removed from the vicinity of the fire. Fire to be dealt with by trained personnel and without involving personal risk

Exercise caution when fighting any chemical fire

Do not enter the area without wearing appropriate protective equipment and self-contained breathing apparatus (SCBA) with full face-piece operated in positive pressure mode. Clothing, including helmets, protective boots and gloves, conforming to EN 469 will provide a basic level of protection for chemical incidents

SECTION 6. Accidental Release Measures

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

- **General measures** Do not attempt to take action without wearing suitable personal protection, refer to SECTION 8.2 of the SDS
 - **Non-emergency personnel** Ensure adequate ventilation
 - **Emergency personnel** Evacuate unnecessary personnel
 - Do not touch or walk through the spilled material. Ventilate spillage area. Do not breathe dust / fumes/ gas / vapours / mist / spray. Avoid contact with skin and eyes
 - Evacuate unnecessary personnel and those not wearing the suitable protection. If outside do not approach from downwind. If outside keep bystanders and passing persons upwind and away from the danger point. Mark out the contaminated area with signage and prevent access by unauthorised persons
 - Do not attempt to take action without suitable protective equipment. Equip clean-up crew with proper protection, see SECTION 8 'Exposure controls / personal protection'
 - Ensure adequate ventilation, including forced ventilation if in an internal space and necessary, and vent externally to be safely away from other persons and the general public
 - Turn leaking containers leak-side up to prevent the escape of material, and place in a sealable leak proof container, label this with the contents
 - Avoid inhalation of vapours, wear respiratory protection as SECTION 8.2
- 6.2 Environmental Precautions** Prevent the product and runoff from contact with soil and from entering drains, sewers, watercourses, basements or confined spaces (refer to SECTION 11). Contain the spillage using bunding

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

Water polluting material, may be harmful to the environment if released in large quantities

Alert the Environmental Agency in the event of spillage, etc. entering water ways, sewers, drains, soil or air

6.3 Methods and Materials for Containment and Cleaning Up

Clean-up should ONLY be dealt with by qualified persons familiar with the specific product

Stop the leak / spillage if it is safe to do so. Move containers from spill area

Small spillages should be absorbed, see list of appropriate bunding below, and this transferred into sealable impervious container(s)

Large spillages should be contained by bunding using absorbent materials and carefully transferred into sealable impervious containers. Remnants from large spillages and small spillages should be absorbed and transferred into these containers

Appropriate bunding - non-combustable absorbent materials: sand, earth, vermiculite or diatomaceous earth

All washings to be retained within the bunding and fully collected up into sealable impervious waste container(s), label these with the contents

All contaminated bunding, including all suspected of being contaminated, to be collected up and transferred to these waste containers

All containers to be labelled and held for disposal as SECTION 13

6.4 Reference to Other Sections

Refer to SECTIONS 1 (Emergency contact), 8 (Personal Protection / Exposure Controls), 12 (Ecological Information) and 13 (Disposal Consideration)

SECTION 7. Handling and Storage

The information in the SECTION includes generic advice and guidance. The list of 'Relevant identified uses' in SECTION 1 should be consulted for any available use-specific information provided here and in SECTION 8

7.1 Precautions for Safe Handling

a. Safe handling

Wear protective equipment as required by use- see SECTION 8

Do not get in eyes, on skin or on clothing - see SECTION 8 for the protection of work clothing. Do not ingest. Obtain special instructions before use. Do not handle or use until all safety precautions have been read and understood.

Only use outdoors or in well ventilated areas, wear appropriate respirator when ventilation is inadequate. Keep in original container, kept tightly closed when not in use

Do not breathe vapours, aerosols or gases

Do not reuse the container, empty containers retain residue, see SECTION 13 for disposal

b. Hygiene measures

Do not eat, drink or smoke when handling. Wash hands and other exposed areas with mild soap and water after using the material and remove contaminated clothing and protective equipment before entering areas where food and drink are consumed and when leaving the work site

Contaminated work clothing should be securely bagged before being allowed out of the work site. See SECTION 13 for the protection of work clothing and the washing or disposal of contaminated work clothing and boots. Wash hands and face before eating, drinking, smoking and using the toilet

See SECTION 8 for additional information on hygiene measures

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

c. Prevention of handling incompatible substances or mixtures

Do not handle other substances or mixtures at the same time. Keep away from other substances and mixtures

d. Operations and conditions that could create new risks

Do not allow opened, part used or the container in use to come into contact with other materials including all surfaces around. Ensure the containers are securely sealed during transport, storage and when at the work site

e. Reduce risk of release to the environment

Avoid spillage. Ensure the floor at storage, transport and the work location will not allow access to drains or water courses. Lay heavy gauge plastic sheeting or similarly impervious protective covering when mixing and dispensing. Contain and clean up spillage as SECTION 6.3 of the SDS

7.2 Conditions for Safe Storage, Including Any Incompatibilities

a. Storage conditions

Store in a well ventilated locked area, keep cool, away from direct sunlight and in accordance with local regulations. Only store in original container. Keep container tightly closed, and upright against spillage. Do not store in unlabelled containers, if transferred to another container include the Batch Number and Manufacturing or Expiry Date on the new label. The floor of the storage area to be impermeable to prevent the escape of spillage

b. Maximum storage period

Maximum storage period (shelf life): 12 months from date of manufacture when stored at 20°C (68°F)

Use of the stock must be by manufacturing date or expiry date rotation. Containers past their expiry date must be removed for disposal according to SECTION 13 of the SDS

c. Control of the effects of weather, ambient pressure, temperature, sunlight, humidity and vibration

Protect from freezing, frost, heat and direct sunlight. Keep away from sources of ignition, open flames or excessive heat

Ensure containers are securely closed against vibration spillage during transport when loading / unloading vehicles, during transport and moving from vehicle to the work location. Unopened containers to be protected against damage during these movements

d. Storage with other substances and mixtures

Only store in the original packaging. Store against falling / touching other materials and in an allocated location

e. Storage room design, quantity limits, ventilation and packaging compatibilities

Storage room to be dry, ventilated, and constructed to have impermeable floors and walls to prevent the escape of spillages into the environment

f. Other considerations

No other data available

7.3 Specific End Use(es)

Part A of a 2-Part liquid applied cementitious waterproofing membrane. Refer to the Technical Data Sheet for further information

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

SECTION 8. Personal Protection/Exposure Control

The information in this SECTION contains generic advice and guidance and is based on typical anticipated uses of the product. Additional measures might be required for bulk handling or uses other than those described in the Technical Data Sheet that could significantly increase worker exposure or environmental releases

8.1 Control Parameters

Workplace Exposure Limits (WEL)

EH40: Taken from the HSE EH40/2005 (3rd edition, published 2018):

- not stated = not on EH40
- if no 15 min STEL, 3x TWA used

Carc: Capable of causing cancer and / or heritable genetic damage

Sen: Capable of causing occupational asthma

Sk: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systematic toxicity

Substance & CAS	Long-term exposure limit (8hr TWA reference period)		Short-term exposure limit (15 minute reference period)		Comments	Source
	ppm	mg / m³	ppm	mg / m³		
No exposure limits known	NDA - not on the EH40 Table					HSE

Recommended monitoring procedures Reference should be made to monitoring standards, such as:

EN 689 Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy

EN 14042 Workplace atmospheres - Guide for the application and use for the assessment of exposure to chemical and biological agents

EN 482 Workplace atmospheres - General requirement for the performance of procedures for the measurement of chemical agents

Reference to national guidance documents for methods for the determination of hazardous substances will also be required

DNELs / DMELs

No DNELs / DMELs available

PNECs

No PNECs available

8.2 Exposure Controls

8.2.1 Appropriate Engineering Controls

a. Ventilation

Ensure there is sufficient ventilation in the area, including forced ventilation if necessary or in an internal or enclosed space with safe exhaust away from other persons. The floor must be impermeable to prevent the escape of liquids, laying impermeable protective covering if in doubt

b. Isolation

Isolate the work area with warning signage against unauthorised access. Ensure all other persons are pre-notified of the works and remain clear of the work area

c. Washing

Provide eye wash facilities, individual eye wash ampoules and safety shower

d. Against contamination

Refer to SECTION 15.1 for any 'Other Regulations' and the REACH Annex XVII statements there

Only mix the 2 Parts of the product on impervious protective sheeting and with this laid at the area(s) where the mixed product is to be applied, against splashes onto the person(s) performing this task, any other persons and onto the surrounding areas:

- When opening each Part and when progressively mixing them together
- When using the power mixer / paddle off a drill, include erecting barrier around if necessary to stop splashes off the protective sheeting onto

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

- other persons, structures, ground, etc
- When applying the mixed product to the area(s) to be treated
- The person(s) performing this to wear disposable overshoes over their safety work boots when working off the protective sheeting against walking contamination onto the surrounding area
- When the mixing is done, dispose of the contaminated protective sheeting, the overshoes, etc as controlled waste

e. Mists

Prevent the formation of vapour or aerosol

f. Hygiene & Occupational care

Do not eat, drink or smoke during stirring or use of the product. Wash hands, face and forearms if uncovered with soap and water before eating, drinking, smoking, using the toilet and when leaving the work site for natural breaks, break times and at end of day

8.2.2 Personal Protective Equipment

a. Work clothing

Clothing and personal protection equipment should be selected based on the task being performed and the risks involved, and should be approved by a specialist before handling this product. EN ISO 13688

Wash contaminated work clothing before reusing

Additional protection: wear impervious disposable 1-piece covering to body, legs and arms with closure at wrists and ankles, and disposable overshoes. EN ISO 13688

b. Eye / face protection

Tight fitting safety chemical goggles / safety glasses with side protection designed to protect against splashes, mists, gases or dusts. EN166

If at risk of splashing to face when mixing and using the 2-part product wear a full face visor

c. Skin protection

(i) Hand Protection

To be impermeable chemical resistant gloves, resistant to micro-organisms, to EN 374

Barrier cream applied to clean hands before using the product

Material of gloves

Impervious gloves, chemical resistant: Vitron® or Nitrile to EN 374

The selection of the suitable gloves does not only depend upon the material, but also further marks of quality and varies from manufacturer to manufacturer

Break through, and other characteristics, depends upon material density, the glove type and use, and must be determined in each case

Gloves to be tightly fitting at the wrists and extend onto the work clothing, see above. Gloves must be inspected prior to each time used and must be replaced when damaged or worn out

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular application conditions of use, as included in the user's Risk Assessment. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: other chemicals which may be handled, physical requirement (cut / puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions / specifications provided by the glove supplier. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred

Penetration time of gloves

Breakthrough time of the glove material

- prolonged use: protection class 6, breakthrough time > 8 hours
- brief contact: protection class 2, breakthrough time > 30 minutes

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

(ii) Other	Chemical resistant safety boots with external feed for the laces, not holes for the laces
	Safety helmet if required, or other head covering, against splashes
d. Respiratory protection	Any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling the product
	Good hygiene measures should be followed at all time
	Mouth & nose filter face mask to EN149:2001, with Face Fit Certification
	In the case of inadequate ventilation use an appropriate gas filter ensuring the filter is within its working limits
e. Thermal hazards	Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a Risk Assessment indicates this is necessary according to EN529. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator
	Mist formation; wear protection as for inadequate ventilation
f. Environmental exposure measures	NDA
g. Hygiene measures	Avoid release to the environment
	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental legislation. In some cases fume scrubbers, ventilation filters, engineering modifications to the process / equipment will be necessary to reduce emissions to acceptable levels
	Wash thoroughly after handling. Do NOT eat, drink or smoke while using this product. Remove contaminated clothing, see SECTION 13 for the washing or disposal of contaminated clothing

SECTION 9. Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

• Appearance	(i) Form	Liquid
	(ii) Colour	White
• Odour		Faint odour
• Odour threshold		NDA
• pH		7
• Melting point/range °C		NDA
• Freezing point/range °C		NDA
• Initial boiling point/range °C		Lowest known value: 100°C (212°F) (water)
• Flash point/self-ignition °C		Closed cup: 101°C
• Evaporation rate		NDA
• Flammability (solid, gas)		NDA
• Flammability limits, lower %		N/A
• Flammability limits, upper %		N/A
• Auto flammability °C		NDA
• Decomposition temperature		NDA
• Explosive properties		NDA
• Explosive limits		N/A

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

• Oxidising properties	NDA
• Vapour pressure	NDA
• Relative vapour density at 20°C	NDA
• Relative density	1.04
• Specific weight	NDA
• Solubility in water	Soluble in cold water
• Partition coefficient n-octanol/water	NDA
• Also soluble in	NDA
• Viscosity, kinematic	2,413.13 mm ² /s (room temperature)
• Viscosity, dynamic	NDA
• VOC g/l	NDA

NOTE: The above values related to physiochemical properties are typical values for this product and should not, therefore, be construed as a specification

9.2 Other Information NDA

SECTION 10. Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity is available for this product
10.2 Chemical Stability	Stable at room temperature, under recommended transport or storage conditions and when protected against the materials or conditions listed in SECTIONS 10.1 and 10.3
10.3 Possibility of Hazardous Reactions	Under normal conditions of storage and use (see the Technical Data Sheet), hazardous reactions will not occur
10.4 Conditions to Avoid	No specific data
10.5 Incompatible Materials to Avoid	No specific data
10.6 Hazardous Decomposition Products	Under normal conditions of storage and use, hazardous decomposition products should not be produced

SECTION 11. Toxicological Information

11.1 Information on Toxicological Effects

In the absence of experimental toxicological data on the product itself, potential health risks were evaluated based on the properties of the constituent substances, according to the criteria from relevant regulations for Classification

- Acute toxicity - Hazardous ingredients

Substance	Route	Test	Species	Value	Exposure
1,2-benzisothiazol-3(2H)-one	Oral	LD50	Rat	1,020 mg/kg	-
Reaction mass of: 5-chloro-2-mthyl-4-isothiazolin-3-one [EC No. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC No. 220-239-6] (3:1)	Oral	LD50	Rat	53 mg/kg	-

- Conclusion: NDA

- Irritation / Corrosion - Hazardous ingredients

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

Substance	Result	Species	Score	Exposure	Observation
1,2-benzisothiazol-3(2H)-one	Skin - mild irritant	Human	-	48 hours 5%	-
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC No. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC No. 220-239-6] (3:1)	Skin - severe irritant	Human	-	0.01%	-

- Conclusion: NDA

- Relevant hazards for product

Hazard	Negative Symptoms
Acute toxicity - oral	Harmful if swallowed
Skin corrosion / irritation	Harmful to skin

Other hazards

Hazard	Basis
Respiratory hazard / inhalation	NDA
Serious eye damage / irritation	NDA
Skin sensitisation	NDA
Carcinogenicity	NDA
Germ cell mutagenicity	NDA
Reproductive toxicity	NDA
Teratogenicity	NDA
STOT single exposure	NDA
STOT repeated exposure	NDA
Acute toxicity - dermal	NDA
Acute toxicity - inhalation	NDA
Aspiration hazard	NDA

- Viscosity, kinematic 2,413.13 mm²/s (room temperature)
- Information on likely routes of exposure
NDA
- Potential acute health effects

Eye contact	- No known significant effects or critical hazards
Inhalation	- No known significant effects or critical hazards
Skin contact	- No known significant effects or critical hazards
Ingestion	- No known significant effects or critical hazards
- Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	- No specific data
Inhalation	- No specific data
Skin contact	- No specific data
Ingestion	- No specific data
- Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short-term exposure	Potential immediate effects	- NDA
	Potential delayed effects	- NDA
Long-term exposure	Potential immediate effects	- NDA
	Potential delayed effects	- NDA
Potential chronic health effects	NDA	
Conclusion	NDA	
	General	- No known significant effects of critical hazard
	Carcinogenicity	- No known significant effects of critical hazard
	Mutagenicity	- No known significant effects of critical hazard

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

- Teratogenicity - No known significant effects of critical hazard
 - Developmental effects - No known significant effects of critical hazards
 - Fertility effects - No known significant effects of critical hazard
- Other information NDA

The product was not tested. The data reported here are based on the manufacturer's SDS which is based on information contained in the safety data sheets of the raw materials that make up the product

SECTION 12. Ecological Information

12.1 Toxicity

Substance	Species	Test	Result		Exposure
1,2-benzisothiazol-3(2H)-one	Daphnia - Daphnia magna	EC50	1.5 mg/L	Acute	48 hours
	Daphnia - Daphnia magna	EC50	97 ppb Fresh water	Acute	48 hours
	Algae - Pseudokirchneriella subcapitata	IC50	0.067 mg/L	Acute	72 hours
	Crustaceans - Ceriodaphnia dubia	LC50	>10 mg/L Fresh water	Acute	48 hours
	Fish - Ochorhyncus mykiss	LC50	1.3 mg/L	Acute	96 hours
	Fish - Oncorhynchus mykiss	LC50	167 ppb Fresh water	Acute	96 hours

Conclusion / Summary NDA

12.2 Persistence and Biodegradability NDA

12.3 Bioaccumulative Potential NDA

12.4 Mobility in Soil NDA

12.5 Results of PBT & vPvT Assessment N/A

12.6 Other Adverse Effects No known significant effects or critical hazards

12.7 Additional information The product was not tested. The data reported here are based on the manufacturer's SDS which is based on information contained in the safety data sheets of the raw materials that make up the product

No other information available

SECTION 13. Disposal Considerations

13.1 Waste Treatment Methods

- Recovery operations Treat as SECTION 6: Accidental Release Measures
- Disposal operations Product - dispose at approved waste collection sites as controlled waste
- Disposal of packaging Plastic 5L screw cap container for controlled waste disposal
- Waste code number Product: - Part A and wet & cured mixed Part A + Part B: 08 01 11*
Part A packaging, always has remnants: 15 01 10*
- Special precautions for the disposal method

The container will always retain residues. Do not attempt to wash it out to remove the residues to avoid dispersal of the wash and runoff to be in contact with soil, waterways, drains and sewers

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out.

Ensure substances or mixtures are not mixed with other materials and if held in the same outer container with other materials all are in separate sealed containers within the outer container
- NB The user's attention is drawn to the possible existence of regional or national regulations regarding disposal

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

SECTION 14. Transport Information

ADR	IMDG	IATA	ADN	RID
14.1 UN Number				
Not regulated	Not regulated	Not regulated	N/A	Not regulated
14.2 UN proper shipping name				
N/A	N/A	N/A	N/A	N/A
14.3 Transport hazard class(es)				
N/A	N/A	N/A	N/A	N/A
14.4 Packing group				
N/A	N/A	N/A	N/A	N/A
14.5 Environmental hazards				
No	No	No	N/A	No
No supplementary information available				
IMDG Code Segregation Group: N/A				

14.6 Special Precautions for User Always transport in closed containers that secure against damage, Ensure that persons transporting the product know what to do in the event of an accident or spillage

- Overland transport N/A
- Transport by sea N/A
- Air transport N/A
- Inland waterway transport N/A
- Rail transport N/A

14.7 Transport in Bulk According to: Transport in bulk is not available / offered

- (i) Annex II of Marpol N/A
- (ii) the IBC Code N/A

SECTION 15. Regulatory Information

15.1 Safety, Health and Environmental Regulations/Legislation Specific for the Substance, Mixture or Article

COMMISSION REGULATIONS (EC) No 1272/2008 and (EU) No 2015/830 of 28/05/2015 amending Regulation (EC) No 1907/2006 and repealing (EU) 453/2010 20 May 2010 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

- Other regulations, limitations and prohibitive regulations

Contains no REACH substances with Annex XVII restrictions

Annex XVII Restrictions: N/A

Other EU Regulations: Not determined

Special packaging requirements: N/A

Ozone depleting substances (1005/2009/EU): Not listed

Prior Informed Consent (PIC) (649/2012/EU): Not listed

National Regulations: Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II and Regulation (EC) No. 1272/2008 (CLP)

15.2 Chemical Safety Assessment

A chemical safety assessment has not been carried out. Data from the component substances is included in this SDS

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

SECTION 16. Other Information

16.1 Basis of this SDS

The data reported here are based on the manufacturer's SDS which is based on information contained in the safety data sheets of the raw materials that make up the product

16.2 Changes Compared to the Previous Version

Date	Replaces	Sections	Item	Change	Comment
22/03/20	1.0	All	All	See Comment	Full re-write, read the entire document

16.3 Key literature and sources of data

Regulation (EC) 1907/2006
Regulation (EC) No. 1272/2008
Regulation (EU) No. 2015/830
Supplier SDS
ECHA, including REACH dossier for component substances
EH40/2005 3rd Edition, 2018

16.4 Abbreviations & Acronyms

ATE: Acute Toxicity Estimate
CLP: EU Regulation 1272/2008: Classification, Labelling & packaging of chemical substances
DMEL: Derived Minimal Effect Level
DNEL: Derived No Effect Level

EC50: Concentration giving response half way between baseline and maximum
EINECS: European Inventory of Existing Commercial Chemical Substances or European List of Notified Chemical Substance number
EUH statement: CLP-specific Hazard statement
HSE: (UK) Health & Safety Executive
IBC Code: International Building Code
IC50: half maximal Inhibitory Concentration
LC50: Lethal Concentration, 50% affected
LD50: Lethal dose, 50% affected
MARPOL: International Convention for the Prevention of Pollution from Ships
N/A: Not Applicable
NDA: No Data Available
PBT: Persistent, Bioaccumulative and Toxic substances
vPvB: Very Persistent and very Bioaccumulative substances
PNEC: Predicted No-Effect Concentration
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals: Regulation (EC) No 1907/2006
SDS: Safety Data Sheet
STEL: Short Term Exposure Limit
STOT RE: Specific target organ toxicity (from) repeated exposure
STOT SE: Specific target organ toxicity (from) single exposure
TWA: Time Weighted Averages
VOC: Volatile organic compounds

16.5 Procedure used to derive the Classification according to Regulation (EC) No. 1272/2008

Classification	Justification
Aquatic Chronic 3, H412	Calculation method

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

16.6 Full text of H and EUH statements

H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe eye burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic reaction
H318	Causes serious eye damage
H331	Toxic if inhaled
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

16.7 Full text of Classifications (CLP / GHS)

Acute Tox. 3, H301	Acute Toxicity (oral) - Category 3
Acute Tox. 3, H311	Acute Toxicity (dermal) - Category 3
Acute Tox. 3, H331	Acute Toxicity (inhalation) - Category 3
Acute Tox. 4, H302	Acute Toxicity (oral) - Category 4
Aquatic Acute 1, H400	Acute Aquatic Hazard - Category 1
Aquatic Chronic 1, H410	Long Term Aquatic Hazard - Category 1
Aquatic Chronic 3, H412	Long Term Aquatic Hazard - Category 3
Eye Dam. 1, H318	Serious Eye Damage / Eye Irritation - Category 1
Skin Corr. 1B, H314	Skin Corrosion / Irritation - Category 1B
Skin Irrit. 2, H315	Skin Corrosion / Irritation - Category 2
Skin Sens. 1, H317	Skin Sensitisation - Category 1

16.8 Training advice

Obtain special instructions and read the Safety Data Sheet before use. Do not handle until all safety precautions have been read and understood. It is recommended that workers are trained in the safe handling of hazardous chemicals

16.9 DISCLAIMER

Persons using the information contained here must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where these purposes are other than as specifically recommended in this Safety Data Sheet and in the Technical Data Sheet, then the user uses the product at their own risk

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best on the Company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the users responsibility to satisfy themselves as to the suitability of such information for their own particular use

HydroCoat 107 Elastic 2K Part B

Cementitious Flexible Waterproofing Membrane

SECTION 1. Identification of the Substance/Mixture and of the Company/Undertaking

Product Identifier

- Product form Mixture
- Product name HydroCoat 107F
- Product codes 107F

Relevant identified uses of the substance and uses advised against

- Use of substance/mixture Professional use only
Internal and external waterproofing
- Uses advised against Not for any other use

Details of the Supplier of the Safety Data Sheet

- Company Address Newton Waterproofing Systems, Newton House, 17-19 Sovereign Way, Tonbridge, Kent TN9 1RH
- Web www.newtonwaterproofing.co.uk
- Email address of the competent person info@newtonwaterproofing.co.uk
- Emergency telephone numbers Newton Waterproofing systems - English language
+44 (0)1732 360095/08:00-17:30 (GMT) Mon-Thur & 08:00-17:00 (GMT) Fri

SECTION 2. Hazards Identification

- Refer to SECTION 16 for The explanation of the abbreviations used throughout this SDS
The full list of Hazard Phrases & Precautionary Statements stated throughout this SDS
- Refer to SECTION 11 for More detailed information on health effects and symptoms

2.1 Classification of the Substance or Mixture

- Classification under Regulation (EC) No. 1272/2008 (CLP)
Not classified
Full text of hazard classes and H-statements: see SECTION 16
- Adverse physicochemical, human health and environmental effects
This product is classified as hazardous according to Regulation (EC) 1272/2008 as amended

2.2 Label Elements

- Signal words (CLP) No signal word
- Hazard pictograms (CLP) No hazard pictograms
- Hazard statements (CLP) No known significant effects or critical hazards
- Precautionary statements (CLP)
 - General: N/A
 - Prevention: N/A
 - Response: N/A
 - Storage: N/A
 - Disposal: Dispose of contents and container in accordance with local, regional, national and/or international regulation
- Supplemental Label elements: Wear appropriate respirator when ventilation is inadequate

HydroCoat 107 Elastic 2K Part B

Cementitious Flexible Waterproofing Membrane

- Other To be handled and used in accordance with good occupational hygiene and safety practice. Wear PPE as SECTION 8.2, handle and store as SECTION 7, manage accidental release as SECTION 6 and follow the instructions in the Data Sheet

2.3 Other Hazards

- PBT / vPvB No additional information available
- Other Hazards None known
- Other information Classification and labelling have been made on the basis of safety data sheets of the raw materials that make up the product

SECTION 3. Composition/information on ingredients

3.2 Mixture

This product is a mixture

Hazardous Substances

Chemical name	Identifiers	%	Classification according to Regulation (EC) No. 1272/2008 (CLP)	Type (see below)
Crystalline silica	EC: 238-878-4 cas: 14808-60-7	≥50 - ≤75	Not classified	2

NB Refer to SECTION 8 for Occupational Exposure Limits & Controls and Personal Protection

Refer to SECTION 16 for the full text of Hazard Statements

There are no additional ingredients present, which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, or are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this SECTION.

Type:

- 1: Substance classified with a health or environmental hazard
- 2: Substance with a workplace exposure limit
- 3: Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- 4: Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- 5: Substance of equivalent concern

SECTION 4. First Aid Measures

4.1 Description of First Aid Measures

- General

Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice. If exposed or concerned get medical advice / attention. If you feel unwell, seek medical advice

Those assisting the exposed persons to take no action involving personal risk or without training. Performing mouth-to-mouth can be dangerous, only to be done by trained personnel

Eye bathing equipment and First Aid Box should be available

Take this SDS with you when seeking medial advice
- Skin contact

Remove contaminated clothing and shoes. Gently remove all traces of product and wash with plenty of soap and water. Continue to rinse for at least 10 minutes. If skin irritation or rash occurs seek medial advice / attention. Do NOT use solvents or thinners
- Eye contact

Do not rub. Immediately rinse eyes cautiously with plenty of water for at least 15 minutes holding the eyelids open. Remove contact lenses if present

HydroCoat 107 Elastic 2K Part B

Cementitious Flexible Waterproofing Membrane

- Ingestion
and easy to do so, then continue to rinse cautiously for 15 minutes. Seek immediate medical attention
If swallowed, seek medical advice immediately and show the container or label and this SDS. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Keep the person warm and at rest. Do NOT induce vomiting. If vomiting occurs, the head should be kept forward and low so vomit does not enter the lungs.
- Inhalation
Ventilate the area. Remove person from the contaminated place to rest in fresh air and keep comfortable and breathing. Assure fresh air breathing. Loosen tight clothing such as collar, tie, belt or waistband. If you feel unwell seek medical advice. Call a doctor or poison centre if you feel unwell
- Self-protection for first aiders
No action to be taken involving any personal risk or without suitable training. If it is suspected that the mixture is still present, wear appropriate Personal Protection Equipment, see SECTION 8.2. If suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wear gloves to remove contaminated clothing, see SECTION 13 for washing or disposal

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Potential acute health effects:

- Skin contact
No known significant effects or critical hazards
- Eye contact
No known significant effects or critical hazards
- Ingestion
No known significant effects or critical hazards
- Inhalation
No known significant effects or critical hazards

Over-exposure signs / symptoms:

- Skin contact
No specific data
- Eye contact
No specific data
- Ingestion
No specific data
- Inhalation
No specific data

4.3 Indication of Any Immediate Medical Attention and Special Treatment Needed

- Notes to physician
Treat symptomatically. Contact poison centre immediately if large quantities have been ingested or inhaled
- Specific treatments
No specific treatment

SECTION 5. Fire-Fighting Measures

- 5.1 Extinguishing Media**
Use an extinguishing media suitable for the surrounding fire
Unsuitable extinguishing media: None known

- 5.2 Special Hazards Arising from the Material**
No specific fire or explosion hazard
Decomposition products may include: carbon dioxide, carbon monoxide, metal oxide / oxides

- 5.3 Advice for Firefighters**
Isolate the affected area
All persons to be immediately removed from the vicinity of the fire. Fire to be dealt with by trained personnel and without involving personal risk
Exercise caution when fighting any chemical fire
Do not enter the area without wearing appropriate protective equipment and self-contained breathing apparatus (SCBA) with full face-piece operated

HydroCoat 107 Elastic 2K Part B

Cementitious Flexible Waterproofing Membrane

in positive pressure mode. Clothing, including helmets, protective boots and gloves, conforming to EN 469 will provide a basic level of protection for chemical incidents

SECTION 6. Accidental Release Measures

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

- **General measures**
Do not attempt to take action without wearing suitable personal protection, refer to SECTION 8.2 of the SDS
Ensure adequate ventilation
- **Non-emergency personnel**
Evacuate unnecessary personnel
Do not touch or walk through the spilled material. Ventilate spillage area. Do not breathe dust / fumes/ gas / vapours / mist / spray. Avoid contact with skin and eyes
- **Emergency personnel**
Evacuate unnecessary personnel and those not wearing the suitable protection. If outside do not approach from downwind. If outside keep bystanders and passing persons upwind and away from the danger point. Mark out the contaminated area with signage and prevent access by unauthorised persons
Do not attempt to take action without suitable protective equipment. Equip clean-up crew with proper protection, see SECTION 8 'Exposure controls / personal protection'
Ensure adequate ventilation, including forced ventilation if in an internal space and necessary, and vent externally to be safely away from other persons and the general public
Turn leaking containers leak-side up to prevent the escape of material, and place in a sealable leak proof container, label this with the contents
Avoid inhalation of vapours, wear respiratory protection as SECTION 8.2

6.2 Environmental Precautions

Prevent the product from contact with soil and from entering soil, drains, sewers or watercourses (refer to SECTION 11). Contain the spillage using bunding
Alert the Environmental Agency in the event of spillage, etc entering water ways, sewers, drains, soil or air

6.3 Methods and Materials for Containment and Cleaning Up

Clean-up should ONLY be dealt with by qualified persons familiar with the specific product. Approach from upwind against dust inhalation
Stop the leak if it is safe to do so. Avoid dust generation
Move the containers from the spill area, except any damaged containers which should be collected along with the spillage
Both small and large spillages should be vacuumed or swept up WITHOUT creating dust. Using a vacuum with a HEPA filter will reduce dust dispersal
All collected spillages and damaged containers to be retained within and fully collected up into sealable impervious waste container(s), label these with the contents
If used, all contaminated bunding, including all suspected of being contaminated, to be collected up and transferred to these waste containers
All containers to be labelled and held for disposal as SECTION 13

6.4 Reference to Other SECTIONS

Sections 1 (emergency contact), 8 (Personal Protection/Exposure Controls), 12 (Ecological Information) and 13 (Disposal Consideration) of the SDS

HydroCoat 107 Elastic 2K Part B

Cementitious Flexible Waterproofing Membrane

SECTION 7. Handling and Storage

The information in the SECTION includes generic advice and guidance. The list of 'Relevant identified uses' in SECTION 1 should be consulted for any available use-specific information provided here and in SECTION 8

7.1 Precautions for Safe Handling

- a. Safe handling
 - Wear protective equipment as required by use- see SECTION 8
 - Do not get in eyes, on skin or on clothing - see SECTION 8 for the protection of work clothing. Do not ingest. Obtain special instructions before use. Do not handle or use until all safety precautions have been read and understood.
 - Only use outdoors or in well ventilated areas, wear appropriate respirator when ventilation is inadequate. Keep in original container, kept tightly closed when not in use
 - Do not breathe vapours, aerosols or gases
- b. Hygiene measures
 - Eating, drinking or smoking should be prohibited in area where this material is handled, stored and processed / used. Wash hands and other exposed areas with mild soap and water and remove contaminated clothing and protective equipment before entering areas where food and drink are consumed and when leaving the work site. Wash hands and face before eating, drinking, smoking and using the toilet
 - Contaminated work clothing should be securely bagged before being allowed out of the work site. See SECTION 13 for the protection of work clothing and the washing or disposal of contaminated work clothing and boots
- c. Prevention of handling incompatible substances or mixtures
 - Do not handle other substances or mixtures at the same time. Keep away from other substances and mixtures
- d. Operations and conditions that could create new risks
 - Do not allow opened, part used or the container in use to come into contact with other materials including all surfaces around. Ensure the containers are securely sealed during transport, storage and when at the work site
- e. Reduce risk of release to the environment
 - Avoid spillage. Ensure the floor at storage, transport and the work location will not allow access to drains, sewers, water courses and soil. Lay heavy gauge plastic sheeting or similarly impervious protective covering when mixing and dispensing. Contain and clean up spillage as SECTION 6.3 of the SDS

7.2 Conditions for Safe Storage, Including Any Incompatibilities

- a. Storage conditions
 - Store in a well ventilated locked area, keep cool and away from direct sunlight. Only store in original containers. If transferred to another container include the Batch Number and Manufacturing or Expiry Date on the new label. Keep container tightly closed. The floor of the storage area to be impermeable to prevent the escape of spillage
- b. Maximum storage period
 - Maximum storage / use period: 12 months at 20°C (68°F), refer to the container label for the Date of Manufacture, Expiry Date or Best Before Date
 - Use of the stock should be by date rotation, using the oldest dates first. Containers past their Best Before date should be removed for disposal according to SECTION 13 of the SDS
- c. Control of the effects of weather, ambient pressure, temperature, sunlight, humidity and vibration
 - Protect from freezing, frost, heat and direct sunlight. Keep away from sources of ignition, open flames or excessive heat
 - Ensure containers are securely closed against vibration spillage during

HydroCoat 107 Elastic 2K Part B

Cementitious Flexible Waterproofing Membrane

transport when loading / unloading vehicles, during transport and moving from vehicle to the work location. Unopened containers to be protected against damage during these movements

d. Storage with other substances and mixtures

Only store in the original packaging. Store against falling / touching other materials and in an allocated location

e. Storage room design, quantity limits, ventilation and packaging compatibilities

Storage room to be dry, ventilated, and constructed to have impermeable floors and walls to prevent the escape of spillages into the environment

f. Other considerations

No other data available

7.3 Specific End Use(es)

Part B of a 2-Part liquid applied cementitious waterproofing membrane. Refer to the Technical Data Sheet for further information

SECTION 8. Personal Protection/Exposure Control

8.1 Control Parameters

Workplace Exposure Limits (WEL)

EH40: Taken from the HSE EH40/2005 (3rd edition, published 2018):

- not stated = not on EH40
- if no 15 min STEL, 3x TWA used

Carc: Capable of causing cancer and / or heritable genetic damage

Sen: Capable of causing occupational asthma

Sk: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systematic toxicity

Substance & CAS	Long-term exposure limit (8hr TWA reference period)		Short-term exposure limit (15 minute reference period)		Comments	Source
	ppm	mg / m ³	ppm	mg / m ³		
Crystalline silica - respirable dust					The Carc, Sen and Sk notations are not exhaustive. Notations have been applied to substances identified in IOELV Directives	
14808-60-7	-	0.1	-	-	-	EH40

Recommended monitoring procedures Reference should be made to monitoring standards, such as:

EN 689 Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy

EN 14042 Workplace atmospheres - Guide for the application and use for the assessment of exposure to chemical and biological agents

EN 482 Workplace atmospheres - General requirement for the performance of procedures for the measurement of chemical agents

Reference to national guidance documents for methods for the determination of hazardous substances will also be required

DNELs / DMELs

No DNELs / DMELs available

PNECs

No PNECs available

8.2 Exposure Controls

8.2.1 Appropriate Engineering Controls

a. Ventilation

Ensure there is sufficient ventilation in the area, including forced ventilation if necessary or in an internal or enclosed space with safe exhaust away from other persons. The floor must be impermeable to prevent the escape of liquids, laying impermeable protective covering if in doubt

HydroCoat 107 Elastic 2K Part B

Cementitious Flexible Waterproofing Membrane

- b. Isolation
Isolate the work area with warning signage against unauthorised access. Ensure all other persons are pre-notified of the works and remain clear of the work area
- c. Washing
Provide eye wash facilities, individual eye wash ampoules and safety shower
- d. Against contamination
Refer to SECTION 15.1 for any 'Other Regulations' and the REACH Annex XVII statements there
Only mix the 2 Parts of the product on impervious protective sheeting and with this laid at the area(s) where the mixed product is to be applied, against splashes onto the person(s) performing this task, any other persons and onto the surrounding areas:
- When opening each Part and when progressively mixing them together
 - When using the power mixer / paddle off a drill, include erecting barrier around if necessary to stop splashes off the protective sheeting onto other persons, structures, ground, etc
 - When applying the mixed product to the area(s) to be treated
 - The person(s) performing this to wear disposable overshoes over their safety work boots when working off the protective sheeting against walking contamination onto the surrounding area
 - When the mixing is done, dispose of the contaminated protective sheeting, the overshoes, etc as controlled waste
- e. Mists
Prevent the formation of vapour or aerosol
- f. Hygiene & Occupational care
Do not eat, drink or smoke during stirring or use of the product. Wash hands with soap and water before eating, drinking, smoking, using the toilet and when leaving the work site for natural breaks, break times and at end of day. Remove contaminated clothing, see SECTION 13 for the washing or disposal of contaminated clothing
- ### 8.2.2 Personal Protective Equipment
- a. Work clothing
Impervious disposable 1-piece covering to body, legs and arms with closure at wrists and ankles, and disposable overshoes. EN ISO 13688
- b. Eye / face protection
Tight fitting safety chemical goggles / safety glasses with side protection designed to protect against splashes, mists, gases or dusts. EN166
If at risk of splashing to face when mixing and using the 2-part product wear a full face visor
- c. Skin protection
- (i) Hand Protection
When only handling Part B: Use chemical resistant gloves classified under EN 374: Protective gloves against chemicals and micro-organisms
When mixing with Part A and handling the resultant mixture: Wear gloves according to Part A and providing protection against chemicals and micro-organisms
- (ii) Other
Chemical resistant safety boots with external feed for the laces, not holes for the laces
Safety helmet if required, or other head covering, against splashes
Any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling the product
Good hygiene measures should be followed at all time
- d. Respiratory protection
Mist formation: wear protection as for inadequate ventilation
When only handling Part B: Use a properly fitted particulate filter respirator complying with an approved Standard is a Risk Assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator

HydroCoat 107 Elastic 2K Part B

Cementitious Flexible Waterproofing Membrane

When mixing with Part A and handling the resultant mixture:

- | | |
|------------------------------------|--|
| | Respiratory protection as for Part A and against dust according to the Risk Assessment |
| e. Thermal hazards | NDA |
| f. Environmental exposure measures | Avoid release to the environment |
| | Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental legislation. In some cases fume scrubbers, ventilation filters, engineering modifications to the process ./ equipment will be necessary to reduce emissions to acceptable levels |

SECTION 9. Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

- | | | |
|---|-------------|---|
| • Appearance | (i) Form | Solid, powder |
| | (ii) Colour | Grey |
| • Odour | | Odourless |
| • Odour threshold | | NDA |
| • pH | | N/A |
| • Melting point/range °C | | NDA |
| • Freezing point/range °C | | NDA |
| • Initial boiling point/range °C | | NDA |
| • Flash point/self-ignition °C | | Closed cup: 101°C |
| • Evaporation rate | | NDA |
| • Flammability (solid, gas) | | NDA |
| • Flammability limits, lower % | | NDA |
| • Flammability limits, upper % | | NDA |
| • Auto flammability °C | | NDA |
| • Decomposition temperature | | NDA |
| • Explosive properties | | NDA |
| • Explosive limits | | NDA |
| • Oxidising properties | | NDA |
| • Vapour pressure | | NDA |
| • Relative vapour density at 20°C | | NDA |
| • Relative density | | 2.71 |
| • Specific weight | | NDA |
| • Solubility in water | | In cold water |
| • Partition coefficient n-octanol/water | | NDA |
| • Also soluble in | | NDA |
| • Viscosity, kinematic | | 999 mm ² /s (room temperature) |
| • Viscosity, dynamic | | NDA |
| • VOC g/l | | NDA |

NOTE:

The above values related to physiochemical properties are typical values for this product and should not, therefore, be construed as a specification

9.2 Other Information

NDA

HydroCoat 107 Elastic 2K Part B

Cementitious Flexible Waterproofing Membrane

SECTION 10. Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients
10.2 Chemical Stability	The product is stable under recommended transport or storage conditions and when protected against the materials or conditions listed in SECTIONS 10.1 and 10.3
10.3 Possibility of Hazardous Reactions	Under normal conditions of storage and use, hazardous reactions will not occur
10.4 Conditions to Avoid	No specific data
10.5 Incompatible Materials to Avoid	No specific data
10.6 Hazardous Decomposition Products	Under normal conditions of storage and use, hazardous decomposition products should not be produced

SECTION 11. Toxicological Information

11.1 Information on Toxicological Effects

- Other hazards

Hazard	Basis
Acute toxicity - oral	NDA
Acute toxicity - dermal	NDA
Acute toxicity - inhalation	NDA
Respiratory hazard / inhalation	NDA
Serious eye damage / irritation	NDA
Skin sensitisation	NDA
Skin corrosion / irritation	NDA
Ingestion	NDA
Carcinogenicity	NDA
Germ cell mutagenicity	NDA
Reproductive toxicity	NDA
Teratogenicity	NDA
Aspiration hazard	NDA
STOT single exposure	NDA
STOT repeated exposure	NDA

Viscosity, kinematic 999 mm²/s

- Information on likely routes of exposure

NDA

- Potential acute health effects

Eye contact	- No known significant effects or critical hazards
Inhalation	- No known significant effects or critical hazards
Skin contact	- No known significant effects or critical hazards
Ingestion	- No known significant effects or critical hazards
- Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	- No specific data
Inhalation	- No specific data
Skin contact	- No specific data
Ingestion	- No specific data

HydroCoat 107 Elastic 2K Part B

Cementitious Flexible Waterproofing Membrane

- Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short-term exposure	Potential immediate effects	- NDA
	Potential delayed effects	- NDA
Long-term exposure	Potential immediate effects	- NDA
	Potential delayed effects	- NDA
Potential chronic health effects	NDA	
Conclusion	NDA	
	General	- No known significant effects of critical hazard
	Carcinogenicity	- No known significant effects of critical hazard
	Mutagenicity	- No known significant effects of critical hazard
	Teratogenicity	- No known significant effects of critical hazard
	Developmental effects	- No known significant effects of critical hazards
	Fertility effects	- No known significant effects of critical hazard
- Other information

NDA
The product was not tested. The data reported here are based on the manufacturer's SDS which is based on information contained in the safety data sheets of the raw materials that make up the product

SECTION 12. Ecological Information

- | | |
|---------------------------------------|--|
| 12.1 Toxicity | NDA |
| 12.2 Persistence and Biodegradability | NDA |
| 12.3 Bioaccumulative Potential | NDA |
| 12.4 Mobility in Soil | NDA |
| 12.5 Results of PBT & vPvT Assessment | N/A |
| 12.6 Other Adverse Effects | No known significant effects or critical hazards
Do not release to the environment |
| 12.7 Additional information | The product was not tested. The data reported here are based on the manufacturers' SDS which is based on information contained in the safety data sheets of the raw materials that make up the product
No other information available |

SECTION 13. Disposal Considerations

13.1 Waste Treatment Methods

- Recovery operations

Treat as SECTION 6: Accidental Release Measures

- Disposal operations

Product - dispose at approved waste collection sites as controlled waste
--
- Disposal of packaging

Paper bag - always has remnants, dispose of a controlled waste
--
- Waste code number

Part B:	08 02 01
Wet & cured mixed Part A+Part B:	08 01 11*
Part B Packaging:	15 01 01
- Special precautions for the disposal method

The container will always retain residues. Do not attempt to wash it out to remove the residues to avoid dispersal of the wash and runoff to be in contact with soil, waterways, drains and sewers

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out.

Ensure substances or mixtures are not mixed with other materials and if held in the same outer container with other materials all are in separate

HydroCoat 107 Elastic 2K Part B

Cementitious Flexible Waterproofing Membrane

sealed containers within the outer container

- NB

The user's attention is drawn to the possible existence of regional or national regulations regarding disposal

SECTION 14. Transport Information

ADR	IMDG	IATA	ADN	RID
14.1 UN Number				
Not regulated	Not regulated	Not regulated	NDA	Not regulated
14.2 UN proper shipping name				
-	-	-	NDA	-
14.3 Transport hazard class(es)				
-	-	-	NDA	-
14.4 Packing group				
-	-	-	NDA	-
14.5 Environmental hazards				
No	No	No	NDA	No
No supplementary information available IMDG Code Segregation Group: N/A				

14.6 Special Precautions for User

Always transport in closed containers that secure against damage, Ensure that persons transporting the product know what to do in the event of an accident or spillage

- Overland transport N/A
- Transport by sea N/A
- Air transport N/A
- Inland waterway transport N/A
- Rail transport N/A

14.7 Transport in Bulk According to:

Transport in bulk in not available / offered

- (i) Annex II of Marpol N/A
- (ii) the IBC Code N/A

SECTION 15. Regulatory Information

15.1 Safety, Health and Environmental Regulations/Legislation Specific for the Substance, Mixture or Article

COMMISSION REGULATIONS (EC) No 1272/2008 and (EU) No 2015/830 of 28/05/2015 amending Regulation (EC) No 1907/2006 and repealing (EU) 453/2010 20 May 2010 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

- Other regulations, limitations and prohibitive regulations

Contains no REACH substances with Annex XVII restrictions

Annex XVII Restrictions: N/A

Other EU Regulations: Not determined

Special packaging requirements: N/A

Ozone depleting substances (1005/2009/EU): Not listed

Prior Informed Consent (PIC) (649/2012/EU): Not listed

HydroCoat 107 Elastic 2K Part B

Cementitious Flexible Waterproofing Membrane

National Regulations: Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II and Regulation (EC) No. 1272/2008 (CLP)

15.2 Chemical Safety Assessment

A chemical safety assessment has not been carried out. Data from the component substances is included in this SDS

SECTION 16. Other Information

16.1 Basis of this SDS

The data reported here are based on the manufacturer's SDS which is based on information contained in the safety data sheets of the raw materials that make up the product

16.2 Changes Compared to the Previous Version

Date	Replaces	Sections	Item	Change	Comment
22/03/20	1.0	All	All	See Comment	This is a full rewrite, read the entire document

16.3 Key literature and sources of data

Regulation (EC) 1907/2006
Regulation (EC) No. 1272/2008
Regulation (EU) No. 2015/830
Supplier SDS
ECHA, including REACH dossier for component substances
EH40/2005 3rd Edition, 2018

16.4 Abbreviations & Acronyms

ATE: aCUTE tOXICITY eSTIMATE

CLP: EU Regulation 1272/2008: Classification, Labelling & packaging of chemical substances

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level

HSE: (UK) Health & Safety Executive

IBC Code: International Building Code

LD50: Lethal dose, 50% affected

MARPOL: International Convention for the Prevention of Pollution from Ships

N/A: Not Applicable

NDA: No Data Available

PBT: Persistent, Bioaccumulative and Toxic substances

vPvB: Very Persistent and very Bioaccumulative substances

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals: Regulation (EC) No 1907/2006

SDS: Safety Data Sheet

STEL: Short Term Exposure Limit

STOT RE: Specific target organ toxicity (from) repeated exposure

STOT SE: Specific target organ toxicity (from) single exposure

TWA: Time Weighted Averages

VOC: Volatile organic compounds

16.5 Procedure used to derive the Classification according to Regulation (EC) No. 1272/2008

Classification	Justification
Not classified	

16.6 Full text of H and EUH statements N/A

16.7 Full text of Classifications (CLP / GHS)

N/A

HydroCoat 107 Elastic 2K Part B

Cementitious Flexible Waterproofing Membrane

16.8 Training advice

Obtain special instructions and read the Safety Data Sheet before use. Do not handle until all safety precautions have been read and understood. It is recommended that workers are trained in the safe handling of hazardous chemicals

16.9 DISCLAIMER

Persons using the information contained here must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where these purposes are other than as specifically recommended in this Safety Data Sheet and in the Technical Data Sheet, then the user uses the product at their own risk

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the Company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability of such information for their own particular use