



ISOTHERM MEMBRANE
Declaration of Performance
No CPR-GB1/0170

DECLARATION OF PERFORMANCE No CPR-GB1/0170

- 1) Unique identification code of the product-type: **ISOTHERM MEMBRANE**
- 2) Intended uses: **Plastic and rubber flexible sheets (Type B) for use as water vapour control layers in buildings.**
- 3) Manufacturer: **Mapei Uk Ltd - Mapei House - Steel Park Road, Halesowen, West Midlands B62 8HD - United Kingdom - www.mapei.co.uk**
- 4) Harmonized standards: **EN 13984:2013**

No: Notified bodies:

0068 MTIC InterCert S.r.l.

- 5) Performances declared and Assessment and Verification of Constancy of Performance (AVCP):

Essential characteristics	Performances	AVCP
Resistance to impact:	NPD	-
Durability: - water vapour resistance after artificial ageing: - chemical resistance:	Pass Pass	4
Resistance to tearing:	longitudinal resistance to tearing (nail shank) ≥ 185 N transversal resistance to tearing (nail shank) ≥ 235 N	4
Joint strength:	NPD	-
Water vapour resistance:	$\mu = 57 \pm 13,5$	3
Tensile properties:	longitudinal tensile strength $\geq 2,8$ N/mm ² transversal tensile strength $\geq 2,0$ N/mm ² longitudinal elongation ≥ 35 % transversal elongation $\geq 45\%$	4
Reaction to fire:	NPD	-



ISOTHERM MEMBRANE
Declaration of Performance
No CPR-GB1/0170

Dangerous substances:	NPD	-
------------------------------	------------	----------

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Paul Hodgetts – Quality Manager**

Halesowen, 09/04/2026

.....
DoP in Pdf format are available in the Mapei website.

<i>Revision 10 notes:</i>	<i>First issue.</i>
---------------------------	---------------------

REACH information: *this is an article in accordance with Article 3 of the REACH Regulation (EC) no. 1907/2006 and pursuant to Article 31 and 33 of the above-mentioned Regulation does not require any Safety Data Sheet. While using the product, pay attention to the recommendations written in the Technical Data Sheet and to the safety requirements laid down in the workplace.*

 0068	 Mapei House - Steel Park Road, Halesowen, West Midlands B62 8HD - United Kingdom www.mapei.co.uk												
26 CPR-GB1/0170 EN 13984 ISOTHERM MEMBRANE Plastic and rubber flexible sheets (Type B) for use as water vapour control layers in buildings.													
<table border="0"> <tr> <td colspan="2">Durability:</td></tr> <tr> <td>- water vapour resistance after artificial ageing:</td><td>Pass</td></tr> <tr> <td>- chemical resistance:</td><td>Pass</td></tr> <tr> <td>Resistance to tearing:</td><td>longitudinal resistance to tearing (nail shank) ≥ 185 N transversal resistance to tearing (nail shank) ≥ 235 N</td></tr> <tr> <td>Water vapour resistance:</td><td>$\mu = 57 \pm 13,5$</td></tr> <tr> <td>Tensile properties:</td><td>longitudinal tensile strength ≥ 2,8 N/mm² transversal tensile strength ≥ 2,0 N/mm² longitudinal elongation ≥ 35 % transversal elongation ≥ 45%</td></tr> </table>		Durability:		- water vapour resistance after artificial ageing:	Pass	- chemical resistance:	Pass	Resistance to tearing:	longitudinal resistance to tearing (nail shank) ≥ 185 N transversal resistance to tearing (nail shank) ≥ 235 N	Water vapour resistance:	$\mu = 57 \pm 13,5$	Tensile properties:	longitudinal tensile strength ≥ 2,8 N/mm ² transversal tensile strength ≥ 2,0 N/mm ² longitudinal elongation ≥ 35 % transversal elongation ≥ 45%
Durability:													
- water vapour resistance after artificial ageing:	Pass												
- chemical resistance:	Pass												
Resistance to tearing:	longitudinal resistance to tearing (nail shank) ≥ 185 N transversal resistance to tearing (nail shank) ≥ 235 N												
Water vapour resistance:	$\mu = 57 \pm 13,5$												
Tensile properties:	longitudinal tensile strength ≥ 2,8 N/mm ² transversal tensile strength ≥ 2,0 N/mm ² longitudinal elongation ≥ 35 % transversal elongation ≥ 45%												

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.