

21.10.2025

Kit components

Product code	Description
--------------	-------------

7,202	PermaCOAT PRO High Build Epoxy Floor Coating
--------------	---

Components:

4,524	PermaCOAT PRO High Build Epoxy Floor Coating Base
4,525	PermaCOAT PRO High Build Epoxy Floor Coating Hardener

Safety Data Sheet according to UK REACH (SI 2020/1577) as amended

Printing date 21.10.2025

Version number 1

Revision: 21.10.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name:** PermaCOAT PRO High Build Epoxy Floor Coating Base

· **Registration number** Mixture

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Product category** PC1 Adhesives, sealants

· **Application of the substance / the mixture** Coating

· **Uses advised against**

Any use carrying a risk of direct contact with eyes/skin where workers are exposed without adequate personal protective equipment (PPE).

Any use involving significant release of aerosol, vapour or dust in the breathing zone of workers where they are exposed without suitable respiratory protective equipment (RPE).

Processes involving extreme heat use advised against.

The product is strictly intended for industrial or professional use only.

· **1.3 Details of the supplier of the safety data sheet**

· **Supplier:**

Permagard Products Ltd
Chitting Industrial Estate
Avonmouth
Bristol BS11 0YB
England

Tel: 0117 82 3282

Email: sales@permagard.co.uk

· **Further information obtainable from:** Product safety department.

· **1.4 Emergency telephone number:**

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to GB-CLP**

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 1A H360F May damage fertility.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· **2.2 Label elements**

· **Labelling according to GB-CLP** The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS07

GHS08

GHS09

· **Signal word** Danger

· **Hazard-determining components of labelling:**

bis[4-(2,3-epoxypropoxy)phenyl]propane

Oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Bisphenol F-epoxy resin

· **Hazard statements**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H360F May damage fertility.

H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P261 Avoid breathing mist/vapours/spray.

P273 Avoid release to the environment.

(Contd. on page 2)

Safety Data Sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 21.10.2025

Version number 1

Revision: 21.10.2025

Trade name: PermaCOAT PRO High Build Epoxy Floor Coating Base

(Contd. of page 1)

- P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local regulations.

2.3 Other hazards
Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

- **Description:** Mixture of substances listed below with nonhazardous additions.

• Dangerous components:		
CAS: 14808-60-7 EINECS: 238-878-4 Reg.nr.: 01-2120770509-45-XXXX	Quartz (SiO ₂) substance with a workplace exposure limit	50 – 100%
CAS: 1675-54-3 EINECS: 216-823-5 Index number: 603-073-00-2 Reg.nr.: 01-2119456619-26-XXXX	bis[4-(2,3-epoxypropoxy)phenyl]propane ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 %	10 – < 25%
EC number: 701-263-0 Reg.nr.: 01-2119454392-40-XXXX	Bisphenol F-epoxy resin ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Skin Sens. 1A, H317	2.5 – < 10%
CAS: 68609-97-2 EINECS: 271-846-8 Index number: 603-103-00-4 Reg.nr.: 01-2119485289-22-XXXX	Oxirane, mono[(C12-14-alkyloxy)methyl] derivs ⚠ Repr. 1A, H360F; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	2.5 – < 10%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Remove the subject from the contaminated area as soon as possible.
Seek immediate medical advice.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Check for and remove any contact lenses.
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
Wash mouth out with water
Do not induce vomiting; call for medical help immediately.
If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
- **Information for doctor:** Treat symptomatically and supportively.
- **4.2 Most important symptoms and effects, both acute and delayed** Allergic reactions
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media
Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
 Use fire extinguishing methods suitable to surrounding conditions.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

5.2 Special hazards arising from the substance or mixture

Combustible

In case of fire, the following can be released:

Carbon monoxide and carbon dioxide
 Nitrogen oxides (NO_x)
 Halogen compounds

5.3 Advice for firefighters
Protective equipment:

Wear self-contained respiratory protective device.
 Do not inhale explosion gases or combustion gases.

(Contd. on page 3)

Safety Data Sheet according to UK REACH (SI 2020/1577) as amended

Printing date 21.10.2025

Version number 1

Revision: 21.10.2025

Trade name: PermaCOAT PRO High Build Epoxy Floor Coating Base

(Contd. of page 2)

Wear fully protective suit.

· **Additional information**

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Particular danger of slipping on leaked/spilled product.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· **6.2 Environmental precautions:**

Do not allow to penetrate the ground/soil.

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

· **6.3 Methods and material for containment and cleaning up:**

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid direct contact (skin/eye contact, ingestion and/or inhalation of fume/mist/dust) with the product in the undiluted form.

· **Information about fire - and explosion protection:** No special measures required.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Prevent any seepage into the ground.

· **Information about storage in one common storage facility:** Store away from oxidising agents.

· **Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· **Storage class:** 6.1 C

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

CAS: 14808-60-7 Quartz (SiO₂)

OEL Short-term value: 0.3 mg/m³

Long-term value: 0.1 mg/m³

· **DNELs**

CAS: 1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

Oral Long-term systemic effects 500 µg/kg bw/day (general population)

Dermal Long-term systemic effects 89.3 µg/kg bw/day (general population)

750 µg/kg bw/day (worker)

Inhalative Long-term systemic effects 4.93 mg/m³ (worker)

Long-term systemic effects 870 µg/m³ (general population)

Bisphenol F-epoxy resin

Oral Long-term systemic effects 6.25 mg/kg bw/day (general population)

Dermal Long-term systemic effects 62.5 mg/kg bw/day (general population)

104.15 mg/kg bw/day (worker)

Inhalative Long-term systemic effects 8.7 mg/m³ (general population)

29.39 mg/m³ (worker)

CAS: 68609-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Oral Long-term systemic effects 500 µg/kg bw/day (general population)

Dermal Long-term systemic effects 1 mg/kg bw/day (worker)

(Contd. on page 4)

Safety Data Sheet according to UK REACH (SI 2020/1577) as amended

Printing date 21.10.2025

Version number 1

Revision: 21.10.2025

Trade name: PermaCOAT PRO High Build Epoxy Floor Coating Base

(Contd. of page 3)

Inhalative	Long-term systemic effects	500 µg/kg bw/day (general population)
	Long-term systemic effects	3.6 mg/m ³ (worker)
	Long-term systemic effects	870 µg/m ³ (general population)
· PNECs		
CAS: 1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane		
Freshwater		6 µg/L
Freshwater - Intermittent releases		18 µg/L
Marine water		600 ng/L
Marine Water - Intermittent releases		1.8 µg/L
Sewage Treatment Plant		10 mg/L
Sediment (freshwater)		341 µg/kg
Sediment (marine water)		34.14 µg/kg
Soil		64.7 µg/kg
Secondary poisoning		11 mg/kg food
Bisphenol F-epoxy resin		
Freshwater		3 µg/L
Freshwater - Intermittent releases		25.4 µg/L
Marine water		300 ng/L
Sewage Treatment Plant		10 mg/L
Sediment (freshwater)		294 µg/kg
Sediment (marine water)		29.4 µg/kg
Soil		237 µg/kg
CAS: 68609-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivs		
Freshwater		105.8 µg/L
Freshwater - Intermittent releases		72 µg/L
Marine water		10.58 µg/L
Sewage Treatment Plant		10 mg/L
Sediment (freshwater)		307.16 mg/kg
Sediment (marine water)		30.72 mg/kg
Soil		1.234 mg/kg

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Ensure that eyewash stations and safety showers are close to the workstation location.

· **Respiratory protection:** Use suitable respiratory protective device in case of insufficient ventilation.

· **Hand protection**



Protective gloves.

Use gloves tested and approved under appropriate government standards such as NIOSH (US) or EN374 (EU).

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



Safety glasses with side-shields conforming to EN166.

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

(Contd. on page 5)

Safety Data Sheet according to UK REACH (SI 2020/1577) as amended

Printing date 21.10.2025

Version number 1

Revision: 21.10.2025

Trade name: PermaCOAT PRO High Build Epoxy Floor Coating Base

(Contd. of page 4)

· **Body protection:**



Protective work clothing

- Body protection must be chosen depending on product properties, activity and possible exposure.
- **Environmental exposure controls** Do not allow to enter drains, sewers or watercourses.
- **Risk management measures** The operators shall be instructed adequately.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· Physical state	Liquid
· Colour:	According to product specification
· Odour:	Characteristic
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	Undetermined.
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	> 93 °C
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	1.6 – 1.75 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

· **9.2 Other information**

· Appearance:	
· Form:	Liquid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not self-igniting.
· Explosive properties:	Product does not present an explosion hazard.
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	Not applicable

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** Heat and static discharge.
- **10.5 Incompatible materials:**
 - Strong acids.
 - Strong bases.
 - Strong oxidising agents.
- **10.6 Hazardous decomposition products:**
 - Carbon monoxide and carbon dioxide
 - Nitrogen oxides (NO_x)

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 6)

Safety Data Sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 21.10.2025

Version number 1

Revision: 21.10.2025

Trade name: PermaCOAT PRO High Build Epoxy Floor Coating Base

(Contd. of page 5)

· LD/LC50 values relevant for classification:		
CAS: 1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane		
Oral	LD50	> 15,000 mg/kg (rat)
Dermal	LD50	> 23,000 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** May damage fertility.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Additional toxicological information:** May cause sensitisation in susceptible persons.
- **11.2 Information on other hazards**

· Endocrine disrupting properties
None of the ingredients are listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:	
CAS: 1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane	
EC50 (72 h)	11 mg/l (algae)
Bisphenol F-epoxy resin	
EC50 (72 h)	1.8 mg/l (algae)

- **12.2 Persistence and degradability** Not easily biodegradable
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Toxic for aquatic organisms
Also poisonous for fish and plankton in water bodies.
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Recommended Hierarchy of Controls:
 - Minimise waste;
 - Reuse if not contaminated;
 - Recycle, if possible; or
 - Safe disposal (if all else fails).
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Contact waste processors for recycling information.
Used, degraded or contaminated product may be classified as hazardous waste. Anyone classifying hazardous waste and determining its fate must be qualified in accordance with state and international legislation.
- **Uncleaned packaging:**
- **Recommendation:**
Do not reuse empty containers - dispose of in accordance with the regulations issued by the appropriate local authorities.
Disposal must be made according to official regulations.

(Contd. on page 7)

Safety Data Sheet according to UK REACH (SI 2020/1577) as amended

Printing date 21.10.2025

Version number 1

Revision: 21.10.2025

Trade name: PermaCOAT PRO High Build Epoxy Floor Coating Base

(Contd. of page 6)

Containers, even those that are "empty," may contain residues that can develop flammable and/or hazardous vapours upon heating. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.

SECTION 14: Transport information

<ul style="list-style-type: none"> · 14.1 UN number or ID number · ADR, IMDG, IATA 	UN3082
<ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG · IATA 	UN3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane, Bisphenol F-epoxy resin) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane, Bisphenol F-epoxy resin), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane, Bisphenol F-epoxy resin)
<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR 	 <ul style="list-style-type: none"> · Class · Label
<ul style="list-style-type: none"> · IMDG, IATA 	 <ul style="list-style-type: none"> · Class · Label
<ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA 	III
<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR): · Special marking (IATA): 	Product contains environmentally hazardous substances: bis[4-(2,3-epoxypropoxy)phenyl]propane Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
<ul style="list-style-type: none"> · 14.6 Special precautions for user · Hazard identification number (Kemler code): · Emergency Action Code: · EMS Number: · Stowage Category 	Warning: Miscellaneous dangerous substances and articles. 90 +3Z F-A,S-F A
<ul style="list-style-type: none"> · 14.7 Maritime transport in bulk according to IMO instruments 	Not applicable.
<ul style="list-style-type: none"> · Transport/Additional information: 	Amounts up to 5kg or 5L per single or inner package are not regulated according to ADR/RID SP 375, IMDG 2.10.2.7 and IATA SP A197.
<ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 (-)

(Contd. on page 8)

Safety Data Sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 21.10.2025

Version number 1

Revision: 21.10.2025

Trade name: PermaCOAT PRO High Build Epoxy Floor Coating Base

(Contd. of page 7)

<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	<p>5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml</p>
<ul style="list-style-type: none"> · UN "Model Regulation": 	<p>UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BIS[4-(2,3-EPOXYPROPOXY)PHENYL]PROPANE, BISPHENOL F-EPOXY RESIN), 9, III</p>

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

<ul style="list-style-type: none"> · Regulated explosives precursors 	<p>None of the ingredients are listed.</p>
<ul style="list-style-type: none"> · Regulated poisons 	<p>None of the ingredients are listed.</p>
<ul style="list-style-type: none"> · Reportable explosives precursors 	<p>None of the ingredients are listed.</p>
<ul style="list-style-type: none"> · Reportable poisons 	<p>None of the ingredients are listed.</p>

- **Control Of Major Accident Hazards Regulations 2015 (COMAH)**
- **Named dangerous substances - ANNEX I** None of the ingredients are listed.
- **COMAH category E2**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

- **Relevant phrases**
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H360F May damage fertility.
 H411 Toxic to aquatic life with long lasting effects.
- **Training hints**
 This product should only be handled by workers who have received sufficient training in the safe handling and use of chemical products.
- **Department issuing SDS:** Product safety department.
- **Abbreviations and acronyms:**
 UK- REACH: The UK REACH etc. (Amendment etc.) (EU Exit) Regulations 2019 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals
 GB- CLP: Retained GB CLP Regulation (EU) No. 1272/2008 as amended for Great Britain on the Classification, Labelling and Packaging of Chemicals.
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DNEL: Derived No-Effect Level (UK REACH)
 PNEC: Predicted No-Effect Concentration (UK REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Skin Sens. 1: Skin sensitisation – Category 1
 Skin Sens. 1A: Skin sensitisation – Category 1A
 Repr. 1A: Reproductive toxicity – Category 1A
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Safety Data Sheet according to UK REACH (SI 2020/1577) as amended

Printing date 21.10.2025

Version number 1

Revision: 21.10.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name:** PermaCOAT PRO High Build Epoxy Floor Coating Hardener

· **Registration number** Mixture

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Product category** PC1 Adhesives, sealants

· **Application of the substance / the mixture** Coating

· **Uses advised against**

Any use carrying a risk of direct contact with eyes/skin where workers are exposed without adequate personal protective equipment (PPE).

Any use involving significant release of aerosol, vapour or dust in the breathing zone of workers where they are exposed without suitable respiratory protective equipment (RPE).

Processes involving extreme heat use advised against.

The product is strictly intended for industrial or professional use only.

· **1.3 Details of the supplier of the safety data sheet**

· **Supplier:**

Permagard Products Ltd
Chitting Industrial Estate
Avonmouth
Bristol BS11 0YB
England

Tel: 0117 82 3282

Email: sales@permagard.co.uk

· **Further information obtainable from:** Product safety department.

· **1.4 Emergency telephone number:**

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to GB-CLP**

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· **2.2 Label elements**

· **Labelling according to GB-CLP** The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS05

GHS07

· **Signal word** Danger

· **Hazard-determining components of labelling:**

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Benzyl alcohol

m-phenylenebis(methylamine)

Salicylic acid

· **Hazard statements**

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P362+P364 Take off contaminated clothing and wash it before reuse.

(Contd. on page 2)

Safety Data Sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 21.10.2025

Version number 1

Revision: 21.10.2025

Trade name: PermaCOAT PRO High Build Epoxy Floor Coating Hardener

(Contd. of page 1)

P405 Store locked up.
 P501 Dispose of contents/container in accordance with local regulations.

· The Detergents (Amendment) (EU Exit) Regulations 2020 / Labelling for contents perfumes (BENZYL ALCOHOL), preservation agents (BENZYL ALCOHOL), SALICYLIC ACID
--

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-XXXX	Benzyl alcohol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1B, H317 ATE: LD50 oral: 1,200 mg/kg LC50/4 h inhalative: 11 mg/l	25 – 50%
CAS: 38294-64-3 NLP: 500-101-4 Reg.nr.: 01-2119965165-33-XXXX	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Skin Sens. 1, H317; Aquatic Chronic 3, H412	25 – 50%
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50-XXXX	m-phenylenebis(methylamine) ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332	5 – 10%
CAS: 69-72-7 EINECS: 200-712-3 Index number: 607-732-00-5 Reg.nr.: 01-2119486984-17-XXXX	Salicylic acid ⚠ Repr. 2, H361d; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302	1 – 2.5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
 Immediately wash with water and soap and rinse thoroughly.
 If skin irritation continues, consult a doctor.
- **After eye contact:**
 Check for and remove any contact lenses.
 Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
 Wash mouth out with water
 Do not induce vomiting; call for medical help immediately.
 If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
- **Information for doctor:**
 Inhalation of an aerosol of this substance may cause lung oedema.
 Treat symptomatically and supportively.
- **4.2 Most important symptoms and effects, both acute and delayed** Allergic reactions
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
 CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
 Use fire extinguishing methods suitable to surrounding conditions.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
 Combustible
 In case of fire, the following can be released:
 Carbon monoxide and carbon dioxide
 Nitrogen oxides (NO_x)
- **5.3 Advice for firefighters**
- **Protective equipment:**
 Wear self-contained respiratory protective device.
 Do not inhale explosion gases or combustion gases.

(Contd. on page 3)

Safety Data Sheet according to UK REACH (SI 2020/1577) as amended

Printing date 21.10.2025

Version number 1

Revision: 21.10.2025

Trade name: PermaCOAT PRO High Build Epoxy Floor Coating Hardener

(Contd. of page 2)

Wear fully protective suit.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Particular danger of slipping on leaked/spilled product.

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow product to reach sewage system or any water course.

6.3 Methods and material for containment and cleaning up:

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid direct contact (skin/eye contact, ingestion and/or inhalation of fume/mist/dust) with the product in the undiluted form.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Safety showers and eye wash facilities should be available at the work area.

Information about fire - and explosion protection: Keep respiratory protective device available.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Prevent any seepage into the ground.

Store only in the original receptacle.

Information about storage in one common storage facility: Store away from oxidising agents.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Storage class: 8 A

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs

CAS: 100-51-6 Benzyl alcohol

Oral	Long-term systemic effects	4 mg/kg bw/day (general population)
	Short-term systemic effects	20 mg/kg bw/day (general population)
Dermal	Long-term systemic effects	4 mg/kg bw/day (general population) 8 mg/kg bw/day (worker)
	Short-term systemic effects	20 mg/kg bw/day (general population) 40 mg/kg bw/day (worker)
Inhalative	Long-term systemic effects	5.4 mg/m ³ (general population) 22 mg/m ³ (worker)
	Short-term systemic effects	27 mg/m ³ (general population) 110 mg/m ³ (worker)
CAS: 38294-64-3 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine		
Oral	Long-term systemic effects	50 µg/kg bw/day (general population)
Dermal	Long-term systemic effects	50 µg/kg bw/day (general population)

(Contd. on page 4)

Safety Data Sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 21.10.2025

Version number 1

Revision: 21.10.2025

Trade name: PermaCOAT PRO High Build Epoxy Floor Coating Hardener

(Contd. of page 3)

Inhalative	Long-term systemic effects	140 µg/kg bw/day (worker) 74 µg/m ³ (general population) 493 µg/m ³ (worker)
CAS: 1477-55-0 m-phenylenebis(methylamine)		
Dermal	Long-term systemic effects	330 µg/kg bw/day (worker)
Inhalative	Long-term systemic effects	1.2 mg/m ³ (worker)
	Long-term local effects	200 µg/m ³ (worker)
CAS: 69-72-7 Salicylic acid		
Oral	Long-term systemic effects	1 mg/kg bw/day (general population)
	Short-term systemic effects	4 mg/kg bw/day (general population)
Dermal	Long-term systemic effects	1 mg/kg bw/day (general population)
		2.3 mg/kg bw/day (worker)
Inhalative	Long-term systemic effects	4 mg/m ³ (general population)
		5 mg/m ³ (worker)
	Long-term local effects	5 mg/m ³ (worker)
· PNECs		
CAS: 100-51-6 Benzyl alcohol		
Freshwater		1 – 1.02 mg/L
Freshwater - Intermittent releases		2.3 mg/L
Marine water		100 – 102 µg/L
Sewage Treatment Plant		39 mg/L
Sediment (freshwater)		5.27 mg/kg
Sediment (marine water)		527 µg/kg
Soil		456 µg/kg
CAS: 38294-64-3 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine		
Freshwater		11.1 µg/L
Freshwater - Intermittent releases		111 µg/L
Marine water		1.11 µg/L
Sewage Treatment Plant		10 mg/L
Sediment (freshwater)		4,320 mg/kg
Sediment (marine water)		432 mg/kg
Soil		864 mg/kg
Secondary poisoning		1 mg/kg food
CAS: 1477-55-0 m-phenylenebis(methylamine)		
Freshwater		94 µg/L
Freshwater - Intermittent releases		152 µg/L
Marine water		9.4 µg/L
Sewage Treatment Plant		10 mg/L
Sediment (freshwater)		12.4 mg/kg
Sediment (marine water)		1.24 mg/kg
Soil		2.44 mg/kg
CAS: 69-72-7 Salicylic acid		
Freshwater		200 µg/L
Freshwater - Intermittent releases		1 mg/L
Marine water		20 µg/L
Sewage Treatment Plant		162 mg/L
Sediment (freshwater)		1.42 mg/kg
Sediment (marine water)		142 µg/kg
Soil		166 µg/kg

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

(Contd. on page 5)

Safety Data Sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 21.10.2025

Version number 1

Revision: 21.10.2025

Trade name: PermaCOAT PRO High Build Epoxy Floor Coating Hardener

(Contd. of page 4)

- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.
- Ensure that eyewash stations and safety showers are close to the workstation location.
- **Respiratory protection:** Use suitable respiratory protective device in case of insufficient ventilation.
- **Hand protection**



Protective gloves.
Use gloves tested and approved under appropriate government standards such as NIOSH (US) or EN374 (EU).

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye/face protection**



Safety glasses with side-shields conforming to EN166.
Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

- **Body protection:**



Protective work clothing

Do not get on skin or clothing. Wear clothing and footwear that cannot be penetrated by the product. Suitable protective equipment may include: Chemical resistant boots, Chemical resistant apron, Full chemical protective suit with a hood, Chemical protective suit consisting of a jacket and trousers. The jacket should be buttoned up to the neck, sleeves sealed at the gloves, and trouser legs worn outside the boots. These precautions are required to prevent the clothing from accidentally trapping product against the skin.

- **Environmental exposure controls** Do not allow to enter drains, sewers or watercourses.

- **Risk management measures** The operators shall be instructed adequately.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Physical state**

Liquid

- **Colour:**

Colourless - pale yellow

- **Odour:**

Amine-like

- **Melting point/freezing point:**

Undetermined.

- **Boiling point or initial boiling point and boiling range**

205.4 °C (CAS: 100-51-6 Benzyl alcohol)

- **Flammability**

Not applicable.

- **Lower and upper explosion limit**

- **Lower:**

1.3 Vol % (CAS: 100-51-6 Benzyl alcohol)

- **Upper:**

13 Vol % (CAS: 100-51-6 Benzyl alcohol)

- **Flash point:**

> 93 °C

- **Auto-ignition temperature:**

435 °C (CAS: 100-51-6 Benzyl alcohol)

- **Decomposition temperature:**

Not determined.

- **pH**

Not determined.

- **Viscosity:**

- **Kinematic viscosity**

Not determined.

- **Dynamic:**

Not determined.

- **Solubility**

- **water:**

Not miscible or difficult to mix.

- **Partition coefficient n-octanol/water (log value)**

Not determined.

- **Vapour pressure at 20 °C:**

0.1 hPa (CAS: 100-51-6 Benzyl alcohol)

- **Vapour pressure at 50 °C:**

0.7 hPa

- **Density and/or relative density**

- **Density at 20 °C:**

1.03 – 1.07 g/cm³

- **Relative density**

Not determined.

(Contd. on page 6)

Safety Data Sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 21.10.2025

Version number 1

Revision: 21.10.2025

Trade name: PermaCOAT PRO High Build Epoxy Floor Coating Hardener

(Contd. of page 5)

· Vapour density	Not determined.
· 9.2 Other information	
· Appearance:	
· Form:	Liquid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not self-igniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	Not applicable

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** At elevated temperatures, explosive vapour/air mixtures may be formed.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** Heat and static discharge.
- **10.5 Incompatible materials:**
 - Strong acids.
 - Strong bases.
 - Strong oxidising agents.
- **10.6 Hazardous decomposition products:**
 - Carbon monoxide and carbon dioxide
 - Nitrogen oxides (NOx)

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral	LD50	2,068.4 mg/kg
Inhalative	LC50/4 h	24.444 mg/l

CAS: 100-51-6 Benzyl alcohol

Oral	LD50	1,200 mg/kg (ATE)
		1,620 mg/kg (rat)

CAS: 1477-55-0 m-phenylenebis(methylamine)

Oral	LD50	930 mg/kg (rat)
Dermal	LD50	3,100 mg/kg (rat)
Inhalative	LC50/4 h	1.34 mg/l (rat)

CAS: 69-72-7 Salicylic acid

Oral	LD50	891 mg/kg (rat)
------	------	-----------------

- **Primary irritant effect:**
- **Skin corrosion/irritation**
 - Causes severe skin burns and eye damage.
- **Serious eye damage/irritation**
 - Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Additional toxicological information:** May cause sensitisation in susceptible persons.
- **11.2 Information on other hazards**

· Endocrine disrupting properties

CAS: 69-72-7 | Salicylic acid

List II; III

(Contd. on page 7)

Safety Data Sheet according to UK REACH (SI 2020/1577) as amended

Printing date 21.10.2025

Version number 1

Revision: 21.10.2025

Trade name: PermaCOAT PRO High Build Epoxy Floor Coating Hardener

(Contd. of page 6)

SECTION 12: Ecological information

· **12.1 Toxicity**

· Aquatic toxicity:	
CAS: 100-51-6 Benzyl alcohol	
EC50 (96 h)	230 mg/l (Bacteria)
EC50 (72 h)	770 mg/l (Algae)
CAS: 1477-55-0 m-phenylenebis(methylamine)	
EC50 (72 h)	20.3 mg/l (algae)

- **12.2 Persistence and degradability** Not easily biodegradable
- **12.3 Bioaccumulative potential** Contains components with the potential to bioaccumulate.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Recommended Hierarchy of Controls:

- Minimise waste;
- Reuse if not contaminated;
- Recycle, if possible; or
- Safe disposal (if all else fails).

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Used, degraded or contaminated product may be classified as hazardous waste. Anyone classifying hazardous waste and determining its fate must be qualified in accordance with state and international legislation.

· **Uncleaned packaging:**

· **Recommendation:**

Do not reuse empty containers - dispose of in accordance with the regulations issued by the appropriate local authorities.

Disposal must be made according to official regulations.

Containers, even those that are "empty," may contain residues that can develop flammable and/or hazardous vapours upon heating. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.

SECTION 14: Transport information

· 14.1 UN number or ID number	
· ADR, IMDG, IATA	UN1760
· 14.2 UN proper shipping name	
· ADR	UN1760 CORROSIVE LIQUID, N.O.S. (4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine))
· IMDG, IATA	CORROSIVE LIQUID, N.O.S. (4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine))

(Contd. on page 8)

Safety Data Sheet
according to UK REACH (SI 2020/1577) as amended

Printing date 21.10.2025

Version number 1

Revision: 21.10.2025

Trade name: PermaCOAT PRO High Build Epoxy Floor Coating Hardener

(Contd. of page 7)

<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) 	
<ul style="list-style-type: none"> · ADR 	
	
<ul style="list-style-type: none"> · Class · Label 	8 (C9) Corrosive substances. 8
<ul style="list-style-type: none"> · IMDG, IATA 	
	
<ul style="list-style-type: none"> · Class · Label 	8 Corrosive substances. 8
<ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA 	II
<ul style="list-style-type: none"> · 14.5 Environmental hazards: 	Not applicable.
<ul style="list-style-type: none"> · 14.6 Special precautions for user · Hazard identification number (Kemler code): · Emergency Action Code: · EMS Number: · Stowage Category · Stowage Code 	Warning: Corrosive substances. 80 2X F-A,S-B B SW2 Clear of living quarters.
<ul style="list-style-type: none"> · 14.7 Maritime transport in bulk according to IMO instruments 	Not applicable.
<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code 	
	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml 2 E
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	
	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
<ul style="list-style-type: none"> · UN "Model Regulation": 	UN 1760 CORROSIVE LIQUID, N.O.S. (4,4'-ISOPROPYLIDENEDIPHENOL, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE, REACTION PRODUCTS WITH 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE, M-PHENYLENEBIS(METHYLAMINE)), 8, II

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Poisons Act**

· **Regulated explosives precursors**
None of the ingredients are listed.

· **Regulated poisons**
None of the ingredients are listed.

· **Reportable explosives precursors**
None of the ingredients are listed.

(Contd. on page 9)

Safety Data Sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 21.10.2025

Version number 1

Revision: 21.10.2025

Trade name: PermaCOAT PRO High Build Epoxy Floor Coating Hardener

(Contd. of page 8)

· Reportable poisons

None of the ingredients are listed.

· Control Of Major Accident Hazards Regulations 2015 (COMAH)**· Named dangerous substances - ANNEX I** None of the ingredients are listed.**· 15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Relevant phrases

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H361d Suspected of damaging the unborn child.

H412 Harmful to aquatic life with long lasting effects.

· Training hints

This product should only be handled by workers who have received sufficient training in the safe handling and use of chemical products.

· Department issuing SDS: Product safety department.**· Abbreviations and acronyms:**

UK- REACH: The UK REACH etc. (Amendment etc.) (EU Exit) Regulations 2019 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals

GB- CLP: Retained GB CLP Regulation (EU) No. 1272/2008 as amended for Great Britain on the Classification, Labelling and Packaging of Chemicals.

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

Repr. 2: Reproductive toxicity – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3