

PermaSEAL Salt Inhibitor



Description

PermaSEAL Salt Inhibitor is a ready to use impregnation agent designed to treat and encapsulate destructive salts in masonry especially nitrates and chlorides. Breathability of the substrate is essentially maintained. Additional strengthening is achieved on friable masonry work through the deposit of silica gel.

Primarily designed for use as a primer and salt inhibitor for the PermaSEAL range of wet applied waterproof tanking and rendering systems. Including PermaSEAL Tanking and PermaSEAL Renovating Plaster.

Do not use on any surface that will be left exposed.

Benefits

- Ready to use product
- Deep penetration
- Maintains breathability
- Solvent free, low VOC

Preparation

All surfaces shall be clean, free of any previous surface coatings and free of dust and residue. On dry surfaces, to

assist the coating in fully wetting out the substrate, the background should be dampened with clean water. Before application the surface should be damp but not wet, any standing water must be removed.

Application

Evenly apply to the clean substrate with a course sprayer, masonry roller or brush at a rate of 0.2 – 0.25l /m² in a single coat. Do not allow to dry. After Salt Inhibitor has been absorbed but before the substrate has dried (15-30 mins) apply wet on wet subsequent coat of tanking or render over the entire area. Only apply enough Salt Inhibitor to an area that can be covered before it dries.

Application Notes

Do not apply to frost filled surfaces or when the temperature is 5°C and falling or 25°C and rising. Do not apply more than one coat. Do not re-apply once dry. Protect non-target surfaces from product due to staining. Splashes and contact with non-target surfaces should be removed immediately as it will be extremely difficult to remove once dry.

Technical & Packaging

Packaging:	5 litre containers.
Coverage:	4-5 m ² per litre dependent on porosity of surface.
Storage:	A storage temperature within a range of + 5 to + 25°C, protect from frost.
Shelf Life:	12 months in original unopened container, will be reduced once opened. Re-seal after use.
Tools:	Clean with warm soapy water.

Health & Safety

Salt Inhibitor is classified under current EC regulations.

Causes skin irritation. Causes eye irritation.

As with all chemicals we recommend goggles, nitrile gloves and impermeable coveralls are worn when handling this product.

Refer to material safety data sheet and product label for full Health and Safety data.

All Permagard products are of a high quality and subject to rigid quality control. The company, however, cannot govern the conditions of usage and application of its products and any warranty, written or implied covers material only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss, injury or patent infringement arising from its use.

Permagard Products Ltd
Units B2-B5, Worthy Road
Chittington Industrial Estate
Avonmouth
Bristol, BS11 0YB

+44 (0)117 982 3282
sales@permagard.co.uk