

Safety Data Sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 18.07.2025

Version number 1

Revision: 18.07.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **PermaSEAL PRO Liquid Gas Membrane**

Registration number Mixture

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product category PC0 Other

Application of the substance / the mixture Liquid Gas Membrane

Uses advised against None identified

1.3 Details of the supplier of the safety data sheet

Supplier:

Permagard Products Ltd
Chittening Industrial Estate
Avonmouth
Bristol BS11 0YB
England

Tel: 0117 82 3282

Email: sales@permagard.co.uk

Further information obtainable from: Product safety department.

1.4 Emergency telephone number:

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to GB-CLP The product is not classified, according to the GB CLP regulation.

2.2 Label elements

Labelling according to GB-CLP Not applicable

Hazard pictograms Not applicable

Signal word Not applicable

Hazard statements Not applicable

Additional information:

EUH208 Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

Contains biocidal active substance(s): 1,2-benzisothiazol-3(2H)-one

The Detergents (Amendment) (EU Exit) Regulations 2020 / Labelling for contents

preservation agents (BENZISOTHIAZOLINONE)

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 2634-33-5 EINECS: 220-120-9 Index number: 613-088-00-6 Reg.nr.: 01-2120761540-60-XXXX	1,2-benzisothiazol-3(2H)-one ⚠ Acute Tox. 2, H330; ⚠ Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1A, H317 ATE: LD50 oral: 450 mg/kg LC50/4 h inhalative: 0.21 mg/l Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.036 %	< 0.025%
---	---	----------

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 2)

Safety Data Sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 18.07.2025

Version number 1

Revision: 18.07.2025

Trade name: PermaSEAL PRO Liquid Gas Membrane

(Contd. of page 1)

- If skin irritation continues, consult a doctor.
- **After eye contact:**
Check for and remove any contact lenses.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
Rinse out mouth and then drink plenty of water.
If symptoms persist consult doctor.
- **Information for doctor:** Treat symptomatically and supportively.
- **4.2 Most important symptoms and effects, both acute and delayed** Allergic reactions
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Use fire extinguishing methods suitable to surrounding conditions.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
In case of fire, the following can be released:
Carbon monoxide and carbon dioxide
Sulphur Oxides (SO_x)
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.
Wear fully protective suit.
- **Additional information**
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Particular danger of slipping on leaked/spilled product.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow to penetrate the ground/soil.
Do not allow product to reach sewage system or any water course in the undiluted form.
- **6.3 Methods and material for containment and cleaning up:**
Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
Avoid direct contact (skin/eye contact, ingestion and/or inhalation of fume/mist/dust) with the product in the undiluted form.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Prevent any seepage into the ground.
- **Information about storage in one common storage facility:** Store away from oxidising agents.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Storage class:** 10
- **7.3 Specific end use(s)** No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 18.07.2025

Version number 1

Revision: 18.07.2025

Trade name: PermaSEAL PRO Liquid Gas Membrane

(Contd. of page 2)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs

CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one

Dermal	Long-term systemic effects	345 µg/kg bw/day (general population) 966 µg/kg bw/day (worker)
Inhalative	Long-term systemic effects	1.2 mg/m ³ (general population) 6.81 mg/m ³ (worker)

PNECs

CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one

Freshwater	4.03 µg/L
Freshwater - Intermittent releases	1.1 µg/L
Marine water	403 ng/L
Marine Water - Intermittent releases	110 ng/L
Sewage Treatment Plant	1.03 mg/L
Sediment (freshwater)	49.9 µg/kg
Sediment (marine water)	4.99 µg/kg
Soil	3 mg/kg

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Do not inhale gases / fumes / aerosols.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.

Hand protection



Protective gloves.

Use gloves tested and approved under appropriate government standards such as NIOSH (US) or EN374 (EU).

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Safety glasses with side-shields conforming to EN166.

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Body protection:



Protective work clothing

Body protection must be chosen depending on product properties, activity and possible exposure.

Environmental exposure controls Do not allow to enter drains, sewers or watercourses.

(Contd. on page 4)

Safety Data Sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 18.07.2025

Version number 1

Revision: 18.07.2025

Trade name: PermaSEAL PRO Liquid Gas Membrane

(Contd. of page 3)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state	Liquid
Colour:	Green
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	Undetermined.
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	Not applicable.
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
Solubility	
water:	Fully miscible.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.

9.2 Other information

Appearance:	
Form:	Fluid
Important information on protection of health and environment, and on safety.	
Ignition temperature:	Product is not self-igniting.
Explosive properties:	Product does not present an explosion hazard.
Change in condition	
Evaporation rate	Not determined.

Information with regard to physical hazard classes

Explosives	Not applicable
Flammable gases	Not applicable
Aerosols	Not applicable
Oxidising gases	Not applicable
Gases under pressure	Not applicable
Flammable liquids	Not applicable
Flammable solids	Not applicable
Self-reactive substances and mixtures	Not applicable
Pyrophoric liquids	Not applicable
Pyrophoric solids	Not applicable
Self-heating substances and mixtures	Not applicable
Substances and mixtures, which emit flammable gases in contact with water	Not applicable
Oxidising liquids	Not applicable
Oxidising solids	Not applicable
Organic peroxides	Not applicable
Corrosive to metals	Not applicable
Desensitised explosives	Not applicable

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid Heat and static discharge.
- 10.5 Incompatible materials:
 - Strong acids.
 - Strong bases.

(Contd. on page 5)

Safety Data Sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 18.07.2025

Version number 1

Revision: 18.07.2025

Trade name: PermaSEAL PRO Liquid Gas Membrane

(Contd. of page 4)

Strong oxidising agents.

10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Sulphur oxides (SOx)

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one

Oral LD50 450 mg/kg (ATE)

Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Subacute to chronic toxicity: Prolonged or repeated skin contact may irritate and cause dermatitis.

Additional toxicological information: Repeated or prolonged skin contact may induce sensitisation.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients are listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one

EC50 (96 h) 3 mg/l (Bacteria)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Recommended Hierarchy of Controls:

- Minimise waste;

- Reuse if not contaminated;

- Recycle, if possible; or

- Safe disposal (if all else fails).

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Used, degraded or contaminated product may be classified as hazardous waste. Anyone classifying hazardous waste and determining its fate must be qualified in accordance with state and international legislation.

Uncleaned packaging:

Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Disposal must be made according to official regulations.

(Contd. on page 6)

Safety Data Sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 18.07.2025

Version number 1

Revision: 18.07.2025

Trade name: PermaSEAL PRO Liquid Gas Membrane

(Contd. of page 5)

Containers, even those that are "empty," may contain residues that can develop flammable and/or hazardous vapours upon heating.

Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.

Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

14.1 UN number or ID number - ADR/RID/ADN, IMDG, IATA	Not applicable
14.2 UN proper shipping name - ADR/RID/ADN, IMDG, IATA	Not applicable
14.3 Transport hazard class(es) - ADR/RID/ADN, ADN, IMDG, IATA - Class	Not applicable
14.4 Packing group - ADR/RID/ADN, IMDG, IATA	Not applicable
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
UN "Model Regulation":	Not applicable

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Poisons Act

Regulated explosives precursors	None of the ingredients are listed.
Regulated poisons	None of the ingredients are listed.
Reportable explosives precursors	None of the ingredients are listed.
Reportable poisons	None of the ingredients are listed.

- Control Of Major Accident Hazards Regulations 2015 (COMAH)

- Named dangerous substances - ANNEX I None of the ingredients are listed.

- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

- Relevant phrases

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

- Department issuing SDS: Product safety department.

- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 7)

Safety Data Sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 18.07.2025

Version number 1

Revision: 18.07.2025

Trade name: PermaSEAL PRO Liquid Gas Membrane

(Contd. of page 6)

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 2: Acute toxicity – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1