



## Declaration of performance

according Annex III of the Regulation (EU) No 305/2011  
amended by Commissions delegated Regulation (EU) No 574/2014

## Declaration of conformity

according Statutory Instruments (UK) 2019 No. 465; 2020 No. 1359

|                                                |                                                                                                                                                                                                   |
|------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| for the product                                | MB 2K                                                                                                                                                                                             |
| No.                                            | GBI-P 73-3                                                                                                                                                                                        |
| Unique identification code of the product-type | 3014                                                                                                                                                                                              |
| Intended use/es                                | Liquid applied water impermeable product for external installations on walls and floors, beneath ceramic tiling (bonded with Remmers FL fix C2 adhesives in accordance with EN 12004)             |
| Manufacturer                                   | Remmers GmbH<br>Bernhard-Remmers-Str. 13<br>49624 Lönigen (DE)<br><br><b>Distributor UKCA:</b><br>Remmers (UK) Limited<br>1 & 2 Garden Suites, Coleshill Manor Campus, Birmingham<br>B46 1DL (GB) |
| System/s of AVCP                               | <b>System 3</b> (for internal and external uses)                                                                                                                                                  |
| Harmonised standard                            | EN 14891:2012-07                                                                                                                                                                                  |
| Notified body/ies                              | Materialprüfanstalt (MPA) Braunschweig<br>Beethovenstr. 52, 38106 Braunschweig<br>Notified Body No 0761                                                                                           |

Certificate of conformity of the factory production control test report no. **1201/532/18e**



Declared performance/s:

| Essential characteristic                                | Performance             | System of assessment and verification of constancy of performance | Harmonised technical specification |
|---------------------------------------------------------|-------------------------|-------------------------------------------------------------------|------------------------------------|
| Initial tensile adhesion strength                       | ≥ 0,5 N/mm <sup>2</sup> | System 3                                                          | EN 14891: 2017-07                  |
| Tensile adhesion strength after water contact           | ≥ 0,5 N/mm <sup>2</sup> |                                                                   |                                    |
| Tensile adhesion strength after heat ageing             | ≥ 0,5 N/mm <sup>2</sup> |                                                                   |                                    |
| Tensile adhesion strength after freeze-thaw cycles      | ≥ 0,5 N/mm <sup>2</sup> |                                                                   |                                    |
| Tensile adhesion strength after contact with lime water | ≥ 0,5 N/mm <sup>2</sup> |                                                                   |                                    |
| Waterproofing                                           | no penetration          |                                                                   |                                    |
| Crack bridging ability                                  | ≥ 0,75 mm               |                                                                   |                                    |
| Crack bridging ability at low temperature               | ≥ 0,75 mm bei -5°C      |                                                                   |                                    |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance & conformity is issued, in accordance with Regulation (EU) No 305/2011 and Statutory Instruments (UK) 2019 No. 465; 2020 No. 1359 under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

Remmers GmbH  
R & D Building protection III

i.V. Dr. Magnus Greiwe  
(Department manager)

i.A. Christian Jaskulke  
(Laboratory staff)

The declaration of performance was created electronically and is also valid without signature.

Löningen, 2024-02-01